View NSN Online: https://aerobasegroup.ae/nsn/6850-00-935-9795

ENGELHARD CORP., CHEMICAL CATALYSTS GROUP -- DESICCITE 25 -- 6850-00-935-9795

Product ID:DESICCITE 25 MSDS Date:06/08/1998 FSC:6850 NIIN:00-935-9795 Status Code:A MSDS Number: CHVWM === Responsible Party === Company Name: ENGELHARD CORP., CHEMICAL CATALYSTS GROUP Address:600 E. MCDOWELL ROAD **City:JACKSON** State:MS ZIP:39204 Country:US Info Phone Num:800-458-8650 OR 800-654-4039 Emergency Phone Num:800-458-8650/800-424-9300(CHEMTREC) CAGE:0NH81 === Contractor Identification === Company Name: ENGELHARD CORP Address:600 E. MCDOWELL ROAD Box:City:JACKSON State:MS ZIP:39204 Country:US Phone:800-458-6850 / 601-948-3966 CAGE:0NH81 Ingred Name: BENTONITE (INCLUDES INGREDIENTS 2 AND 3.) CAS:1302-78-9 RTECS #:CT9450000 Fraction by Wt: SEE 2&3%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 (DU

ST) ACGIH TLV:5 MG/M3 (DUST)

Ingred Name:SILICA, CRYSTALLINE - QUARTZ CAS:14808-60-7 RTECS #:VV7330000 Fraction by Wt: 1 - 3% Other REC Limits:NONE RECOMMENDED OSHA PEL:SEE TABLE Z-3 ACGIH TLV:0.1 MG/M3 RDUST;9495

Ingred Name:ALUMINUM SILICATE, CAS:12141-46-7 Fraction by Wt: 97% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT KNOWN. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports o

f Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY TRACT. ACUTE- EYES:MAY CAUSE IRRITATION & DISCOMFORT. SKIN:MAY CAUSE IRRITATION, REDNESS. INHALE:CAUSES RESPIRATORY TRACT IRRITATION & MAY CAUSE DISABLING, PROGRES SIVE PULMONARY FIBROSIS (SILICOSIS). ORAL:NO ADVERSE EFFECTS EXPECTED. CHRONIC- INHALATION MAY CAUSE LUNG DAMAGE.

Explanation of Carcinogenicity:CONTAINS CRYSTALLINE SILICA (QUARTZ). Effects of Over

exposure:IRRITATION, COUGH, DYSPNEA, WHEEZING, CHEST DISCOMFORT

Medical Cond Aggravated by Exposure:BREATHING OF DUST MAY AGGRAVATE EXISTING MEDICAL CONDITIONS SUCH AS RESPIRATORY AILMENTS.

First Aid:GET MEDICAL CARE IF SYMPTOMS PERSIST. EYES: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN: FLUSH WITH PLENTY OF WATER. INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEED ED. SWAL

LOWED: IF LARGE QUANTITIES INGESTED, CONTACT PHYSICIAN.	
NOTE TO PHYSICAN: DESICCANT GENERATES HEAT AS IT ADSORBS	WATER. USED
PRODUCT CAN CONTAIN HAZARDOUS CHEMICALS.	

Flash Point:NONE

Extinguishing Media:UNUSED MATERIAL WILL NOT BURN. USE WATER, CARBON DIOXIDE OR FOAM FOR SURROUNDING FIRE.

Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. USED MATERIAL MAY PR ODUCE

HAZARDOUS DECOMPOSITION PRODUCTS. Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. CAREFULLY SWEEP OR VACUUM THE SPILL AREA. COLLECT AND PLACE THE SPILLED MATERIAL IN A WASTE DISPOSAL CONTAINER. AVOID DUSTING. Neutralizing Agent:NOT RELEVANT

Handling and Storage Precautions:STORE IN DRY PLACE, IN TIGHTL Y CLOSED

CONTAINER, AWAY FROM INCOMPATIBLE MATERIALS. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:WEAR GOGGLES IF DUST CAUSES EYE DISCOMFORT. WEAR A PROPERLY FITTED NIOSH-APPROVED DUST RESPIRATOR FOR DUSTY CONDITIONS. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. AVOID CONTACT WIT H EYES. OPEN CONTAINER SLOWLY.

Respiratory Protection: IF ENGINEERING CONTROLS ARE INADEQUATE TO CONTRO

L DUST CONCENTRATIONS TO AN ACCEPTABLE LEVEL, A NIOSH-APPROVED DUST RESPIRATOR SHOULD BE WORN IF NEEDED. IF RESPIRATORS ARE USED, A PROGRAM SHOULD BE IN STITUTED TO COMPLY WITH OSHA.

Ventilation: USE GENERAL OR LOCAL EXHAUST VENTILATION TO MEET TLV REQUIREMENTS.

Protective Gloves:COTTON/RUBBER/LATEX FOR REPEATED CONTACT Eye Protection:SAFETY GOGGLES FOR DUSTY CONDITIONS Other Protective Equipment:LONG SLEEVE WORK CLOTHING, EYE WASH FOUNTAIN Work Hygienic Practices:WASH THOROUGHLY BEFORE EATING, DRINKING OR SMOKING. VACUUM UP ANY DUST. LAUNDER CLOTHING BEFORE REUSE. Supplemental Safety and Health

HCC:N1 NRC/State Lic Num:NOT RELEVANT Melt/Freeze Pt:M.P/F.P Text:NOT KNOWN Spec Gravity:2.4 Viscosity:NOT RELEVANT Evaporation Rate & amp; Reference:NOT RELEVANT Solubility in Water:NEGLIGIBLE Appearance and Odor:GREY TO OFF-WHITE GRANULES; ODORLESS

Stability Indicator/Materials to Avoid:YES STRONG ALKALI, STRONG OXIDIZING AGENTS Stability Condition to Avoid:MOISTURE Hazardous Decomposition Products:NONE

Waste Disposal Methods:DISCARD ANY PRODUCT (INCLUDING ANY RETAINED MATERIALS OF USE), DISPOSABLE CONTAINERS OR LINER IN AN ENVIRONMENTALLY ACCEPTABLE MANNER, IN FULL COMPLIANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with

this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.