View NSN Online: https://aerobasegroup.ae/nsn/9525-00-529-0442

BROOKFIELD WIRE CO INC -- STAINLESS (300 & 400 SERIES),NI,NI-CU AND NI-CR-FE ALLOYS --9525-00-529-0442

Product ID:STAINLESS (300 & 400 SERIES), NI, NI-CU AND NI-CR-FE ALLOYS MSDS Date:10/13/1997 FSC:9525 NIIN:00-529-0442 Status Code:A **MSDS Number: CHYYQ** === Responsible Party === Company Name: BROOKFIELD WIRE CO INC Box:248 City:BROOKFIELD State:MA ZIP:01506-0248 Co untry:US Info Phone Num:617-867-6474 Emergency Phone Num:617-867-6474 CAGE:94129 === Contractor Identification === Company Name: BROOKFIELD WIRE CO INC Box:City:BROOKFIELD State:MA ZIP:01506-0248 Country:US Phone:617-867-6474 CAGE:94129 Ingred Name:CHROMIUM (SARA 313) (CERCLA) CAS:7440-47-3 RTECS #:GB4200000 Other REC Limits:NONE RECOMMENDED OSHA PEL:1 MG/M3 ACGIH TLV:0.5 MG/M3; 9596 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB Ingred N

ame:COBALT (SARA 313) CAS:7440-48-4 RTECS #:GF8750000 Other REC Limits:NONE RECOMMENDED OSHA PEL:0.1 MG/M3 ACGIH TLV:0.02 MG/M3; A3; 9596

Ingred Name:COPPER (SARA 313) (CERCLA) CAS:7440-50-8 RTECS #:GL5325000 Other REC Limits:NONE RECOMMENDED OSHA PEL:0.1MG/M3 FUME/1 DUST ACGIH TLV:0.2 MG/M3 FUME; 9596 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:IRON CAS:7439-89-6 RTECS #:NO4565500 Other REC Limits:NONE RECOMMENDED OSHA PEL:10 MG/M3 (TDUST) ACGIH TLV:5 MG/M3 (OXIDE FUME)

Ingred Name :MANGANESE (SARA 313) CAS:7439-96-5 RTECS #:OO9275000 Other REC Limits:NONE RECOMMENDED OSHA PEL:C, 5 MG/M3 (FUME) ACGIH TLV:0.2 MG/M3; 9596

Ingred Name:MOLYBDENUM CAS:7439-98-7 RTECS #:QA4680000 Other REC Limits:NONE RECOMMENDED OSHA PEL:10 PPM. ACGIH TLV:10 PPM.

Ingred Name:NICKEL (SARA 313) (CERCLA) CAS:7440-02-0 RTECS #:QR5950000 Other REC Limits:NONE RECOMMENDED OSHA PEL:1 MG/M3 ACGIH TLV:1 MG/M3; 9596

Ingred Name:SILICON CAS:7440-21-3 RTECS #:VW0400000 Other REC Limits:NONE RECOMMENDED LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT RELEVANT.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS: EYES, SKIN, LUNG, CNS.
ACUTE- NO HAZARD AS WIRE. DUST CAN IRRITATE EYES & RESPIRATORY
TRACT. FUMES CAN CAUSE IRRITATION, CNS EFFECTS. MAY CAUSE METAL
FUME FEVER. ARC RAYS CAN INJURE EYE S & BURN SKIN. ELECTRIC SHOCK
CAN KILL.INGESTION IS UNLIKELY. CHRONIC- NEUROLOGICAL DAMAGE, LUNG
FIBROSIS & DAMAGE.
Explanation of Carcinogenicity:CONTAINS NICKEL AND CHROMIUM.
Effects of Overexposure:FUMES OR DUST: IRRITATION, COUGH, WHEEZING AND
SHORTNESS OF BREATH, DECREASED PULMONARY FUNCTION, HEADACHE, NAUSEA, VOMITING, WEAKNESS, CONVULSION
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN
DISORDERS, EYE PROBLEMS OR IM

PAIRED RESPIRATORY FUNCTION MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EMPLOY FIRST AID TECHNIQUE RECOMMENDED BY RED CROSS. IF BREATHING IS DIFFICULT, PROVIDE OXYGEN/CPR. FOR ELECTRIC SHOCK, DISCONNECT POWER. FOR ARC BURNS, APPL Y COLD, CLEAN COMPRESSES & CALL A PHYSICIAN. IF EYE CONTACT, FLUSH WITH WATER FOR 15 MINUTES. IF SKIN CONTACT, WAS H

WITH SOAP & WATER.

Flash Point:NONE Lower Limits:NOT RELEVANT

Upper Limits:NOT RELEVANT

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL FOR SURROUNDING FIRE. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures: TREAT AS A METALLIC FIRE. WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard: MAY FORM TOXIC FUMES.

WELDING ARC AND SPARKS CAN IGNITE COMBUSTIBLES AND FLAMMABLES.

Spill Release Procedures: CLEAN UP ANY GRINDING DUST OR WASTE RESIDUE AND PLACE IN SUITABLE CONTAINER FOR DISPOSAL. AVOID GENERATING AIRBORNE DUST. AVOID INHALATION OF DUST. Neutralizing Agent: NOT RELEVANT

Handling and Storage Precautions:STORE IN A DRY PLACE AWAY FROM INCOMPATIBL

ES. KEEP OUT OF REACH OF CHILDREN.

Other Precautions: AVOID INHALATION AND EXCESSIVE SKIN CONTACT. AVOID BREATHING OF FUMES. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING AND DRINKING. REMOVE CONTAMINATED CLOTHING. LAUND ER BEFORE REUSE.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:USE NIOSH APPROVED SUPPLIED AIR RESPIRATORY PROTECTION OR RESPIRABLE FUME RESPIRATOR WHEN WELDING, BRAZING OR SOLDER

ING IN CONFINED SPACE OR WHERE LOCAL EXHAUST VENTILATION DOES NOT KEEP EXPOSURE BELO W TLV.

Ventilation:USE GENERAL & LOCAL EXHAUST AT FLAME TO KEEP FUMES AND GASES BELOW TLV'S IN THE WORKER'S BREATHING ZONE & GENERAL AREA. Protective Gloves:WELDER'S GLOVE

Eye Protection: HELMET/FACE SHIELD WITH FILTER LENS

Other Protective Equipment:EYE WASH STATION, SAFETY SHOWER, APRON (ALUMINIZED), EAR PROTECTION (TO AVOID EXCESSIVE NOISE) Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRAC TICES AND

RECOMMENDED PROCEDURES.

Supplemental Safety and Health

HCC:N1

NRC/State Lic Num:NOT RELEVANT Viscosity:NOT RELEVANT Evaporation Rate & amp; Reference:NOT RELEVANT Solubility in Water:INSOLUBLE Appearance and Odor:SOLID WIRE (ROUND OR FLATTENED)

Stability Indicator/Materials to Avoid:YES STRONG ACIDS Stability Condition to Avoid:WELDING ARCS Haz ardous Decomposition Products:WELDING FUMES (OXIDES OF METAL BEING WELD) AND GASES SUCH AS OZONE, CARBON MONOXIDE, CARBON DIOXIDE, NITROGEN OXIDES...

Waste Disposal Methods:DISPOSED OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. PREVENT WASTE FROM CONTAMINATING ENVIRONMENT.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of th e Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.