

SHERWIN-WILLIAMS CO -- 1604 SHADOW GRAY, INDUSTRIAL MAINTENANCE (SUPDAT) --
8010-00-055-4748

===== Product Identification =====

Product ID:1604 SHADOW GRAY, INDUSTRIAL MAINTENANCE (SUPDAT)

MSDS Date:09/01/1996

FSC:8010

NIIN:00-055-4748

Status Code:A

MSDS Number: CJCKW

=== Responsible Party ===

Company Name:SHERWIN-WILLIAMS CO

Address:31500 SOLON RD

City:SOLON

State:OH

ZIP:44139

Country:US

Info Ph

one Num:800-777-2966

Emergency Phone Num:215-566-2917

CAGE:DO642

=== Contractor Identification ===

Company Name:SHERWIN-WILLIAMS CO THE SPECIALTY DIV.

Address:6830 COCHRAN RD.

Box:6709

City:SOLON

State:OH

ZIP:44139-3908

Phone:216-292-7400

CAGE:DO642

Company Name:SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.

Address:26300 FARGO AVENUE

Box:City:BEDFORD HEIGHTS

State:OH

ZIP:44146

Country:US

Phone:216-292-7400 OR 216-595-8634

CAGE:09800

===== Composition/Information on Ingredients =====

==

Ingred Name:PROPANE. VP: 760.
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 14%
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN

Ingred Name:BUTANE. VP: 760.
CAS:106-97-8
RTECS #:EJ4200000
Fraction by Wt: 6%
OSHA PEL:800 PPM
ACGIH TLV:800 PPM

Ingred Name:ETHYLBENZENE (SARA 313). VP: 7.1.
CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: 2%
OSHA PEL:100 PPM
ACGIH TLV:100 PPM; 125 STEL
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENE (SARA 313) (CERCLA). VP: 5.9.
CAS:1330-20-7
RTECS #:ZE
2100000
Fraction by Wt: 9%
OSHA PEL:100 PPM
ACGIH TLV:100 PPM; 150 STEL
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA 313) (CERCLA). VP: 180.
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: 39%
OSHA PEL:1000 PPM
ACGIH TLV:750 PPM; 1000 STEL
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (SARA 313) (CERCLA). VP: 70.
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 4%
OSHA PEL:200 PPM
ACGIH TLV:200 PPM; 300 STEL
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000

LBS

Ingred Name:METHYLISOBUTYL KETONE (SARA 313) (CERCLA). VP: 18.

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 3%

OSHA PEL:100 PPM

ACGIH TLV:50 PPM; 75 STEL

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:1-METHOXY-2-PROPANOL ACETATE. VP: 1.8.

CAS:108-65-6

RTECS #:AI8925000

Fraction by Wt: 7%

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 3%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST

Ingred Name:VOLATILE ORGANIC COMP

OUND BY WEIGHT PER BAAQMD RULE 49:

45.4%; VOC TOTAL: 2.98 LBS/GAL.

RTECS #:9999999VO

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:EFTS OF OVEREXP: ATTAINABLE IN WORKPLACE. RPTS HAVE ASSOC

RPTD & PRLNGD OVEREXP TO SOLVS W/PERM BRAIN & NERVOUS (ING 12)

RTECS #:9999999ZZ

Ingred Name:ING 11: SYS DMG. WARNING:THESE PRODS CNTN CHEM/S KNOWN TO

STATE OF CA TO CAUSE CANCER & BIRTH DEFECTS/OTHER REPRO HARM.

RTECS #:9999999ZZ

Ingred Name:WASTE DISP METH: NOT INCINERATE. DEPRESSURIZE CNTNR.

D

ISPOSE OF I/A/W FED, STATE & LOCAL REGS REGARDING POLLUTION.
RTECS #:9999999ZZ

Inged Name:HNDLG/STOR PRECS: VENTD - DO NOT SMOKE - EXTING ALL FLAMES,
PILOT LIGHTS & HEATERS - TURN OFF STOVES, ELEC TOOLS(ING 15)
RTECS #:9999999ZZ

Inged Name:ING 14:& APPLIANCES & ANY OTHER IGNIT SOURCES. CONSULT NFPA
CODE. USE APPRVD BONDING & GROUNDING PROCS. CONTENTS(ING 16)
RTECS #:9999999ZZ

Inged Name:ING 15: UNDER PRESS. DO NOT PUNCTURE, INCIN OR EXPOSE TO
TEMPS >120F. HEAT FROM SUNLIGHT, RA
DIA, STOVES, HOT (ING 17)
RTECS #:9999999ZZ

Inged Name:ING 16: WATER & OTHER HEAT SOURCES COULD CAUSE CNTNR TO
BURST. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.
RTECS #:9999999ZZ

Inged Name:OTHER PRECS: LISTED "AS DUST" IN INGRED SECTION) WHICH MAY
BE PRESENT AT HAZ LEVELS ONLY DURING SANDING/ABRADING(ING 19)
RTECS #:9999999ZZ

Inged Name:ING 18: OF DRIED FILM. IF NO SPECIFIC DUSTS LISTED, APPLIC
LIMS FOR NUISANCE DUSTS ARE ACGIH TLV 10 MG/M3 (ING 20)
RTECS #:9999999
ZZ

Inged Name:ING 19: (TDUST), OSHA PEL 15 MG/M3 (TDUST), 5 MG/M3
(RESPIRABLE FRACTION).
RTECS #:9999999ZZ

Inged Name:RESP PROT: FROM THIS PRODUCT, UNDERLYING PAINT OR THE
ABRASIVE.
RTECS #:9999999ZZ

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: IRRIT OF EYES, SKI

N & RESP SYS.

MAY CAUSE NERVOUS SYS DEPRESS. EXTREME OVEREXP MAY RSLT IN UNCON & POSS DEATH. HDCH, DIZZ, NAUS & LOSS OF COORD ARE INDICATIONS OF EXCESSIVE EXPOS TO VAPS OR SPR AY MISTS. REDNESS & ITCHING OR BURNING SENSATION MAY INDICATE EYE OR EXCESSIVE SKIN EXPOS. CHRONIC: (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HLTH HAZ: PRLNGD OVEREXP TO SOLV INGREDIENTS LISTED MAY CAUSE ADVERSE EFTS TO LIVER, URINARY, BLOOD-FORMING, CARDI

OVASCULAR & REPRO SYS. METHYL ETHYL KETONE MAY INCR NERVOUS SYS EFTS OF OTHER SOLVS. RATS EXPOSED TO TITANIUM DIOXIDE DUST AT 250MG/M3 DEVELOPED LUNG CANCER, HOWEVER, SUCH EXPOS LEVELS ARE NOT (ING 11)

Medical Cond Aggravated by Exposure:NONE GENERALLY RECOGNIZED.

=====
===== First Aid Measures =====

First Aid:INHAL: IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE BRTHG. KEEP WARM & QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY W/SOAP & WATER. REMOV

E CONTAM CLTHG & LAUNDER BEFORE REUSE. EYES: FLUSH EYES W/LARGE AMT S OF WATER FOR AT LEAST 15 MIN. GET MEDATTN. INGEST: NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON. DO NOT INDUCE VOMITING. GIVE CONSCIOUS PATIENT SEVERAL GLASSES OF WATER. SEEK MED ATTN.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point: