View NSN Online: https://aerobasegroup.com/nsn/8040-00-104-9323

## TECHNICAL WIRE PRODUCTS INC -- CONDUCTIVE ADHESIVE CON RTV 1, 72-00002

\_\_\_\_\_\_

MSDS Safety Information

\_\_\_\_\_

FSC: 8040

NIIN: 00-104-9323 MSDS Date: 06/01/1991 MSDS Num: CJCVW

Product ID: CONDUCTIVE ADHESIVE CON RTV 1, 72-00002

MFN: 02

Responsible Party Cage: 53217

Name: TECHNICAL WIRE PRODUCTS INC

Address: 129 DERMODY ST

City

: CRANFORD NJ 07016

Info Phone Number: 908-272-5500

Emergency Phone Number: 908-272-5500

Proprietary Ind: Y Review Ind: Y Published: Y

\_\_\_\_\_\_

Contractor Summary

\_\_\_\_\_

Cage: 53217

Name: TECHNICAL WIRE PRODUCTS INC DBA TECKNIT INC

Address: 320 N NOPAL ST

City: SANTA BARBARA CA 93103-3225

Phone: UNKNOWN

Cage: 07700

Name: TECHNICAL WIRE PRODUCTS INC, DBA. TECKNIT

Address: 129 DERMODY ST

City: CRANFORD

NJ 07016

Phone: 908-272-5500

\_\_\_\_\_

Item Description Information

\_\_\_\_\_\_

Item Manager: GSA Item Name: ADHESIVE

Unit of Issue: TU

Quantitative Expression: 00000000002OZ

UI Container Qty: 0

\_\_\_\_\_

Ingredients

\_\_\_\_\_\_

Name: \*\*\* PROPRIETARY \*\*\*

-----

\_\_\_\_\_\_

\_\_\_\_\_\_

Health Hazards Data

\_\_\_\_\_

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Route Of Entry Inds - Inhalation: YES

Skin: YES Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO OSHA: NO

Effects of Exposure: PROLONGED OR REPEATED ABSORPTION OF SILVER COMPOUNDS CAN LEAD TO GRAYISH-BLUE DISCOLORATION OF SKIN KNOWN AS ARGYROSIS. RELEASE OF ACETIC ACID DURING CURE MAY CAUSE RESPIRATORY AILMENTS.

Explanation Of Carcinog enicity: NOT RELEVANT.

Signs And Symptions Of Overexposure: INGEST: MAY CAUSE GASTRIC DISTRESS. SKIN: UNCURED PROD WILL IRRIT LIPS, GUMS, TONGUE & DESTRICT OF AMP;/OR

PRLNGD SKIN CONT W/SILVER CMPDS MAY CAUSE GRAYISH-BLUE DISCOLORATION OF SKIN.

INHAL: CAUSES MOD RESP IRRIT. RPTD & DESCRIPTION OF ACETIC ACID LIBERATED DURING CURE MAY CAUSE RESP AILMENTS. EYE: UNCURED (SUPDAT)

Medical Cond Aggravated By Exposure: NONE KNOWN.

First Aid: INGESTION: RINSE MOUTH WITH WATER SEVER

AL TIMES. SKIN: REMOVE

COMPLETELY WITH DRY CLOTH OR PAPER TOWEL, BEFORE WASHING WITH DETERGENT AND WATER. INHALATION: MOVE PERSON TO FRESH AIR. EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

\_\_\_\_\_\_

Handling and Disposal

Spill Release Procedures: WIPE OR SOAK UP WITH ABSORBENT MATERIAL AND PUT INTO CONTAINER FOR

DISPOSAL. WASH WALKING SURFACES WITH DETERGENT AND WATER TO REDUCE SLIPPING HAZARD.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATION.

Handling And Storage Precautions: USE CAUTION COMBUSTIBLE MATERIAL.

Other Precautions: AVOID CONT W/SKIN & DESCRIPTION OF CONT LENSES MUST NOT HNDL LENSES UNTIL ALL SEALANT HAS BEEN CLEANED FROM FINGERTIPS. RESIDUAL SILICONE WILL TRANSFER TO LEN

SES & SEV EYE IRRIT. PROD RELS ACET IC ACID DURING APPLIC & SEV EYE IRRIT. PROD RELS ACET IC ACID DURING APPLIC & SEV EYE IRRIT. PROD RELS ACET IC ACID DURING APPLIC & SEV EYE IRRIT. PROD RELS ACET IC ACID DURING APPLIC & SEV EYE IRRIT. PROD RELS ACET IC ACID DURING APPLIC & SEV EYE IRRIT. PROD RELS ACET IC ACID DURING APPLIC & SEV EYE IRRIT. PROD RELS ACET IC ACID DURING APPLIC & SEV EYE IRRIT. PROD RELS ACET IC ACID DURING APPLIC & SEV EYE IRRIT. PROD RELS ACET IC ACID DURING APPLIC & SEV EYE IRRIT. PROD RELS ACET IC ACID DURING APPLIC & SEV EYE IRRIT. PROD RELS ACET IC ACID DURING APPLIC & SEV EYE IRRIT. PROD RELS ACET IC ACID DURING APPLIC & SEV EYE IRRIT. PROD RELS ACET IC ACID DURING APPLIC & SEV EYE IRRIT. PROD RELS ACET IC ACID DURING APPLIC & SEV EYE IRRIT. PROD RELS ACET IC ACID DURING APPLIC & SEV EYE IRRIT. PROD RELS ACET IC ACID DURING APPLIC & SEV EYE IRRIT. PROD RELS ACET IC ACID DURING APPLIC & SEV EYE IRRIT.

\_\_\_\_\_

Fire and Explosion Hazard Information

\_\_\_\_\_

Flash Point Method: PMCC Flash Point Text: 162F,72C

Extinguishing Media: ALL STANDARD FIRE FIGHTING MEDIA.

Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE

EQUIPMENT (FP N). EVACUATE ALL NON-ESSENTIAL PERSONNEL.

Unusual Fire/Exp

losion Hazard: MATERIAL IS COMBUST, FOLLOW APPROP PROCS. ALSO,

SILVER DUST IS MODERATELY FLAMMABLE WHEN EXPOSED TO FLAME OR CHEMICAL

OXIDIZERS. SOME DECOMP PRODS MAY BE TOXIC.

\_\_\_\_\_

**Control Measures** 

\_\_\_\_\_\_

Respiratory Protection: NONE REQUIRED UNDER NORMAL WORK CONDITIONS. HOWEVER IF LARGE QUANTITIES ARE SPILLED OR IN CASE OF FIRE, USE NIOSH/MSHA APPROVED

SCBA.

Ventilation: LOCAL AND MECHA

NICAL RECOMMENDED.

Protective Gloves: CLOTH GLOVES.

Eye Protection: CHEMICAL SAFETY GOGGLES (FP N).

Other Protective Equipment: NONE KNOWN.

Work Hygienic Practices: FOLLOW STD WORK/HYGIENIC PRACTS. WASH HANDS THORO W/SOAP & WATER AFTER HNDLG, BEFORE EATING/SMOKING, & AT END OF SHIFT. Supplemental Safety and Health: EFFECTS OF OVEREXPOSURE: PRODUCT CONTACT

IRRITATES EYES. OTHER PRECAUTIONS: USE MECHANICAL VENTILATION TO STAY BELOW

TLV OF 10 PPM. ACETIC ACID. UNCURED PRODUCT CONTACT WILL IRR

ITATE EYES AND

MAY IRRI TATE SKIN.

\_\_\_\_\_

Physical/Chemical Properties

\_\_\_\_\_

HCC: V4

Spec Gravity: 3.06 +/- 0.05 Solubility in Water: INSOLUBLE

Appearance and Odor: SILVER/TAN COLORED PASTE WITH ACETIC ACID ODOR.

Percent Volatiles by Volume: 5.0

\_\_\_\_\_

Reactivity Data

\_\_\_\_\_\_

Stability Indicator: YE

S

Stability Condition To Avoid: EXPOSURE TO MOISTURE BEFORE USING.

Materials To Avoid: MATL WILL HYDROLYZE IN PRESENCE OF WATER/HUMID AIR. ALSO,

SILVER MAY REACT VIOLENTLY WITH OXIDIZING AGENTS, ACIDS/BASES.

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, SIO\*2,

ACETIC ACID (CH\*3COOH).

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NOT RELEVANT.

\_\_\_\_\_\_

**Toxicological Information** 

=============

\_\_\_\_\_

\_\_\_\_\_\_

**Ecological Information** 

\_\_\_\_\_

\_\_\_\_\_\_

**MSDS** Transport Information

\_\_\_\_\_

\_\_\_\_\_\_

Regulatory Information

\_\_\_\_\_\_

\_\_\_\_\_

====

Other Information

\_\_\_\_\_

\_\_\_\_\_\_

HAZCOM Label

\_\_\_\_\_\_

Product ID: CONDUCTIVE ADHESIVE CON RTV 1, 72-00002

Cage: 53217

Company Name: TECHNICAL WIRE PRODUCTS INC DBA TECKNIT INC

Street: 320 N NOPAL ST City: SANTA BARBARA CA

Zipcode: 93103-3225

Health Emergency Phone: 908-272-5500

Label Required IND: Y

Date Of Label Review: 01/26/1999

Status Code:

Α

Origination Code: G

\_\_\_\_\_\_

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contrac

ting with any instrumentality of the United

States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.