View NSN Online: https://aerobasegroup.ae/nsn/9330-01-387-0413

DUPONT KAPTON/TEFLON CUSTOMER SERVICE -- KAPOO1 -- 9330-01-387-0413

Product ID:KAPOO1 MSDS Date:10/08/1996

FSC:9330

NIIN:01-387-0413 Status Code:A

MSDS Number: CJDQB === Responsible Party ===

Company Name: DUPONT KAPTON/TEFLON CUSTOMER SERVICE

Box:89

City:CIRCLEVILLE

State:OH ZIP:43113 Country:US

Emergency Phone Num:800-237-4357

CAGE:DUPP0

=== Contractor Identific

ation ===

Company Name: DUPONT KAPTON/TEFLON CUSTOMER SERVICE

Box:89

City:CIRCLEVILLE

State:OH ZIP:43113 Country:US

Phone:800-237-4357/800-441-3637

CAGE:DUPP0

====== Composition/Information on Ingredients ========

Ingred Name: INERT POLYIMIDE FILM

< Wt:100.

Ingred Name:.ALPHA.-ALUMINA

CAS:1344-28-1

RTECS #:BD1200000 Minumum % Wt:0. Maxumum % Wt:35. OSHA PEL:15 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name: CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000 Minumum % Wt:0. Maxumum % Wt:20.

OSH

Ingred Name: DIMETHYL ACETAMIDE CAS:127-19-5 RTECS #:AB7700000 < Wt:1. OSHA PEL:35 MG/M3;10 PPM ACGIH TLV:36 MG/M3;10 PPM Ingred Name: POLYIMIDE POLYMER CAS:25038-81-7 =========== Hazards Identification ========================== Reports of Carcinogenicity:NTP:UNKNOWN IARC:YES Health Hazards Acute and Chronic: INHALATION: EXPOSURE TO ALUMINA/CARBON BLACK ENCAPSULATED IN THE POLYMER IS NOT LIKELY. SKIN: DUPONT RECOMMENDS TREATING POLYMER D UST AS A NUISANCE PARTICULATE. SKIN/EYES: NOT A PROBABLE ROUTE OF EXPO SURE FOR FILM. Explanation of Carcinogenicity: THE FOLLOWING COMPONENTS ARE LISTED BY IARC, NTP, OSHA/ACGIH AS CARCINOGENS: CARBON BLACK. First Aid:SKIN: WASH W/SOAP & WATER AFTER HANDLING. EYES: FLUSH W/WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES. ============ Fire Fighting Measures ========================= Extinguishing Media:WATER , FOAM, DRY CHEMICAL, CO2 Fire Fighting Procedures: NONE REQUIRED. Unusual Fire/Explosion Hazard: THE FLAMMABILITY CHARACTERISTIC OF POLYIMIDE FILM IS REPORTED AS SELF EXTINGUISHING. ======== Accidental Release Measures ============ Spill Release Procedures: REVIEW FIRE FIGHTING MEASURES & HANDLING SECTIONS BEFORE PROCEEDING W/CLEAN-UP. USE APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT DURING CLEAN-UP. PICK UP TO PREVENT SLIPPING HAZARD. ====== Handl

A PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3

ing and Storage ============
Handling and Storage Precautions:STORE AWAY FROM FLAMMABLE MATERIALS.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NOT NEEDED FOR NORMAL USE. Ventilation:FOR SMALL QUANTITIES: USE NORMAL AIR CIRCULATION IN CASE OF OVERHEATING. VENTILATION AT HIGHER TEMPS WILL DEPEND ON FILM QUANTITY/TEMPERATURE & EXPOSURE TIME. Protective Gloves:RECOMMENDED Eye Protection:SAFETY GLASSES RECOMMENDED Other Protective E quipment:NOT NEEDED FOR NORMAL USE. Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING. Supplemental Safety and Health
KAPTON WILL BURN IN AN ATMOSPHERE OF 100% OXYGEN. THE PROCESSING OF POLYIMIDE FILMS CAN CAUSE THE GENERATION OF STATIC CHARGE. PRECAUTIONS FOR STATIC CHARGES SHOULD BE TAKEN WHEN REMOVING PLASTIC FILM S USED AS PROTECTIVE PACKAGING FOR KAPTON.
========= Physical/Chemical Properties =========
Melt/Freeze Pt:M.P/F.P Text:NONE Spec Gravity:>1.4
Solubility in Water:INSOLUBLE Appearance and Odor:LIGHT AMBER TRANSPARENT FILM W/NO ODOR Percent Volatiles by Volume:1%
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES NONE Stability Condition to Avoid:STATIC CHARGES, TEMPERATURES ABOVE 752F.
Hazardous Decomposition Products:CO, CO2
========= Ecological Information ============
Ecological:AQUATIC TOXICITY. INSOLUBLE.
======= Disposal Conside

rations	=======================================
---------	---

Waste Disposal Methods:LANDFILL/INCINERATE/DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

======== Regulatory Information ============

State Regulatory Information:SUBSTANCES ON THE PENNSYLVANIA HAZARDOUS SUBSTANCES LIST PRESENT AT A CONCENTRATION OF 1%/MORE (0.01 FOR SPECIAL HAZARDOUS SUBSTANCES) DIMETHYL ACETAMIDE (1% MAXMUM); SOME TYPES CONTAIN CARBON BLACK (2-30%); SOME TYPES CONTAIN ALUMIN (35% MAX

IMUM). SUBSTANCES ON THE NEW JERSEY WORKPLACE HAZARDOUS SUBSTANCE LIST PRESENT AT A CONCENTRATION OF 1%/MORE (0.1% FOR SUBSTANCES IDENTIFIED AS CARCINOGENS, M UTAGENS/TERATOGENS) DIMETHYL ACETAMIDE (1% MAXIMUM); SOME TYPES CONTAIN CARBON BLACK (2-30%) SOME TY PES CONTAIN ALUMINA (35% MAXIMUM).

============= Other Information =============================

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.