

OPTIMA BATTERIES INC -- ENGINE STARTING BATTERIES 34/78-1050 -- 6140-01-374-2243
===== Product Identification =====

Product ID:ENGINE STARTING BATTERIES 34/78-1050

MSDS Date:01/04/1999

FSC:6140

NIIN:01-374-2243

Status Code:A

MSDS Number: CJGLT

=== Responsible Party ===

Company Name:OPTIMA BATTERIES INC

Address:5 E MISSISSIPPI AVE

City:DENVER

State:CO

ZIP:80210

Country:US

Info Phone Num:303-744-53

60

Emergency Phone Num:(800)424-9300

Resp. Party Other MSDS Num.:OBI-0001 C

Chemtrec Ind/Phone:(800)424-9300

CAGE:0UJ55

=== Contractor Identification ===

Company Name:OPTIMA BATTERIES INC

Address:17500 E 22ND AVENUE

Box:City:AURORA

State:CO

ZIP:80011

Country:US

Phone:303-448-8899 OR 800-292-4359

CAGE:0UJ55

===== Composition/Information on Ingredients =====

Ingred Name:LEAD COMPOUNDS

CAS:7439-92-1

RTECS #:OF7525000

Minumum % Wt:68.

Maxumum % Wt:81.

ACGIH TLV:0.15 MG/M3

EPA Rpt

Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:SULFURIC ACID ELECTROLYTE
CAS:7664-93-9
RTECS #:WS5600000
Minumum % Wt:17.
Maxumum % Wt:25.
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3
ACGIH STEL:3 MG/M3
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:POLYPROPYLENE CASE MATERIAL
CAS:9003-07-0
RTECS #:UD1842000
Minumum % Wt:2.
Maxumum % Wt:6.

Ingred Name:SEPARATOR/PASTER PAPER FIBROUS GLASS
CAS:65997-17-3
Code:F
Minumum % Wt:1.
Maxumum % Wt:4.

=====
===== Hazards Identification =====
=====

LD50 LC50 Mixture:NONE STATED BY MANUFACTURER
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:NONE EXPECTED FOR FINISHED PRODUCT
UNDER NORMAL CONDITIONS OF USE.
Explanation of Carcinogenicity:NOTA APPLICABLE FOR FINISHED PRODUCT
UNDER NORMAL CONDITIONS OF USE.
Effects of Overexposure:NONE EXPECTED FOR FINISHED PRODUCT UNDER NORMAL
CONDITIONS OF USE.
Medical Cond Aggravated by Exposure:N
ONE EXPECTED FOR FINISHED PRODUCT
UNDER NORMAL CONDITIONS OF USE.

=====
===== First Aid Measures =====
=====

First Aid:NONE EXPECTED FOR FINISHED PRODUCT UNDER NORMAL CONDITIONS OF
USE. INHALED-IF ACID VAPOR RELEAED, REMOVE PERSON TO FRESH AIR. IF
BREATHING DIFFICULT, OXYGEN MAY BE ADMINISTERED. IF BREATHING
STOPPED, ARTIFICIAL RESPIRATION MAY BE STARTED. SEEK MEDICAL
ATTENTION. EYES-IF ELECTROLYTE ENTERES EYES, FLUSH WITH WATER FOR
AT LEAST 1

5 MINUTES. SEEK PROMPT MEDICAL ATTENTION IF IRRITATION DEVELOPS. SKIN-IF ELECTROLYTE CONTACTS SKIN, FLUSH WITH MILD SOAP & WATER. SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS. INGESTED-IF ANY MATERIALS INGESTED, SEEK PROMPT MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Extinguishing Media:MULTIPURPOSE DRY CHEMICAL OR MULTIPURPOSE CARBON DIOXIDE (CO2).

Fire Fighting Procedures:EVACUATE AREA. SELF-CONTAINED BREATHING APPARATUS MUST

BE WORN TO PREVENT POSSIBLE INHALATION OF ACID

MISTS, SMOKE AND DECOMPOSITION PRODUCTS IN A FIRE. REMOVE ALL IGNITION SOURCES. COOL BATTERY (S) T O PREVENT RUPTURE.

Unusual Fire/Explosion Hazard:HYDROGEN GAS MAY BE PRODUCED AND MAY EXPLODE IF IGNITED. REMOVE ALL IGNITION SOURCES. VENTILATE AREA.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID CONTACT WITH ACID MATERIALS. USE SODA ASH, BAKING SODA OR LIME TO NEUTRALIZE ACID IF R
ELEASED.

Neutralizing Agent:SODA ASH, BAKING SODA, LIME.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT CARRY BATTERY BY TERMINALS. DO NOT DROP BATTERY, PUNCTURE OR ATTEMPT TO OPEN BATTERY CASE. KEEP AWAY FROM FLAMES DURING AND IMMEDIATELY AFTER CHARGE. AVOID PROLONGED OVERCHARGES IN CONFINED ARE AS. STORE AT AMBIENT ROOM TEMPERATURE. DO NOT SUBJECT PRODUCT TO OPEN FLAME OR FIRE.

Other Precautions:AVOID CONDITIONS WHI

CH COULD CAUSE ARCING BETWEEN

BATTERY TERMINALS. WASH HANDS THOROUGHLY BEFORE EATING OR SMOKING AFTER HANDLING BATTERIES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NECESSARY UNDER NORMAL CONDITIONS OF USE FOR FINISHED PRODUCT.

Ventilation:NOT NECESSARY UNDER NORMAL CONDITIONS OF USE FOR FINISHED PRODUCT.

Protective Gloves:NOT NECESSARY UNDER NORMAL CONDITIONS OF USE FOR FINISHED PRODUCT.

Eye Protection:NOT NECESSARY UNDER

NORMAL CONDITIONS OF USE FOR
FINISHED PRODUCT.

Other Protective Equipment:NOT NECESSARY UNDER NORMAL CONDITIONS OF USE
FOR FINISHED PRODUCT.

Work Hygienic Practices:NOT NECESSARY UNDER NORMAL CONDITIONS OF USE
FOR FINISHED PRODUCT.

Supplemental Safety and Health

THE SEALED LEAD ACID BATTERY IS NOT CONSIDERED FLAMMABLE, BUT WILL BURN
IF INVOLVED IN A FIRE. SHORT CIRCUIT CAN ALSO RESULT IN FIRE.

EVACUATE AREA. SELF-CONTAINED BREATHING APPARATUS MUST BE WORN TO
PREVENT INH

ALATION OF ACID MISTS, SMOKE & DECOMPOSITION PRODUCTS IN
A FIRE. REMOVE ALL IGNITION SOURCES.

===== Physical/Chemical Properties =====

HCC:Z4

Appearance and Odor:SEALED LEAD ACID BATTERY.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE STATED BY MANUFACTURER.

Stability Condition to Avoid:AVOID SHORTING, USE ONLY APPROVED CHARGING
METHODS. DO NOT PUNCTURE BATTERY CASE.

Hazardous Decompositi

on Products:NONE STATED BY MANUFACTURER.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Toxicological Information =====

Toxicological Information:THREASHOLD LIMIT VALUE: NONE APPLICABLE FOR
FINISHED PRODUCT. ROUTE OF ENTRY: NONE APPLICABLE FOR FINISHED
PRODUCT UNDER NORMAL CONDITIONS OF USE. SIGNS OF SYMPTOMS OF ACUTE
EXPOSURE: NONE EXPECTED FO R FINISHED PRODUCT UNDER NORMAL
CONDITIONS OF USE. CHRONIC EXPOSURE: NONE EXPECTED FOR FINISHED
PRODUCT UNDER NORMAL CONDITIONS OF USE. EFFECTS OF OVEREXPOSURE,
CONDITIONS TO AVOID: NO EXPOSURE EXPEC TED FOR FINISHED
PRODUCT.HOWEVER, DO NOT PUNCTURE OR OPEN BATTERY CASE. ACID
ELECTROLYTE MAY BE RELEASED.

===== Ecological Information =====

Ecological:NONE STATED BY MANUFACTURER.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE
AND FEDERAL REGULA

TIONS. SEND TO A LEAD RECYCLING FACILITY WHICH
FOLLOWS APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS FOR ROUTINE
DISPOSAL OF SPENT OR DAMAGED BATTERIES. THE DISTRIBUTOR/USER IS
RESPONSIBLE FOR ROUTINE DISPOSITION OF SPENT OR DAMAGED
BATTERIES.

===== MSDS Transport Information =====

Transport Information:SEALED LEAD ACID BATTERY IS NOT A US DOT
HAZARDOUS MATERIAL. UNDER DANGEROUS GOODS REGULATIONS, 38TH
EDITION, EFFECTIVE JANUARY 1, 199
7, PRODUCED BY INTERNATIONAL AIR
TRANSPORTATION ASSOCIATION (IATA) : OPTIMA BATTERIES ARE CLASSIFIED
AS NON-REGULATED BY SPECIAL PROVISIONS A-48 AND A-67 FOR UN NUMBER
UN2800. UNDER THE CODE OF FEDERAL REGULATIONS #49, MARCH 1, 1998
EDITION, OPTIMA BATTERIES ARE CLAS SIFIED AS AN EXCEPTION FROM ALL
OTHER REQUIREMENTS OR CONDITIONS AS STATED IN: BATTERIES WET,
173:159 (D)(3)(I)[VIBRATION TEST] AND (D)(3)(I)(I)[PRESSURE
DIFFERENTIAL TEST].

===== Regula
tory Information =====

SARA Title III Information:NONE STATED BY MANUFACTURER.
Federal Regulatory Information:ACCORDING TO THE OSHA HAZARD
COMMUNICATION STANDARD, SEALED LEAD ACID BATTERY IN ITS
MANUFACTURED AND SUPPLIED STATE IS CONSIDERED NON-HAZARDOUS.
State Regulatory Information:NONE STATED BY MANUFACTURER.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information
is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.