

DEXTER HYSOL AEROSPACE INC DIV OF EXTER CORP -- EPK 0150 PART B -- 6080-01-358-9686

===== Product Identification =====

Product ID:EPK 0150 PART B

MSDS Date:05/20/1988

FSC:6080

NIIN:01-358-9686

Status Code:A

Kit Part:Y

MSDS Number: CJGPB

=== Responsible Party ===

Company Name:DEXTER HYSOL AEROSPACE INC DIV OF EXTER CORP

Address:2850 WILLOW PASS ROAD

Box:312

City:PITTSBURG

State:CA

ZIP:94565-3237

Co

untry:US

Info Phone Num:510-458-8000

Emergency Phone Num:415-687-4201

CAGE:33564

=== Contractor Identification ===

Company Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS

Address:2850 WILLOW PASS ROAD

Box:312

City:BAY POINT

State:CA

ZIP:94565-3299

Country:US

Phone:202-483-7616

CAGE:33564

Company Name:LUCENT TECHNOLOGIES

Address:2000 NE EXPY

Box:UNKNOW

City:NORCROSS

State:GA

ZIP:30071

Country:US

Phone:770-798-3846

CAGE:1K705

===== Composition/Information on Ingredients =====

Ingred Name:SILICA  
CAS:7631-86-9  
&lt; Wt:5.  
OSHA PEL:20 MPPCF

Ingred Name:TRIETHYLENETETRAMINE  
CAS:112-24-3  
RTECS #:YE6650000  
&lt; Wt:30.

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:MATERIAL IS CORROSIVE TO SKIN. MAY  
CAUSE CHEMICAL BURN TO EYES AND SKIN. REPEAT CONTACT MAY  
CAUSE  
SENSITIZATION.  
Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER  
Effects of Overexposure:POSSIBLE BURNS TO EYES AND SKIN, IRRITATION AND  
POSSIBLE SENSITIZATION TO SKIN.  
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER

===== First Aid Measures =====

First Aid:FLUSH SKIN AND EYES WITH PLENTY OF WATER. WASH SKIN  
THOROUGHLY WITH SOAP 7 WATER, RUBBING ALCOHOL OR HAND CLEANER. DO  
NOT USE SOLVENTS. REMOVE SOILED  
CLOTHES AND WASH BEFORE REUSE. IF  
IRRITATION PERSI STS, SEE PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:=129.4C, 265.F  
Extinguishing Media:DRY CHEMICAL OR HALON FIRE EXTINGUISHER, OR WATER  
SPRAY, FOAM, FOG  
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS WHEN  
FIGHTING FIRES IN CONFINED AREAS.  
Unusual Fire/Explosion Hazard:DENSE SMOKE AND TOXIC GASES MAY BE  
LIBERATED.

===== Acci

dental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE CLOTHES, GLOVES AND SAFETY GLASSES. SCRAPE UP AND TRANSFER TO METAL CONTAINER. WIPE UP REMAINING RESIDUE WITH SOLVENTS, OBSERVING SOLVENT FLAMMABILITY CAUTIONS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER

===== Handling and Storage =====

Handling and Storage Precautions:KEEP COOL IN ACCORDANCE WITH LABEL INSTRUCTIONS. STORE AT ROOM TEMPERATURE (70 DEG F ) FOR 12 MONTHS.

Other Precautions:FOLLOW RECOMMENDED CURING SCHEDULE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED WITH GOOD INDUSTRIAL VENTILATION.

Ventilation:LOCAL EXHAUST RECOMMENDED.

Protective Gloves:IMPERVIOUS PLASTIC OR RUBBER

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:AS NEEDED TO PROTECT SKIN AND CLOTHING

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER

Supplemental Safety and Health

NONE SPECIFI

ED BY MANUFACTURER. KEY1=B2.

===== Physical/Chemical Properties =====

HCC:B2

Boiling Pt:=277.2C, 531.F

Vapor Pres:1

Spec Gravity:0.98

Evaporation Rate & Reference: