

MG INDUSTRIES -- LIQUID NITROGEN -- 9135-00-559-5287

=====  
Product Identification  
=====

Product ID:LIQUID NITROGEN  
MSDS Date:09/10/1998  
FSC:9135  
NIIN:00-559-5287  
Status Code:A  
MSDS Number: CJGXH  
=== Responsible Party ===  
Company Name:MG INDUSTRIES  
Address:3 GREAT VALLEY PARKWAY  
City:MALVERN  
State:PA  
ZIP:19355-1424  
Country:US  
Info Phone Num:215-630-5422  
Emergency Phone Num:800-424-9300(CHEMTREC) 21  
5-630-5422  
Preparer's Name:OCCUPATIONAL HEALTH SRVCS  
Chemtrec Ind/Phone:(800)424-9300  
CAGE:08772

=== Contractor Identification ===

Company Name:MG INDUSTRIES  
Address:3 GREAT VALLEY PKY  
Box:City:MALVERN  
State:PA  
ZIP:19355-1424  
Country:US  
Phone:610-695-7400 / 610-695-7449  
CAGE:08772

=====  
Composition/Information on Ingredients  
=====

Ingred Name:OXYGEN  
CAS:7782-44-7  
RTECS #:RS2060000  
= Wt:100.  
Other REC Limits:NONE SPECIFIED

=====  
Hazards Identification  
=====

=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: MAY CAUSE IRRITATION, LUNG  
CONGESTION & BLOOD DISORDERS. LONG TERM EXPOSURE MAY CAUSE LUNG  
DAMAGE. SKIN: FROSTBITE. EYES: IRRITATION, BLURRED VISION,  
BLINDNESS. INGESTION: FROSTBITE.  
Effects of Overexposure:IRRITATION, NAUSEA, ASTHMA, IRREGULAR  
HEARTBEAT, DIZZINESS, TINGLING SENSATION, DILATED PUPILS,  
CONGESTION, CONVULSIONS, CHEST PAIN, BLISTERS, FROSTBITE, BLURRED  
VISION

===== First Aid Measures =====

First Aid:INHALE:REMOVE FROM EXPOSURE IMMEDIATELY. USE A BAG VALVE  
MASK/SIMILAR DEVICE TO PERFORM CPR IF NEEDED. SKIN: WASH IF NEEDED.  
IF FROSTBITE, FREEZING/CRYOGENIC BURNS OCCUR, WARM AREA IN WARM  
WATER/GENTLY WRAP AFFECTED PARTS IN BLANKETS. ALLOW CIRCULATION TO  
RETURN NATURALLY. EYES: WASH IMMEDIATELY W/LARGE AMOUNTS OF WATER.  
OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Extinguishing Media:CARBON DIOXIDE, REGULAR/DRY CHEMICAL.  
Fire Fighting Procedures:USE FOAM/FLOOD W/FINE WATER SPRAY. MOVE  
CONTAINER FROM FIRE W/O RISK. COOL CONTAINERS W/WATER SPRAY/W/WATER  
FROM UNMANNED HOSE HOLDER/MONITOR NOZZLES UNTIL FIRE IS OUT. KEEP  
PEOPLE AWAY, ISOLATE AREA & DENY ENTRY.STAY AWAY FROM THE ENDS OF  
TANKS. EVACUATE RADIUS: 800 METERS/1 HALF MILE.  
Unusual  
Fire/Explosion Hazard:MAY IGNITE/EXPLODE ON CONTACT  
W/COMBUSTIBLE MATERIALS. CONTAINERS MAY RUPTURE/EXPLODE IF EXPOSED  
TO HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID CONTACT W/COMBUSTIBLE MATERIALS. DON'T  
TOUCH SPILLED MATERIAL. STOP LEAK IF POSSIBLE W/O RISK. KEEP  
UNNECESSARY PEOPLE AWAY, ISOLATE AREA & DENY ENTRY.

===== Handling and Storage =====

Handling and Storage Precautions

:STORE & HANDLE IN ACCORDANCE W/OSHA  
29CFR1910.104. PROTECT FROM PHYSICAL DAMAGE. KEEP SEPARATED FROM  
INCOMPATIBLE SUBSTANCES. STORE IN A COOL, DRY PLACE. STORE  
OUTSIDE/IN A DETACHED BUILDING.

Other Precautions:AVOID CONTACT WITH COMBUSTIBLE MATERIALS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FOR FREQUENT USE/HEAVY EXPOSURE, USE ANY  
SUPPLIED-AIR RESPIRATOR W/FULL FACEPIECE & OPERATED IN A PRESSURE  
DEMAND /OTHER POSITIVE PRES  
SURE MODE IN COMBINATION W/A SEPARATE  
ESCAPE SUPPLY/ANY SELF CONTAINED BREATHING APPARATUS W/A FULL  
FACEPIECE.

Ventilation:ENSURE COMPLIANCE W/APPLICABLE EXPOSURE LIMITS.

Protective Gloves:INSULATED

Eye Protection:SPLASH-RESISTANT SAFETY GOGGLES

Other Protective Equipment:EMERGENCY EYE WASH FOUNTAIN, QUICK DRENCH  
SHOWER IN THE IMMEDIATE WORK AREA, PROTECTIVE COLD INSULATING  
CLOTHING.

Supplemental Safety and Health

CONTACT LENSES SHOULD NOT BE WORN.

===== Physical/

Chemical Properties =====

HCC:G7

Boiling Pt:=-183.C, -297.4F

Melt/Freeze Pt:=-218.C, -360.4F

Vapor Pres:760

Vapor Density:1.1

Spec Gravity:1.1407

Solubility in Water:3.2%

Appearance and Odor:ODORLESS LIGHT BLUE LIQUID.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

COMBUSTIBLE MATERIALS; HALO CARBONS, METALS, BASES, REDUCING AGENTS,  
AMINES, METAL SALTS, OXIDIZING MATERIALS.

Stability Condition to Avoid:HEAT

Haza

rdous Decomposition Products:FORMS EXPLOSIVE MIXTURES, PEROXIDES,  
COMPOUNDS

===== Toxicological Information =====

Toxicological Information:LIQUID MAY CAUSE FROSTBITE TO EYES & SKIN.  
MAY CAUSE REDNESS, TINGLING, PAIN & NUMBNESS. IN SEVERE CASES, THE  
SKIN MAY BECOME HARD & WHITE, DEVELOPING BLISTERS. EYES: MAY CAUSE  
BLURRED VISION. IF LIQ UID IS SWALLOWED, FROSTBITE DAMGE OF THE  
LIPS, MOUTH & MUCOUS MEMBRANES MAY OCCUR.

===== Di  
sposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE &  
FEDERAL REGULATIONS.

===== MSDS Transport Information =====

Transport Information:U.S. EPA 40 CFR 262. HAZARDOUS WASTE NUMBER D001.  
U.S. DOT 49 CFR 172.101 OXYGEN REFRIGERATED LIQUID UN1073.

===== Regulatory Information =====

SARA Title III Information:SARA HAZARD CATEGORIES, SARA SECTIONS  
311/312 40CFR370.21

: FIRE, SUDDEN RELEASE

State Regulatory Information:EUROPEAN REGULATIONS: EC RISK & SAFETY  
PHRASES; CONTACT W/COMBUSTIBLE MATERIAL MAY CAUSE FIRE. R8.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate a  
nd  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.