

MCCABE AND SONS, INC -- MCCABE GASOLINE LEVEL INDICATOR PASTE -- 6850-00-270-5526
===== Product Identification =====

Product ID:MCCABE GASOLINE LEVEL INDICATOR PASTE

MSDS Date:02/17/1998

FSC:6850

NIIN:00-270-5526

Status Code:A

MSDS Number: CJMLF

=== Responsible Party ===

Company Name:MCCABE AND SONS, INC

Box:235

City:GLEN ROCK

State:PA

ZIP:17327

Country:US

Info Phone Num:717-235-2685

Emergency Ph

one Num:717.235.2685

Preparer's Name:C. WILLIAMS

CAGE:TO298

=== Contractor Identification ===

Company Name:MCCABE AND SONS, INC

Box:235

City:GLEN ROCK

State:PA

ZIP:17327

Country:US

Phone:717-235-2685

CAGE:TO298

Company Name:VEHICLES INC.

Address:702 GARFIELD ST

Box:1444

City:EMPORIA

State:KS

ZIP:66801-5110

Country:US

Phone:316-343-6653

CAGE:0E5D8

===== Composition/Information on Ingredients =====

Ingred Name:ZINC OXIDE

CAS:1314-13-2

RTECS #:ZH4810000

OSHA PEL:5 MG/M3

ACGIH TL

V:10 MG/M3 DUST
ACGIH STEL:5 MG/M3 FUME

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS: RESPIRATORY SYSTEM
(HMIS). ACUTE OVEREXPOSURE CAN CAUSE IRRITATION OF THE EYES,
RESPIRATORY TRACT AND SKIN. LIBERATION OF ZINC FUME MAY CAUSE
FEVER, CHILLS, NAUSEA, AND VOMITING. CHRONIC EXPOSURE HAS PRODUCED
NO KNOWN HEALTH HAZARDS.
Explanation of Carcinogenicity:MATERIAL IS NOT TO BE CARCINOGENIC BY
NTP, IARC, OSHA.
Effects of Overexposure:IRRITATION, METAL FUME FEVER CAUSES CHILLS,
FEVER, NAUSEA, AND VOMITING
Medical Cond Aggravated by Exposure:NONE KNOWN.

=====
===== First Aid Measures =====

First Aid:EYE CONTACT - FLUSH EYES IMMEDIATELY WITH WATER FOR 15
MINUTES AND CALL A PHYSICIAN. INGESTION - INDUCE VOMITING
IMMEDIATELY AND CALL A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:=-198.9C, 390.F
390-495F
Extinguishing Media:DRY CHEMICAL, FOAM, WATER OR CARBON DIOXIDE.
Fire Fighting Procedures:AVOID BREATHING VAPORS
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:SEGREGATE AND CLEAN UP TO AVOID GENERATING
DUST AND VAPOR. CONSIDER USE OF RESPIRATORS AND PERSONAL PROTECTIVE
EQUIPMENT IN E

XTREME CASES INVOLVING LARGE QUANTITIES OF THIS MATERIAL.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, WELL-VENTILATED AREA.

Other Precautions:DO NOT INGEST. AVOID CONTACT WITH EYES AND SKIN. KEEP CONTAINER CLOSED AND AWAY FROM OXIDIZERS. WASH THOROUGHLY AFTER HANDLING.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:CONSIDER USE OF NIOSH APPROVED RESPIRATOR IF

DUST OR FUME PRESENT ABOVE PEL

Ventilation:LOCAL EXHAUST IS RECOMMENDED TO KEEP BELOW PEL.

Protective Gloves:IMPERVIOUS GLOVES ARE USUALLY NOT REQUIRED.

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS OR CHEMICAL GOGGLES

Other Protective Equipment:BOOTS, APRON, AND SUIT MAY BE CONSIDERED IN EXTREME SITUATIONS

Work Hygienic Practices:AVOID BREATHING DUST OR VAPOR. WEAR LONG SLEEVED SHIRT, TROUSERS, AND SAFETY SHOES.

Supplemental Safety and Health

EYEWASH AND SAFETY SHOWER SHOULD BE AVAILABLE.

=====
===== Physical/Chemical Properties =====

HCC:V5

Boiling Pt:>232.2C, 450.F

Vapor Pres: