View NSN Online: https://aerobasegroup.ae/nsn/9150-01-374-2021

ROYAL LUBRICANTS COMPANY INC. -- ROYCO 308A -- 9150-01-374-2021

Product ID:ROYCO 308A MSDS Date:07/18/1995 FSC:9150 NIIN:01-374-2021 Status Code:A MSDS Number: CJTWY === Responsible Party === Company Name: ROYAL LUBRICANTS COMPANY INC. Box:518 **City:EAST HANOVER** State:NJ ZIP:07936-0518 Country:US Info Phone Num:973-887-7411 / 7410 973-887-8404 **Emergency Phone Num:** (800)424-9300 Resp. Party Other MSDS Num.:750,002-2 Preparer's Name: PRODUCT SAFETY, RLC INC. Chemtrec Ind/Phone:(800)424-9300 CAGE:07950 === Contractor Identification === Company Name: AMERICAN INK AND OIL CORP Address:33 ENDICOTT STREET Box:City:NORWOOD State:MA ZIP:02062-3006 Country:US Phone:781-762-0026 / FAX: 781-762-1617 CAGE:82956 Company Name: ROYAL LUBRICANTS COMPANY INC. Address:215 MERRY LN Box:518 **City:EAST HANOVER** State:NJ ZIP:07936 Country:US Phone:973-887-7411/7410 Contract Num:SP04

50-99-D-0498 CAGE:07950

Ingred Name:HYDROTREATED LIGHT NAPHTHENIC DISTILLATE (PETROLEUM) CAS:64742-53-6 RTECS #:PY8036000 Minumum % Wt:85. Maxumum % Wt:95. OSHA PEL:5 MG/M3 OIL MIST ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name:SOLVENT REFINED, HYDROTREATED MIDDLE DISTILLATE CAS:64742-46-7 RTECS #:JN9379645 Minumum % Wt:1. Maxumum % Wt:5. OSHA PEL:5 MG/M3 OIL MIST ACGIH TLV:5 MG/M3 OIL MIST

Ingred Name:BARIUM DINONYLNAPHTHALENE SU LFONATE CAS:25619-56-1 Minumum % Wt:1. Maxumum % Wt:2. OSHA PEL:0.5 MG/M3 SOL BA ACGIH TLV:0.5 MG/M3 SOL BA

Ingred Name:MINOR ADDITIVES (NON-HAZARDOUS) & lt; Wt:4.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE CONTACT: BASED ON PRESENCE OF
COMPONENT 3, PRODUCT IS IRRITATING TO THE EYES. SKIN CONTACT:
PROLONGED OR REPEA
TED CONTACT MAY CAUSE VARIOUS SKIN DISORDERS SUCH
AS DERMATITIS, FOLLICULITIS OR OIL A CNE. INHALATION: INHALATION OF
VAPORS (GENERATED AT HIGH TEMPERATURES ONLY) OR OIL MIST MAY BE
MILDLY IRRIATATING TO THE NOSE. THROAT AND RESPIRATORY TRACT.
INGESTION: INGESTION OF PRODUCT MAY RESULT IN VOMITING, ASPIRATION
(BREATHING) OF VOMITUS INTO THE LUNGS MUST BE AVOIDED AS EVEN SMALL
QUATITIES MAY RESULT IN ASPIRATION PNEUMONITIS.

Explanation of Carcinogenicity: THIS PRODUCT DOES

NOT CONTAIN ANY CARCINOGEN AS IDENTIFIED BY IARC, NTP OR OSHA. Effects of Overexposure: IRRITATION AS NOTED ABOVE. ASPIRATION PNEUMONITIS MAY BE EVIDENCED BY COUGHING, LABORED BREATHING AND CYANOSIS (BLUISH SKIN); IN SEVERE CASES DEATH MAY OCCUR. Medical Cond Aggravated by Exposure: PREEXISTING EYE, SKIN AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

First Aid:EYE CONTACT: IMMEDIATE

LY FLUSH WITH PLENTY OF WATER FOR AT

LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN CONTACT: REMOVE CONTAMINATED CLOTHING/SHOES AND WIPE EXCESS FROM SK IN. FLUSH SKIN WITH WATER. FOLLOW BY WASHING WITH SOAP AND WATER. IF IRRITATION OCCURS. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO THE LUNGS. GET MEDICAL ATTENTION.

Flash Point Method:COC
Flash Point:>148.9C, 300.F
Lower Limits:N/AV
Upper Limits:N/AV
Extinguishing Media:USE WATER FOG, FOAM, DRY CHEMICAL OR CO2. DO NOT USE A DIRECT STREAM OF WATER. PRODUCT WILL FLOAT AND CAN BE REIGNITED ON SURFACE OF WATER.
Fire Fighting Procedures:MATERIAL WILL NOT BURN UNLESS PREHEATED. DO NOT ENTER CONFINE FIRE SPACE WITHOUT FULL BUNKER GEAR (HELMET) WITH FACE SHIELD, BUNKER COATS, GLOVES AND RUBBER BOOTS)
, INCLUDING A POSITIVE PRESSURE NIOS H APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER.
Unusual Fire/Explosion Hazard:PRODUCT WILL FLOAT AND CAN BE REIGNITED ON SURFACE OF WATER.

Spill Release Procedures: REMOVE SOURCES OF IGNITION. WEAR PROTECTIVE EQUIPMENT. LARGE SPILL: WEAR APPROPRIATE PROTECTIVE EQUIPMENT. DIKE AND CONTAIN SPILL. DO NOT ALLOW SPILL TO ENTER DRAINS, S EWERS OR WATERWAYS. RECOVER FREE -LIQUID IF POSSIBLE. ABSORB SPILL WITH INERT MATERIAL AND PLACE IN AN APPROPRIATE CONTAINER FOR DISPOSAL. SMALL SPILLS: SOAK UP WITH INERT ABSORBENT. STORE IN CLOSED CONTAINER FOR PROPER DISPOSAL.

Handling and Storage Precautions: STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY FROM OPNE FLAMES AND HIGH TEMPERATURES. Other Precautions: WASH THOROUGHLYWITH S OAP AND WATER BEFORE EATING/DRINKING/SMOKING & AT END OF WORKDAY. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE. Respiratory Protection: IF EXPOSURE MAY OR DOES EXCEED OCCUPATIONAL EXPOSURE LIMITS, USE A NIOSH-APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE, IN ACCORD WITH 29 CFR 1910.134 USE EITHER AN ATMOSPHERE-SUPPLYING RESPIRATOR OR AN AIR-PURIFYING RESPIRATOR FOR ORGANIC VAPORS AND PARTICULATES. Protective Gloves:WEAR NITRILE GLOVES AND OTHER CLOTHING AS REQUIRED TO MINIMIZE CONTACT. Eve Protection: CHEMICAL GOGGLES. Work Hygienic Practices: AVOID CONTACT WITH EYES. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. Supplemental Safety and Health TEST DATA FROM PUBLISHED LITERATURE AND/OR CLOTHING MANUFACTURERS INDICATE THE BEST PROTECTION IS PROVIDED BY NITRILE GLOVES.

HCC:V6 Boiling Pt:B.P. Text:N/A (NOT AVAILABLE) Vap or Pres:NA Vapor Density:NA Spec Gravity:0.88 Viscosity:CS(40C): 12 Evaporation Rate & amp; Reference:NA Solubility in Water:NEGLIGIBLE Appearance and Odor:LIGHT AMBER OIL, SLIGHT HYDROCARBON ODOR.

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:AVOID HEAT, FLAME AND CONTACT WITH STRONG OXIDIZING AGENTS.
Hazardous Decomposition Products:A COMPLES MIXTURE OF AIRBORNE SOLID,

PARTICULATE GASES WILL EVOLVE WHEN THIS MATERIAL UNDERGOES PYROLYSIS/COMBUSTION.CARBON MONOXIDE & OTHER UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED UPON COMBUSTION Conditions to Avoid Polymerization:WILL NOT OCCUR

Toxicological Information:TOXICITY WARNING: DO NOT USE THIS OIL IN FOOD PROCESSING OR FOOD HANDLING EQUIPMENT ON SURFACES THAT MAY CONTACT FOOD. DO NOT ALLOW THE OIL TO CONTAMINATE FOODSTUFFS.

====

Ecological:UNDER EPA-CWA, THIS PRODUCT IS CLASSIFIED AS AN OIL UNDER SEC 311. SPILLS INTO OR LEADING TO SURFACE WATERS THAT CAUSE A SHEEN MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER, 800-424-8802.

Waste Disposal Methods:THIS PRODUCT CONTAINS BARIUM AT GREATER THAN 100 MG/L. UNDER EPA-RCRA (40CFR261.24) THIS IS A HAZARDOUS WASTE (#D0005).

DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS. OR MATERIAL MAY B E RECYCLED. HAZARDOUS USED OIL THAT IS RECYCLED IS MINIMALLY REGULATED UNDER RCRA OR EXEMPT UNDER SU BTITLE C. CHECK WITH LOCAL AUTHORITIES.

Transport Information:NOT REGULATED.

SARA Title III Information: UNDER EPA-CWA, THIS PRODUCT IS CLASSIFIED AS AN OIL UND

ER SEC 311. SPILLS INTO OR LEADING TO SURFACE WATERS THAT CAUSE A SHEEN MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER, 800-424-8802. UNDER SAR A TITLE II SEC 313, THIS PRODUCT CONTAINS BARIUM COMPOUNDS.

Federal Regulatory Information: THE COMPONENTS OF THIS PRODUCT ARE LISTED ON THE EPA/TSCA INVEMNTORY OF CHEMICAL SUBSTANCES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense . The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.