

PRAXAIR SURFACE TECHNOLOGIES INC -- NI-533 PRODUCT CODE: ZNI533-0010 --
3439-01-426-5420

===== Product Identification =====

Product ID:NI-533 PRODUCT CODE: ZNI533-0010

MSDS Date:09/02/1993

FSC:3439

NIIN:01-426-5420

Status Code:A

MSDS Number: CJWTM

=== Responsible Party ===

Company Name:PRAXAIR SURFACE TECHNOLOGIES INC

Address:1555 MAIN STREET

City:INDIANAPOLIS

State:IN

ZIP:46224-3283

Country:US

In

fo Phone Num:317-240-2650

Emergency Phone Num:(800)424-9300

Preparer's Name:MICHELLE ALEXANCER

Chemtrec Ind/Phone:(800)424-9300

CAGE:0FGH2

=== Contractor Identification ===

Company Name:PRAXAIR SURFACE TECHNOLOGIES INC

Address:1555 MAIN STREET

Box:City:INDIANAPOLIS

State:IN

ZIP:46224-3283

Country:US

Phone:317-240-2650

CAGE:0FGH2

Company Name:STARGHILL TECHNOLOGIES CORP

Address:3850 OAKMAN BLVD

Box:City:DETROIT

State:MI

ZIP:48204-1119

Country:US

Phone:313-933-4141

Contract Num:SP0450-95-D-4037

CA

GE:0VYG8

=====
Composition/Information on Ingredients
=====

Ingred Name:CHROMIUM

CAS:7440-47-3

RTECS #:GB4200000

Minumum % Wt:5.

Maxumum % Wt:20.

OSHA PEL:1 MG/M3

ACGIH TLV:0.5 MG/M3

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:NICKEL

CAS:7440-02-0

RTECS #:QR5950000

Minumum % Wt:50.

Maxumum % Wt:75.

OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3

Ingred Name:ALUMINUM

CAS:7429-90-5

RTECS #:BD0330000

Minumum % Wt:5.

Maxumum % Wt:20.

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:MOLYB

DENUM

CAS:7439-98-7

RTECS #:QA4680000

Minumum % Wt:1.

Maxumum % Wt:5.

ACGIH TLV:10 MG/M3

Ingred Name:COLUMBIUM/NIOBIUM

CAS:7440-03-1

RTECS #:QT9900000

Minumum % Wt:1.

Maxumum % Wt:5.

Ingred Name:TITANIUM

CAS:7440-32-6

RTECS #:XR1700000

Minumum % Wt:1.

Maxumum % Wt:5.

=====
Hazards Identification
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSH

A: YES

Health Hazards Acute and Chronic: SKIN: MAY CAUSE ALLERGIC DERMATITIS, WITH REDNESS & PAPULAR FORMATION IN SUSCEPTIBLE INDIVIDUALS. MAY CAUSE ULCERS PROGRESSING TO DRY & SCALY SKIN, FEVER. EYE: MAY CAUSE IRRITATION, EXPERIENCED AS REDNESS & EXCESS REDNESS OF THE CONJUCTIVA. SWALLOWING: MAY CAUSE NAUSEA, ABDOMINAL PAIN, VOMITING, DIARRHEA, CENTRAL NERVOUS SYSTEM DEPRESSION, & BURNING SENSATION. INHALATION: MAY CAUSE RESPIRATORY TRACT IRRITATION, WITH CHEST PAIN, V

VOMITING, DIARRHEA, BURNING SENSATION, & CENTRAL NERVOUS SYSTEM DEPRESSION. MAY ALSO CAUSE INTERSTITIAL PNEUMONITIS & SENSITIZATION OF THE RESPIRATORY TRACT IN SUSCEPTIBLE PERSONS.

Explanation of Carcinogenicity: NICKEL AND CHROMIUM HAVE BEEN DETERMINED TO CAUSE CANCER IN EXPERIMENTAL ANIMALS (IARC, NTP). NICKEL IS LISTED AS A PROBABLE HUMAN CARCINOGEN. CHROMIUM IS LISTED AS A HUMAN CARCINOGEN. CHRONIC ECZEMA/NEURODERMATITIS FROM NICKEL DOES NOT REQUIRE CONTINUOUS METAL CONTACT.

Effects of Overexposure: MAY CAUSE SENSITIZATION IN SUSCEPTIBLE INDIVIDUALS. CHRONIC EXPOSURE TO THE EYE CAN CAUSE CORNEAL DAMAGE, POLYCYTHEMIA, HYPERPLASIA OF THE THYROID GLAND AND DAMAGE TO THE ALPHA CELLS OF THE PANCREAS. REPEATED INHALATION MAY CAUSE EMPHYSEMA OR PULMONARY FIBROTIC DISEASE. CHRONIC SKIN CONTACT MAY SPREAD TO THE WHOLE BODY WITH LESIONS, ITCHING, SORENESS, BURNING SENSATION AND REDNESS.

Medical Condition Aggravated by Exposure: BREATHING OF DUST MAY AGGRAVATE

ASTHMA AND INFLAMMATORY OR FIBROTIC PULMONARY DISEASE. MAY ALSO AGGRAVATE AN EXISTING DERMATITIS.

=====
===== First Aid Measures =====
=====

First Aid: SWALLOWING: GIVE AT LEAST 2 GLASSES OF MILK OR WATER. INDUCE VOMITING, UNLESS PATIENT IS UNCONSCIOUS. CALL A PHYSICIAN. SKIN: WASH THOROUGHLY WITH SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NOT BREATHING. OXYGEN MAY BE GIVEN IF NECESSARY. CALL A PHYSICIAN.

EYES: FLUSH THOROUGHLY WITH PLENTY OF WATER. IF DISCOMFORT PERSISTS, SEEK MEDICAL ATTENTION. PREFERABLY AN OPHTHALMOLOGIST. NOTES TO PHYSICIAN: THE HAZARDS OF THIS MATERIAL ARE MAINLY DUE TO ITS SENSITIZING AND MILD IRRITATING PROPERTIES. THERE IS NO SPECIFIC ANTIDOTE.

=====
===== Fire Fighting Measures =====
=====

Flash Point: NONE

Upper Limits: 0.00%

Extinguishing Media: USE SPECIAL DRY POWDER METAL EXTINGUISHING MATERIAL TO EXTINGUISH METAL FIRES. USE

APPROPRIATE EXTINGUISHER FOR
COMBUSTABLE MATERIALS THAT MAY BE IGNITED BY THE THERMAL SPRAY
FLAME.

Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER.
Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT TO PROTECT AGAINST
HAZARDS AND DISPOSE OF PER WASTE DISPOSAL METHOD.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Hand
ling and Storage =====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.
Other Precautions:CAUTION: WHEN THERMAL SPRAYING - ELECTRICITY CAN
CAUSE FATAL SHOCK! DO NOT TOUCH LIVE ELECTRICAL PARTS! ARC RAYS CAN
BURN EYES AND SKIN! WEAR RECOMMENDED EYE AND BODY PROTECTION.
FUMES, GAS, AND DUST CAN HARM YOUR HEALTH. PROVIDE ENOUGH
VENTILATION AND WEAR RESPIRATOR IF REQUIRED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:DEPENDS UPON SPECIFIC USE, CONDITION, AND
LOCATION. IF THERE IS DUSTINESS, WEAR RESPRI-RATOR SELECTED PER
OSHA 1910.134, AND OSHA 29 CFR 1910.252 AND ANSI Z49.1.
Ventilation:LOCAL DUST PICK UP AND VENTILATION RECOMMENDED.
Protective Gloves:NOT REQUIRED.
Eye Protection:WHEN DUSTY USE GOGGLES PER OSHA 1910.13
Other Protective Equipment:SEE ANSI Z49.1, ANSI Z87.1, ANSI Z88.2 FOR
HELMETS, FACE SHIELDS AND GOGGLES.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

S
upplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:NONE
Vapor Density:N/VOLATILE
Evaporation Rate & Reference:UNAVAILABLE
Appearance and Odor:DUSTY DARK GRAY POWDER
Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE KNOWN.
Stability Condition to Avoid:NONE KNOWN.
Hazardous Decomposition P

roducts:WHEN THERMAL SPRAYING, WILL VARY WITH
OPERATING CONDITIONS. REASONABLY EXPECTED DECOMPOSITION PRODUCTS OF
NORMAL OPERATION FROM THIS THERMAL SPRAY POWDER INCLUDE OXIDES OF
THE LISTED INGREDIENTS.

===== Toxicological Information =====

Toxicological Information:NONE SPECIFIED BY MANUFACTURER.

===== Ecological Information =====

Ecological:NONE SPECIFIED BY MANUFACTURER.

===== Disposal Considerati
ons =====

Waste Disposal Methods:DISPOSE OF WASTE PER LOCAL, STATE, AND FEDERAL
REGULATIONS.

===== MSDS Transport Information =====

Transport Information:NONE SPECIFIED BY MANUFACTURER.

===== Regulatory Information =====

SARA Title III Information:PRODUCT CONTAINS THE FOLLOWING TOXIC
CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF
THE EMERGENCY PLANNING AND COMMUNITY RIGHT TO KNOW
ACT OF 1986 AND
OF 40 CFR 372: CHROMIUM, CAS# 7440-47-3,