

DURANT PAINTS INC -- OLIVE DRAB # 34088 ONE GAL CAN -- 8010-00-297-2116

=====
Product Identification
=====

Product ID:OLIVE DRAB # 34088 ONE GAL CAN

MSDS Date:03/01/1998

FSC:8010

NIIN:00-297-2116

Status Code:A

MSDS Number: CKCXV

=== Responsible Party ===

Company Name:DURANT PAINTS INC

Address:112 RAILROAD ST

City:REVERE

State:MA

ZIP:02151-4007

Country:US

Info Phone Num:781-289-8415

Emergency Phone

Num:781-289-8415

CAGE:3F338

=== Contractor Identification ===

Company Name:DURANT PAINTS INC

Address:112 RAILROAD ST

Box:City:REVERE

State:MA

ZIP:02151-4007

Country:US

Phone:781-289-8415

CAGE:3F338

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENE

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 45.70% WT

OSHA PEL:100 PPM

ACGIH STEL:100 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====
Hazards Identification
=====

Eff

ects of Overexposure:DIZZINESS, NAUSEA, VOMITING, LOSS OF
COORDINATION AND FATIGUE.

Medical Cond Aggravated by Exposure:ASTHMA, HEART CONDITION.

===== First Aid Measures =====

First Aid:SKIN CONTACT : FLUSH WITH WATER. IF REDNESS PERSISTS SEEK
MEDICAL ATTENTION. INHALATION: IF RESPIRATORY SYMPTOMS DEVELOP,
REMOVE VICTIM FROM SOURCE OF EXPOSURE TO FRESH AIR. IF SYMPTOMS
PERSIST, SEEK MEDICAL ATTENTION. INGESTION: SEEK EMERGENCY
M
EDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:=-27.2C, 81.F

81F

Upper Limits:7

Extinguishing Media:CO2/FOAM

Fire Fighting Procedures:THIS MATERIAL MAY BE IGNITED BY HEAT, SPARKS
FLAME, OR STATIC ELECTRICITY. KEEP CONTAINERS CLOSED WHEN NOT IN
USE. ISOLATE FROM HEAT, SPARKS, PILOT LIGHTS, SMOKING MATERIALS,
AND OTHER SOURCES OF IGNITION.

Unusual Fire/Explosion Hazard:THE USE OF SCBA IS RECOMMENDED FOR
F

FIREFIGHTERS. WATER SPRAY MAY BE USEFUL IN COOLING CONTAINERS
EXPOSED TO HEAT AND FLAME. AVOID SPREADING BURNING LIQUID WITH
WATER USED FOR COLLING PURPOSES. FIGHT AS VOLATILE LIQUID FIRE.
CLOSED CONTIANERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:STAY UPWIND, REMOVE SOURCE OF IGNITION, KEEP
OUT OF DRAINS, SEWERS, WATERWAYS. USE ABSORBENT PADS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED ORGANIC SUPPLIED AIR RESPIRATOR.

Ventilation:MECHANICAL/

Protective Gloves:EXPLOSION PROOF

Eye Protection:AVOID CONTACT WITH EYES. WEAR SAFETY GLASSES OR
GOGGLES.

Other Protective Equipment:WEAR IMPERVIOUS CLOTHING.

Work Hygienic Practices:WASH WITH SOAP AND WATER BEFORE EATING,
DRINKING, SMOKING, APPLYING COSMETICS, OR USING TOILET FACILITIES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

=====
Boiling Pt:>138.9C, 282.F
B.P. Text:282-286F
Vapor Density:HEAVIER
Volatile Org Content %:4
Evaporation Rate & Reference:SLOWER THAN AIR
Solubility in Water:NIL
Appearance and Odor:LIQUID
Percent Volatiles by Volume:66%

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
CO2
Stability Condition to Avoid:AVOID HEAT, FLAME, STATIC ELECTRICITY.

=====
Ecological Information
=====

=

Ecological:KEEP PRODUCT OUT OF DRAINS, SEWERS, WATERWAYS. DISPOSE OF
PRODUCT IN ACCORDANCE WITH LOCAL/STATE/ FED REGULATIONS.

=====
Disposal Considerations
=====

Waste Disposal Methods:DISPOSE PRODUCT IN ACCORDANCE WITH LOCAL, STATE
AND FEDERAL REGULATIONS.

=====
Regulatory Information
=====

State Regulatory Information:

=====
Other Information
=====

Disclaimer (provided with
this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.