

AMERON PROTECTIVE COATINGS GROUP INT. -- 601S6963 DEVFLEX 601595A22563 BEACH SAND
-- 8010-01-206-4712

===== Product Identification =====

Product ID:601S6963 DEVFLEX 601595A22563 BEACH SAND
MSDS Date:12/19/1997
FSC:8010
NIIN:01-206-4712
MSDS Number: CKJKN
=== Responsible Party ===
Company Name:AMERON PROTECTIVE COATINGS GROUP INT.
Address:201 NORTH BERRY ST
City:BREA
State:CA
ZIP:92821
Country:U
S
Info Phone Num:7145291951
Emergency Phone Num:800-424-9300
Preparer's Name:H. KLINE
Chemtrec Ind/Phone:(800)424-9300
CAGE:55849

=== Contractor Identification ===

Company Name:AMERON INTERNATIONAL PROTECTIVE COATINGS GROUP
Address:201 NORTH BERRY ST.
Box:City:BREA
State:CA
ZIP:92821
Country:US
Phone:714-529-1951
CAGE:55849

===== Composition/Information on Ingredients =====

Ingred Name:VINYL COPOLYMER RESIN (AS VINYL ACETATE. TRACE CONTAMINANTS
ACRYLAMIDE** FORMALDEHYDE**
0.05%, VINYL ACETATE 0.09%
ACETALDEHYDE** 0.095%. STEL 15PPM, 53 MG/M3.). **=CA TITLE 26:
22-12000 (PROP. 65).
RTECS #:VC1010194
Fraction by Wt: 25.0%
OSHA PEL:10.000 PPM TWA
ACGIH TLV:10.0000 PPM TWA

Ingred Name:+TITANIUM DIOXIDE (AS TI, TRACE CONTAMINANTS 2.5% ALUMINUM
HYDROXIDE 3% AMORPHOUS SILICA). += PIGMENT CONTENT IS DEPENDANT ON
COLOR.
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 15.0%
ACGIH TLV:5.00 TWA MG/M3

Ingred Name:WATER (VP=1.0 MMGH @ 68F)
CAS:7732-18-5
RT

ECS #:ZC0110000
Fraction by Wt: 9.10%

Ingred Name:ANTIMONY TRIOXIDE (**) * FED OSHA: Y NTP: NO ACGIH: A2
IARC: B2 (AS ANTIMONY, TRACE IMPURITIES ARSENIC**>0.5%,
LEAD**#>0.2% NICKEL**>0.0003%). **=CA. TITLE 26:22-12000 (PROP
65).#=PROP 65 - BIRTH DEFE

CAS:1309-64-4
RTECS #:CC5650000
Fraction by Wt: 5.0%
OSHA PEL:5.000 PEL-TWA
ACGIH TLV:5.00 MG/M3
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:VINYL COPOLYMER RESIN (TRACE CONTAMINANT VINYL CHLORIDE**)
**=CA TITLE 26:22-12

000 PROP 65).
CAS:9002-86-2
Code:F
RTECS #:KV0350000
Fraction by Wt: 5.0%
OSHA PEL:5.000 MG/M3 TWA
ACGIH TLV:5.00 MG/M3 TWA

Ingred Name:DIPROPYLENE GLYCOL MONOMETHYL ETHER (STEL 150 PPM, 900
MG/M3.) VP=0.4 MMHG @ 68F

CAS:34590-94-8
RTECS #:JM1575000
Fraction by Wt: 3.60%
OSHA PEL:100.000 PPM TWA
ACGIH TLV:100.0000 PPM TWA

Ingred Name:ACRYLIC RESIN (TRACE CONTAMINANTS; ACRYLIC MONOMERS < 0.1%,
FORMALDEHYDE**