

OCCIDENTAL CHEMICAL CORP. -- FLUOROLUBE LG 160 -- 9150-00-698-3821

=====
Product Identification
=====

Product ID:FLUOROLUBE LG 160

MSDS Date:05/04/1988

FSC:9150

NIIN:00-698-3821

Status Code:A

MSDS Number: CKJZD

=== Responsible Party ===

Company Name:OCCIDENTAL CHEMICAL CORP.

Address:CUSTOMER SERVICE,OCCIDENTAL TOWER

Box:809050

City:DALLAS

State:TX

ZIP:75380

Info Phone Num:1-800-752-5151

Emergency

Phone Num:716-278-7021

CAGE:0AH54

=== Contractor Identification ===

Company Name:OCCIDENTAL CHEMICAL CORP (OXYCHEM)SHORT ABBREVIAT

Address:360 RAINBOW BLDVD SOUTH

Box:728

City:NIAGARA FALLS

State:NY

ZIP:14302

Country:US

Phone:1-800-733-3665

CAGE:91784

Company Name:OCCIDENTAL CHEMICAL CORPORATION

Address:5005 LYNDON B JOHNSON FWY

Box:City:DALLAS

State:TX

ZIP:75244-6198

Country:US

Phone:800-752-5151/972-404-3800

CAGE:0AH54

=====
Composition/Information on Ingredients
=====

Ing

red Name:FUMED SILICA (AMORPHOUS).PRESENT IN FLUOROLUBE GREASES,NOT AN INHAL HAZ (MFR).ACGIH TLV FOR NO ASBESTOS,10 G/KG (SEE SUPP)

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SEE SIGNS AND SYMPTOMS OF OVEREXPOSURE.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:EYES:MILD IRRITATION.SKIN:NO EFFECTS EXPECTED.INGESTION:PRACTICALLY NON-TOXIC.INHALATION:NO EFFECTS EXPECTED.

M
Medical Cond Aggravated by Exposure:N/K

=====
===== First Aid Measures =====

First Aid:EYES:IMMED FLUSH W/ DIRECTED STREAM OF WATER FOR AT LEAST 15 MIN.FORCIBLY HOLD LIDS APART FOR COMPLETE IRRIGATION OF ALL TISSUE.GET MED ATTN IF IRRIT OCCURS.SKIN:WASH W/ SOAP & WATER.INGEST:NEVER GIVE ANYTHING BY MOUTH TO UNCON PERSON.DO NOT INDUCE VOMIT.GIVE LARGE QUANTITIES OF WATER OR MILK.IF VOMIT OCCURS KEEP AIRWAY CLEAR & GIVE MORE WATER.GET MED ATTN IMMED.INHAL:REMOVE TO FRESH AIR.

=====
===== Fire Fighting Measures =====

Extinguishing Media:USE AGENT SUITABLE FOR SURROUNDING FIRE.

Fire Fighting Procedures:WEAR PRESSURE DEMAND SCBA AND FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:DECOMP & DEPOLYMERIZE ABOVE 500F,260C.DECOMP PROD TOXIC & HAZ:HYDROGEN FLUORIDE,HYDROGEN CHLORIDE,CHLOROTRIFLUOROETHYLENE,OTHER ORGANIC FLUORINE COMPOUNDS. PHOSGENE .

=====
===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP FLUOROLUBE OILS & GREASES OR TAKE UP WITH ABSORBENT MATERIAL & PLACE IN MARKED CONTAINERS FOR RECLAMATION OR DISPOSAL.

Neutralizing Agent:N/K

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTR TIGHTLY SEALED TO AVOID CONTAM.AVOID GALLING OR FRICTION W/ ALUMINUM OR MAGNESIUM PARTS INCLUDING CONTR CLOSURES.

Other Precautions:DO NOT REUSE CONTR (RESIDU

ES).OBSERVE ALL PREC.DISP

OF CONTR PER GOVT REGS.PROD DISP-COMpletely REMOVE FROM CONTR.DISP
PER REGS MATL THAT CANNOT BE USED/REPROCESSED.NO SMKNG IN AREA OF
USE.DO NOT USE IN GEN VICIN OF ARC WELDING, OPEN FLAMES OR HOT
SURFACES. HEAT MAY CAUSE THE FORMATION OF HCL OR PHO SGENE .

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR
EXPOSURE OF CONCERN .

Ventilation:LOCAL AND GENERAL VENT
ILATION NECESSARY TO KEEP AIR
CONCENTRATION BELOW TLV .

Protective Gloves:IMPERVIOUS

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:N/K

Work Hygienic Practices:N/K

Supplemental Safety and Health

LD50-LC50 MIX: LD50 DERMAL RABBIT >5 G/KG. NEW MATERIAL IS RELATIVELY
NON-TOXIC. MATERIAL IN SERVICE MAY BE CONTAMINATED WITH TOXIC
FOREIGN SUBSTANCES.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:N/K

Melt/Freeze Pt:M.P/F

.P Text:N/K

Decomp Temp:Decomp Text:>500F,260C

Vapor Pres:0.013 MM HG @ 200F

Spec Gravity:1.87-1.96 @ 100F (H2O=1)

Evaporation Rate & Reference:N/K

Solubility in Water:INSOLUBLE

Appearance and Odor:CLEAR,COLORLESS OIL OR GREASE.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

REACTS VIOLENTLY W/ SODIUM,POTASSIUM,AMINES,LIQ FLUORINE,LIQ CHLORINE
TRIFLUORIDE.KEEP AWAY FROM ALUMINUM & MAGNESIUM.

Stability Condition to Avoid:

FRICION OR GALLING IN CONT W/ AL OR MG
PARTS.CAUSES LOCAL AREAS OF HIGH PRESS/TEMP RESULTING IN LOCALIZED
DETONATION.

Hazardous Decomposition Products:HYDROGEN FLUORIDE,HYDROGEN
CHLORIDE,CHLOROTRIFLUOROETHYLENE & OTHER TOXIC ORGANIC FLUORINE
CMPDS.PHOSGENE .

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE IN ACCORDANCE WITH
FEDERAL,STATE AND LOCAL REGULATIONS .INCINERATE IN EQUIP DESIGNED
TO HANDLE HYDROGEN CH
LORIDE & HYDROGEN FLUORIDE AS COMBUSTION
PRODUCTS OR SUBMIT TO APPROVED CHEMICAL DISPOSAL SERVICE FOR
DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent pro
fessional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.