

PLASTIC FLAMECOAT(R) SYSTEMS, INC. -- PF110-H101 BLACK -- 8010-01-414-4969

=====
Product Identification
=====

Product ID:PF110-H101 BLACK

MSDS Date:10/18/1994

FSC:8010

NIIN:01-414-4969

Status Code:A

MSDS Number: CKMCS

=== Responsible Party ===

Company Name:PLASTIC FLAMECOAT(R) SYSTEMS, INC.

Address:3400 WEST 7TH

City:BIG SPRING

State:TX

ZIP:79720

Country:US

Info Phone Num:800-753-5263

Emergency Ph

one Num:1-800-753-5263

CAGE:03FB0

=== Contractor Identification ===

Company Name:PLASTIC FLAMECOAT(R) SYSTEMS, INC.

Address:3400 WEST 7TH

Box:City:BIG SPRING

State:TX

ZIP:79720

Country:US

Phone:800-753-5263

CAGE:03FB0

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYLENE METHACRYLIC ACID COPOLYMER

CAS:25053-53-6

Minumum % Wt:0.

Maxumum % Wt:100.

Ingred Name:RESIDUAL METHYLACRYLIC ACID

CAS:79-41-4

RTECS #:OZ2975000

= Wt:.05

ACGIH TLV:20 PPM

Ingred Name:BLAC

K PIGMENT
CAS:1333-86-4
RTECS #:FF5800000
Minumum % Wt:0.
Maxumum % Wt:10.
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3

Ingred Name:LIGHT STABILIZER
CAS:52829-07-9
Minumum % Wt:0.
Maxumum % Wt:1.

Ingred Name:ANTIOCIDANT/STABILIZER
CAS:6683-19-8
RTECS #:DA8340900
Minumum % Wt:0.
Maxumum % Wt:1.

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:INHALATION: MAY CAUSE IRRITATION TO
UPPER RE
SPIRATORY TRACT. SKIN: MAY CAUSE IRRITATION AND ALLERGIC
REACTION. INGESTION: NOT LIKELY. MAY CAUSE IRRITATION TO THE
GASTROINTESTINAL TRACT. EYES: MAY CAUS E IRRITATION.
Medical Cond Aggravated by Exposure:

=====
===== First Aid Measures =====

First Aid:INGESTION:IF LARGE AMMOUNT SWALLOWED, GIVE SEVERAL GLASSES OF
WATER.CONTACT MEDICAL PERSONNEL FOR FURTHER ASSISTANCE.IF
UNCONCIOUS/CONVULSING,DO NOT GIVE ANYTHING BY MOUTH.EYE CONTACT:
FLUSH
WITH PLEN TY OF RUNNING WATER FOR AT LEAST 15 MINITUES.HOLD
THE EYELIDS APART TO ENSURE THE RINSING OF ENTIIRE SURFACE.SEEK
MEDICAL ATTENTION IF EYE IRRITATION OCCURS.SKIN CONTACT:FLUSH ALL
AREAS WITH PLENTY OF WATER FOR SEVERAL MINITUES. REMOVE/CLEAN
CONTAMINATED CLOTHING/SHOES.SEEK MEDICAL ATTENTION IF SKIN
IRRITATION OCCURS. INHALATION:REMOVE TO FRESH AIR.SEEK MEDICAL
ATTENTION IF RESPIRATORY IRRITATION OCCURS/ BREATHING BECOMES
DIFFICULT.

=====

Fire Fighting Measures =====

Lower Limits:30 GRAMS/CM

Extinguishing Media:WATER, FOAM, CARBON DIOXIDE, DRY CHEMICALS. COOL FIRE EXPOSED CONTAINERS WITH WATER.

Fire Fighting Procedures:PRODUCTS OF COMBUSTION MAY BE TOXIC. AVOID BREATHING FUMES. FIREFIGHTERS SHOULD BE QQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS. DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL BUNKER GEAR (HELMET W ITH FACE SHIELD, BUNKER COATS, GLOVES AND RUBBER BOOTS). INCLUDING A POSITIV

E PRESSURE BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:DUST CAN FORM AN EXPLOSIVE MIXTURE WITH AIR. ELLIMINATION OF SOURCES OF IGNITION IS ESSENTIAL.

===== Accidental Release Measures =====

Spill Release Procedures:SWEEP UP TO AVOID SLIPPING HAZARD. USE APPROPIATE PERSONAL PROTECTIVE EQUIPMENT DURING CLEANUP.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL DRY PLACE. KEEP CONTAINERS CLOSED TO PREVENT CONTAMINATION AND ACCUMULATION OF MOISTURE.

Other Precautions:CARBON BLACK IS DESIGNATED A NUISANCE DUST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE A NIOSH/MSHA APPROVED RESPIRATOR EQUIPPED WITH THE APPROPRIATE FILTER FOR PARTICULATE DUST EXPOSURE.

Ventilation:LOCAL VENTILATION SHOULD BE USED OVER PROCESSING EQUIPMENT.

Protective Gloves:PROTECTIVE GLOVES SHOULD BE USED.

Eye Protection:SAFTEY GLASSES ARE RECOM MENDED.

Other Protective Equipment:LONG SLEEVE COTTON SHIRT AND PANTS ARE RECOMMENDED TO PREVENT SKIN CONTACT.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:=80.C, 176.F

B.P. Text:176-221F

Spec Gravity:> 0.93

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLACK FINELY DIVIDED POWDER MILD METHACRYLIC ACID ODOR

Percent Volatiles by Volume:NEGLIGIBLE

===== Stability and Reactivity Data =====

tability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: THE MATERIALS ARE NORMALLY STABLE AND DECOMPOSE ONLY IN EXTREME CASES SUCH AS FIRE.

Hazardous Decomposition Products: OXIDES OF NITROGEN, CARBON AND MIXTURE OF ORGANIC COMPOUND ARE THE EXPECTED IN THE PRESENCE OF LARGE AMOUNTS OF AIR. CARBON MONOXIDE AND HYDROCARBON OXIDATION. ORGANIC ACIDS, ALDEHYDES AND ALCOHOLS.

===== Toxicological Information =====

Toxicological Information:

TOXICITY IS EXPECTED TO BE LOW BASED ON NEGLIGIBLE WATER SOLUBILITY.

===== Disposal Considerations =====

Waste Disposal Methods: PREFERRED OPTIONS FOR DISPOSAL ARE (1) RECYCLING, (2) INCINERATION WITH ENERGY RECOVERY, AND (3) LANDFILL. THE HIGH FUEL VALUE OF THIS PRODUCT MAKES OPTION 2 VERY DESIRABLE FOR MATERIAL THAT CANNOT BE RECYCLED. TREATMENT, STORAGE, TRANSPORTATION AND DISPOSAL; MUST BE IN ACCORDANCE WITH FEDERAL, STATE AND PROVINCIAL AND LOCAL REGULATIONS.

===== Regulatory Information =====

SARA Title III Information: CARBON BLACK, CAS#133-86-4, HIGHEST % BY WEIGHT 2.50.

State Regulatory Information:

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.