View NSN Online: https://aerobasegroup.ae/nsn/2090-00-372-6064

ABBEY COLOR & CHEMICAL CO., INC. -- 18005PB, MIL-R-19907D PASTE HARDENER PART B -- 2090-00-372-6064

============= Product Identification ==================

Product ID:18005PB, MIL-R-19907D PASTE HARDENER PART B

MSDS Date:03/18/1997

FSC:2090

NIIN:00-372-6064 Status Code:A

Kit Part:Y

MSDS Number: CKMRZ === Responsible Party ===

Company Name: ABBEY COLOR & CHEMICAL CO., INC.

Address:400 E TIOGA STREET

City:PHILADELPHIA

St

ate:PA

ZIP:19134-1127 Country:US

Info Phone Num:215-739-9960

Emergency Phone Num:215-739-9960 Preparer's Name:JOHN BARTUSIAK

CAGE:19092

=== Contractor Identification ===

Company Name: ABBEY COLOR INC DBA ABBEY PRODUCTS AND BONDED

Address:400 E TIOGA ST Box:City:PHILADELPHIA

State:PA

ZIP:19134-1127 Country:US

Phone:215-739-9960

Contract Num:SP0760-00-6004

CAGE:19092

====== Composition/Information on Ingredients ========

Ingred Name:TRIPHENYL PHOSPHITE

CAS:101-02-0

RTECS #:TH1575000

Ingred Name: PARA-TOLUENESULFONAMIDE RESIN

CAS:1338-51-8

Ingred Name:TRIETHANOLAMINE

CAS:102-71-6

RTECS #:KL9275000 ACGIH TLV:5 MG/M3

Ingred Name:TRIETHYLENETETRAMINE

CAS:112-24-3

RTECS #:YE6650000

Ingred Name: POLYAMIDE RESINS

CAS:63428-83-1 RTECS #:RF5250000

Ingred Name: ALUNIMUM SILICATE

CAS:12269-78-2

Ingred Name:BLACK IRON OXIDE

CAS:1317-38-0 RTECS #:GL7900000 ACGIH TLV:5 MG/M3

Ingred Name: MILLED GLASS

CAS:65997-17-3

ACGIH TLV:10 MG/M3

Ingred Name: SILICONE DIOXIDE, AMORPHOUS

CAS:67762

-90-7

ACGIH TLV:10 MG/M3

========= Hazards Identification =============

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE AND CHRONIC: A KNOWN SENSITIZER
WHICH MAY CAUSE SKIN RASH WITH PROLONGED OR REPEATED CONTACT AND
CAN CAUSE IRRITATION OF THE NOSE, THROAT AND LUNGS.

Explanation of Carcinogenicity: NO INFORMATION FOUND.

Effects of Overexposure:INHALATION: MAY CAUSE NAUSEA AND CAN BE IRRITATING TO AIR PASSAGES UPON PR

OLONGED EXPOSURE. SKIN AND EYE CONTACT: MAY CAUSE SKIN IRRITATION WITH PROLONGED OR REPEATED CONTACT. PROLONGED EXPOSURE TO VA PORS CAN CAUSE EYE IRRITATION. SKIN ABSORPTION: IRRITATION OF SKIN. REDNESS AND ITCHING. INGESTION: INGESTION HEALTH RISKS ARE NOT USUAL. IF INGESTED, CAN CAUSE ABDOMINAL DISCOMFORT. Medical Cond Aggravated by Exposure: SKIN ABRASIONS AND HEAD COLDS. First Aid: EYES: IMMEDIATELY FLUS H WITH WATER FOR AT LEAST 15 MINUTES. CALL A PHYSICIAN. SKIN: WASH WITH MILD SOAP AND WATER AFFECTED EXPOSED SKIN SURFACES. INHALATION: REMOVE VICTIM TO FRESH AIR. GIVE OXYGEN IF BREATHING IS DIFFICULT CALL A PHYSICIAN. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. =========== Fire Fighting Measures ========================== Flash Point Method:COC Flash Point:=98.9C, 210.F Extinguishing Media:FOAM, CO2, DRY CHEMICAL. Fire Fighting Procedures: WEAR COMPLETE FIRE FIGHTING EQUIPMENT INCLUDING SELF-CONTAINED BREATHING UNIT. REMAIN UPWIND FROM FIRE. SPRAY WATER ON CONTAINERS IN FIRE AREA TO KEEP COOL AND PREVENT FROM BURSTING. Unusual Fire/Explosion Hazard: HANDLE AS A COMBUSTIBLE MATERIAL WHEN EXPOSED TO FIRE. SEALED CONTAINERS IN A FIRE AREA MAY DEVELOP PRESSURE AND BURST. ======== Accidental Release Measures ============ SOAK UP WITH ABSORBENT AND EYES. SHOVEL INTO CONTAINERS FOR SAFE SHIPMENT TO APPROVED DISPOSAL AREAS. WORK IN WE LL VENTILATED AREA.

Spill Release Procedures: CONTAIN SPILL AND REMOVE IGNITION SOURCES.

MATERIALS. WEAR PROTECTIVE CLOTHING FOR SKIN

============ Handling and Storage ===========================

Handling and Storage Precautions: WORK IN A WELL-VENTILATED AREA. PRACTICE GOOD CAUSTION AND PERSONAL CLEANLINESS TO PREVENT EYE AND SKIN CONTACT. AVOID BREATHING VAPORS. WASH EXPOSED SKIN AREAS AFTER HANDLING PRODUCT. STORE IN A COOL, DRY AREA, IN TIGHTL

CONTAINERS.
Other Precautions:LAUNDER CLOTHING BEFORE REUSE. DISCARD HEAVILY CONTAMINATED CLOTHING, HEAVILY CONTAMINATED SHOES, AND LEATHER ARTICLES.
,
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NIOSH APPROVED MASKS IN ABSENCE OF PROPER ENVIRONMENTAL CONTROLS.
Ventilation:LOCAL REQUIRED TO DISSIPATE VAPORS. MECHANICAL: RECOMMENDED. SPECIAL: BLOW VAPORS AWAY FROM OPERATOR.
Protective Gloves:IMPERVIOUS GLOVES. Eye Protect
ion:SPLASH PROOF GOGGLES OR FACE SHIELD.
Other Protective Equipment:IMPERVIOUS GARMENTS, SAFETY SPRAY OR SHOWER, EYE BATH.
Work Hygienic Practices:PRACTICE GOOD CAUTION, PERSONAL CLEANLINESS TO PREVENT EYE AND SKIN CONTACT. WASH EXPOSED AREAS ESPECIALLY BEFORE EATING.
Supplemental Safety and Health
PITEM IS PART OF A KIT.
======================================
HCC:V5
Boiling Pt:B.P. Text:N/D
Spec Gravity:1.1-1.2 H20=1
Solubility in Water:VERY SLIGHT
A
ppearance and Odor:BLACK PASTE WITH AN AMINE ODOR.
========= Stability and Reactivity Data ===========
Stability Indicator/Materials to Avoid:YES
ACIDS AND OXIDIZING AGENTS.
Stability Condition to Avoid:PROLONGED STORAGE OVER 90F.
Hazardous Decomposition Products:NITROGEN OXIDES, CARBON MONOXIDE AND OR CARBON DIOXIDE.
======== Disposal Considerations =============

Y CLOSED

Waste Disposal Methods:REACT THIS PART B WITH PART A AND DISPOSE OF IN ACCORDANCE WI

TH FEDERAL, STATE, AND LOCAL REGULATIONS.

========== Other Information ==============

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.