

TECHNICAL CHEMICAL COMPANY -- J. DEERE 80% S/F 7 OZ. EA UN1960 (SEE SUPP) --
6850-01-082-6783

===== Product Identification =====

Product ID:J. DEERE 80% S/F 7 OZ. EA UN1960 (SEE SUPP)

MSDS Date:06/15/1995

FSC:6850

NIIN:01-082-6783

Status Code:A

MSDS Number: CKPYR

=== Responsible Party ===

Company Name:TECHNICAL CHEMICAL COMPANY

Address:10737 SPANGLER ROAD

Box:20098

City:DALLAS

State:TX

ZIP:75220

C

Country:US

Info Phone Num:972-556-1421

Emergency Phone Num:214-556-1421

Resp. Party Other MSDS Num.:RE336361

CAGE:8X792

=== Contractor Identification ===

Company Name:DEERE AND CO

Address:JOHN DEERE RD

Box:City:MOLINE

State:IL

ZIP:61265

Country:US

Phone:309-765-8000

CAGE:75160

Company Name:SHEFFORD-MEADE INC

Address:498 RED LION RD

Box:City:WEST CHESTER

State:PA

ZIP:19382

Country:US

Phone:610-793-3340

Contract Num:SP0450-00-M-SD31

CAGE:9U847

Company Name:TECHNICAL CHEMICAL COMPANY

Address:10737 S

PANGLER ROAD
Box:20098
City:DALLAS
State:TX
ZIP:75220-7101
Country:US
Phone:972-556-1421
CAGE:8X792

=====
===== Composition/Information on Ingredients =====

Ingred Name:ETHYL ETHER (CERCLA)
CAS:60-29-7
RTECS #:KI5775000
= Wt:80.
Other REC Limits:NONE RECOMMENDED
OSHA PEL:400 PPM
ACGIH TLV:400PPM/500STEL; 9596
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:BUTANE (TOTAL PERCENTAGE OF INGREDIENTS 2 AND 3: 10-20%)
CAS:106-97-8
RTECS #:EJ4200000
Minumum % Wt:10.
Maxumum % Wt:20.
Other REC Limits:NONE RECOMMENDED
OSHA PEL:800 PPM
ACGIH TLV:800 PPM; 9596

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Minumum % Wt:10.
Maxumum % Wt:20.
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9596

Ingred Name:CARBON DIOXIDE
CAS:124-38-9
RTECS #:FF6400000
< Wt:10.
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5000 PPM
ACGIH TLV:5000PPM/30000STEL;96

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATE, SOLVENT DEWAXED (MILD),
HEAVY PARAFFINIC/LUBRICATING OI

L
CAS:64742-65-0
RTECS #:PY8038500
< Wt:10.
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 AS OIL MIST
ACGIH TLV:5 MG/M3 AS OIL MIST

=====
Hazards Identification
=====

LD50 LC50 Mixture:NO DATA PROVIDED BY RESPONSIBLE PARTY.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Health Hazards Acute and Chronic:NO DATA PROVIDED BY RESPONSIBLE PARTY.
Explanation of Carcinogenicity:NO DATA PROVIDED BY RESPONSIBLE PARTY.
Effects of Overexposure:DROWSINESS,
ASPHIXIATION, FROSTBITE: NECROSIS
BY LIP AND TONGUE, BLANCHING OF SKIN, PAIN AND TENDERNESS.
Medical Cond Aggravated by Exposure:NO DATA PROVIDED BY RESPONSIBLE
PARTY.

=====
First Aid Measures
=====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALATION: REMOVE TO
FRESH AIR. KEEP WARM AND AT REST. PROVIDE ARTIFICIAL
RESPIRATION/OXYGEN/CPR IF NEEDED. DO NOT GIVE STIMULANTS
(ADREHALINE, EPINIPHRINE OR HA ND HELD AEROSOLS). EYES:FLUSH
WITH
WATER FOR 20 MINUTES. FLUSH EXPOSED AREA WITH LUKEWARM WATER OR
OTHERWISE WARM SKIN SLOWLY. FROSTBITE IS PROBABLE. SKIN:FLUSH WITH
WATER. TREAT FOR FROSTBITE IF NEED ED. ORAL:GET MEDICAL ATTENTION
IMMEDIATELY - FROSTBITE IS PROBABLE. WARM SKIN SLOWLY.

=====
Fire Fighting Measures
=====

Flash Point:=-60.C, -76.F
Autoignition Temp:=-405.C, 761.F
Lower Limits:1.9
Upper Limits:9.5
Extinguishing Media:NO DATA PROVIDED BY RESPONSIBLE PARTY.
Fire

Fighting Procedures:WHEN FIGHTING FIRE OR INVOLVED WITH THIS PRODUCT, USE SELF CONTAINED BREATHING APPARATUS. PROTECTIVE CLOTHING SHOULD MINIMIZE EXPOSED SKIN AND INCLUDE GOGGLES, FULL FACED SHEILD IF POSSIBLE AND LINED RUBBER GLOVES.

Unusual Fire/Explosion Hazard:NO DATA PROVIDED BY RESPONSIBLE PARTY.

===== Accidental Release Measures =====

Spill Release Procedures:FOLLOW ACCEPTED INDUSTRY PRACTICES AND/OR COMPLY WITH APPLICABLE FEDERAL, STATE, AND LOCAL GOVERNMENT

REGULATIONS. CHECK BEFORE HANDLING.

Neutralizing Agent:NO DATA PROVIDED BY RESPONSIBLE PARTY.

===== Handling and Storage =====

Handling and Storage Precautions:ALL IGNITION SOURCES SHOULD BE ELIMINATED. SMOKING SHOULD BE PROHIBITED IN STORAGE AREAS. ELECTRICAL INSTALLATIONS SHOULD BE IN ACCORDANCE WITH ARTICLE 501 OF THE NATIONAL ELECTRICAL CODE. NFPA FLAMMA BLE AND COMBUSTIBLE CODE, SHOULD BE FOLLOWED FOR ALL STORAGE AND HANDLING.

Other Precautions:FREQUENT CAREFUL LEAKAGE INSPECTION SHOULD BE DONE. AUTOMATIC SPRINKLER SYSTEMS SHOULD BE PROVIDED. ISOLATE OXIDIZER CHEMICALS CAPABLE OF SPONTANEOUS HEATING, MATERIALS REACTING WITH AIR OR MOISTURE T O LIBERATE HEAT, IGNITION SOURCES AND EXPLOSIVES. CONSULT LOCAL FIRE CODES FOR ADDITIONAL STORAGE IN FORMATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO DATA PROVIDED BY RESPONSIBLE PARTY.

Ventilatio

n:ADEQUATE VENTILATION. NEVER USE IN A CLOSED AND CONFINED SPACE. LOCAL EXHAUST MAY BE NECESSARY.

Protective Gloves:NO DATA PROVIDED BY RESPONSIBLE PARTY.

Eye Protection:SAFETY GOGGLES

Other Protective Equipment:NO DATA PROVIDED BY RESPONSIBLE PARTY.

Work Hygienic Practices:EXPOSED EMPLOYEES SHOULD EXERCISE REASONABLE PERSONAL CLEALINESS; THIS INCLUDES CLEANSING EXPOSED SKIN AREAS SEVERAL TIMES DAILY. LAUNDER CLOTHES AT LEAST TWICE WEEKLY.

Supplemental Safety and Health

THIS ITEM IS

FOR USE WITH TRACTORS ONLY. NOT FOR AUTOMOBILE USE.
SHEFFORD-MEADE, INC P/N: RE336361

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:=34.5C, 94.1F

Melt/Freeze Pt:M.P/F.P Text:FR116.2

Vapor Density:>1.5

Spec Gravity:0.721

Evaporation Rate & Reference:>1 (N-BUTYL ACETATE=1)

Solubility in Water:>1

Appearance and Odor:BLUE LIQUID AND BLUE TINGED VAPOR; SLIGHT ETHEREAL
ODOR.

===== Stability and Reactivity Data =====

Sta

bility Indicator/Materials to Avoid:NO

NO DATA PROVIDED BY RESPONSIBLE PARTY.

Stability Condition to Avoid:KEEP AWAY FROM HEAT, SPARKS AND FLAMES,
PRODUCTS TEND TO FORM EXPLOSIVE PEROXIDES UNDER THE INFLUENCE OF
AIR AND LIGHT AND ON LONG STANDING.

Hazardous Decomposition Products:NO DATA PROVIDED BY RESPONSIBLE PARTY.

===== Toxicological Information =====

Toxicological Information:NO DATA PROVIDED BY RESPONSIBLE PARTY.

===== Ecological Inf
ormation =====

Ecological:NO DATA PROVIDED BY RESPONSIBLE PARTY.

===== Disposal Considerations =====

Waste Disposal Methods:NO DATA PROVIDED BY RESPONSIBLE PARTY.

===== MSDS Transport Information =====

Transport Information:DOT SHIPPING NAME: ENGINE STARTING FLUID. DOT
HAZARD CLASS: FLAMMABLE GAS. DOT ID NUMBER: UN1960.

===== Regulatory Information =====

SARA Title III Info

Information: NO DATA PROVIDED BY RESPONSIBLE PARTY.

Federal Regulatory Information: NO DATA PROVIDED BY RESPONSIBLE PARTY.

State Regulatory Information: NO DATA PROVIDED BY RESPONSIBLE PARTY.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.