

DISTEC, INC -- TFL 50 DRY LUBE, 60132(5 OZ); 60133(10 OZ) -- 9150-01-339-6225

===== Product Identification =====

Product ID:TFL 50 DRY LUBE, 60132(5 OZ); 60133(10 OZ)

MSDS Date:06/19/1997

FSC:9150

NIIN:01-339-6225

Status Code:A

MSDS Number: CKTMY

=== Responsible Party ===

Company Name:DISTEC, INC

Address:914 ARCTIC STREET, BLDG #777

City:BRIDGEPORT

State:CT

ZIP:19804

Country:US

Info Phone Num:800-

643-6735

Emergency Phone Num:800-424-9300

Chemtrec Ind/Phone:(800)424-9300

CAGE:UO041

=== Contractor Identification ===

Company Name:DISTEC, INC

Address:914 ARCTIC STREET, BLDG #777

Box:City:BRIDGEPORT

State:CT

ZIP:19804

Country:US

Phone:800-643-6735

CAGE:UO041

Company Name:WET'N DRY LUBES INC

Address:242 N JAMES ST #106

City:WILMINGTON

State:DE

ZIP:19804

Phone:(201) 943-1130

CAGE:PO155

===== Composition/Information on Ingredients =====

Ingred Name:SOLVENT NAPHTHA (PETROLEUM)

, LIGHT ALIPH.  
CAS:64742-89-8  
&lt; Wt:30.

Ingred Name:FLUOROCARBON TELOMER  
&lt; Wt:10.

Ingred Name:PROPELLANT (CONSIST OF PROPANE, CAS 74-98-6 {20%} AND  
ISOBUTANE, CAS 75-28-5 {80%})  
&lt; Wt:70.

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:SHORT TERM: INHALATION: MAY CAUSE  
IRRITATION OF RESPIRATORY TRACT. INTENTIONAL MISUSE OF THIS PRODUCT  
BY DELIBERATELY CONCENTRATING AND INHALING CAN BE HARMFUL OR FATAL.  
INGESTION: MAY CAUSE GASTROINTESTINAL IRRITATION AND DEPRESSION OF  
CENTRAL NERVOUS SYSTEM. SKIN/EYE: MAY CAUSE IRRITATION. LONG TERM:  
PROLONGED OR REPEATED CONTACT MAY CAUSE DERMATITIS. MAY CAUSE SKIN  
IRRITATION ON PROLONGED OR REPEATED CONTACT.  
Medical Condition Aggravated by Exposure:NONE RECOGNIZED.

=====  
First Aid Measures  
=====

First Aid:INHALATION: IF USER EXPERIENCES DIFFICULTY, MOVE TO AIR FREE  
OF VAPORS. ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION UNTIL  
MEDICAL ASSISTANCE CAN BE RENDERED. INGESTION: DO NOT INDUCE  
VOMITING. CALL POISON CONTROL CENTER, HOSPITAL EMERGENCY ROOM OR  
PHYSICIAN IMMEDIATELY. SKIN: WASH WITH SOAP AND WATER. EYE: FLUSH  
WITH LARGE QUANTITIES OF WATER FOR AT LEAST 15 MINUTES. IF  
IRRITATION FROM CONTACT PERSISTS, GET MEDICAL ATTENTION.

=====  
Fire Fighting Measures  
=====

Extinguishing Media:USE CARBON DIOXIDE, DRY POWDER OR FOAM  
Fire Fighting Procedures:SELF-CONTAINED RESPIRATORY PROTECTION SHOULD  
BE PROVIDED FOR FIREFIGHTERS FIGHTING FLAMES IN BUILDINGS OR  
CONFINED AREAS. STORAGE CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT  
COOL WITH WATER SPRAY TO PREVENT PRESSURE BUILDUP.  
Unusual Fire/Explosion Hazard:CONTENTS UNDER PRESSURE. DO NOT PUNCTURE,  
INCINERATE OR STORE ABOVE 120 F. EXPOSURE TO HEAT OR PROLONGED  
EXPOSURE TO SUN MAY CAUSE BURSTING. ISOLATE FROM HEAT, ELECTRICAL  
E

QUIPMENT, SPARKS, OPEN FLAMES AND HOT SURFACES.

===== Accidental Release Measures =====

Spill Release Procedures: AVOID BREATHING VAPORS. VENTILATE AREA. FLUSH LARGE SPILLS OF MATERIAL INTO SUITABLE RETAINING AREA OR CONTAINERS WITH LARGE QUANTITIES OF WATER. SMALL SPILL CAN BE ABSORBED BY APPROPRIATE INERT ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions: DO NOT STORE NEAR FLAMES OR AT ELEVATED TEMPERATURES.

Other Precautions: READ CAREFULLY ALL CAUTIONS AND DIRECTIONS ON PRODUCT LABEL BEFORE USE. SINCE EMPTY CONTAINER RETAINS RESIDUE, FOLLOW ALL LABEL WARNING EVEN AFTER CONTAINER IS EMPTY. DISPOSE OF EMPTY CONTAINER ACCORDING TO LOCAL REGULATIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: FOR OSHA CONTROLLED WORK PLACE, USE ONLY WITH ADEQUATE VENTILATION UNDER ENGINEERED AIR CONTROL SYSTEMS DESIGNED TO PROVIDE MAXIMUM APPROPRIATE TLV. FOR OCCASIONAL USE WHERE ENGINEERED AIR CONTROL IS NOT FEASIBLE, USE NIOSH APPROVED RESPIRATORS. FOR OCCASIONAL CONSUMER USE, USE ONLY WITH ADEQUATE VENTILATION.

Ventilation: ADEQUATE VENTILATION MUST BE PROVIDED. SEE RESPIRATORY PROTECTION ABOVE.

Protective Gloves: USE IMPERMEABLE GLOVES TO PREVENT SKIN CONTACT.

Eye Protection: SAFETY GLASSES, CHEMICAL GOGGLES AND/OR FACESHIELD

Other Protective Equipment: USUALLY NONE REQUIRED.

Work Hygienic Practices:

WASH HANDS THOROUGHLY AFTER USE. BEFORE REUSE, THOROUGHLY CLEAN ANY CLOTHING OR PROTECTIVE EQUIPMENT WHICH HAS BEEN CONTAMINATED BY PRIOR USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC: V3

Boiling Pt: B.P. Text: 185-230F

Vapor Density: >AIR

VOC Grams/Liter: 7.06

Evaporation Rate & Reference: