

EASTMAN KODAK COMPANY -- 158 2352,PT A,KODAK EKTACOLOR RA BLEACH FIXER / RA-4 --
6750-01-376-5884

===== Product Identification =====

Product ID:158 2352,PT A,KODAK EKTACOLOR RA BLEACH FIXER / RA-4

MSDS Date:07/22/2000

FSC:6750

NIIN:01-376-5884

Status Code:A

Kit Part:Y

MSDS Number: CKTYG

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZI

P:14650

Country:US

Info Phone Num:716-722-5151/(800) 242-2424

Emergency Phone Num:716 722-5151

Preparer's Name:NOT PROVIDED

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Minimum % Wt:60.

Maximum % Wt:6

5.
Other REC Limits:NOT PROVIDED
Code:F
Code:F

Ingred Name:AMMONIUM THIOSULFATE
CAS:7783-18-8
RTECS #:XN6465000
= Wt:37.

Other REC Limits:NOT PROVIDED
OSHA PEL:NOT PROVIDED
ACGIH TLV:NOT PROVIDED

Ingred Name:SODIUM BISULFITE
CAS:7631-90-5
RTECS #:VZ2000000
Minumum % Wt:1.
Maxumum % Wt:5.
Other REC Limits:NOT PROVIDED
OSHA PEL:NOT PROVIDED
ACGIH TLV:5 MG/M3
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ACETIC ACID
CAS:64-19-7
RTECS #:AF1225000
Minumum % Wt:1.
Maxumum % Wt:5.
Other REC
Limits:NOT PROVIDED
OSHA PEL:25 MG/M3;10 PPM
ACGIH TLV:25 MG/M3;10 PPM
ACGIH STEL:37 MG/M3;15 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NOT PROVIDED
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EFFECTS OF EXPOSURE: INHALATION:
EXPECTED TO BE A LOW HAZARD FOR RECOMMENDED HANDLING. IN CONTACT
WITH STRONG ACIDS OR IF HEATED, SULFITES MAY LIBERATE SULFUR
D

IOXIDE GAS. SULFUR DIOXIDE GAS IS IRRITATING TO THE RESPIRATORY TRACT. SOME ASTHMATICS OR HYPERSENSITIVE INDIVIDUALS MAY EXPERIENCE DIFFICULT BREATHING. EYES: NO SPECIFIC HAZARD KNOWN. MAY CAUSE TRANSIENT IRRITATION. SKIN: THIS MATERIAL HAS A LOW POTENTIAL TO CAUSE ALLERGIC SKIN REACTIONS; HOWEVER, CASES OF HUMAN SKIN SENSITIZATION HAVE BEEN REPORTED. INGESTION: MAY BE HARMFUL IF SWALLOWED.

Explanation of Carcinogenicity: CARCINOGENICITY CLASSIFICATION (COMPONENTS P

RESENT AT 0.1% OR MORE): - INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC): NONE - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS (ACGIH): NONE - NATIONAL TOXICOLOGY PROGRAM (NTP): NONE - OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA): NONE

Effects of Overexposure: INHALATION: IN CONTACT WITH STRONG ACIDS OR IF HEATED, SULFITES MAY LIBERATE SULFUR DIOXIDE GAS. SULFUR DIOXIDE GAS IS IRRITATING TO THE RESPIRATORY TRACT. SOME ASTHMATICS OR HYPERSENSITIVE

INDIVIDUALS MAY EXPERIENCE DIFFICULT BREATHING. EYES: MAY CAUSE TRANSIENT IRRITATION.

Medical Cond Aggravated by Exposure: SOME ASTHMATICS, HYPERSENSITIVE OR SULFITE-SENSITIVE INDIVIDUALS MAY EXPERIENCE DIFFICULT BREATHING, WHEEZING, CHEST TIGHTNESS, STOMACH UPSET, HIVES, FAINTNESS, WEAKNESS AND DIARRHEA.

=====
===== First Aid Measures =====

First Aid: INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. TREAT SYMPTOMATICALLY. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES:

IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. SKIN: WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. WASH CONTAMINATED CLOTHING BEFORE REUSE. DESTROY OR THOROUGHLY CLEAN CONTAMINATED SHOES. INGESTION: DRINK 1-2 GLASSES OF WATER. SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

=====
===== Fire Fighting Measures =====
=====

Flash Point: NONE

Extinguishing Media: FLOOD WITH WATER.

Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS.

Unusual Fire/Explosion Hazard: SOLUTION CONTAINS A STRONG REDUCING AGENT. DRIED PRODUCT RESIDUE CAN ACT AS A REDUCING AGENT.

=====
===== Accidental Release Measures =====

Spill Release Procedures: COLLECT IN A NONCOMBUSTIBLE CONTAINER FOR

es =====

HCC:N1

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:>100.C, 212.F

Melt/Freeze Pt:M.P/F.P Text:NOT PROVIDED

Decomp Temp:Decomp Text:NOT PROVIDED

Vapor Pres:(68F): 24 MBAR (18 MM HG)

Vapor Density:0.6

Spec Gravity:1.23

pH:5.5

Viscosity:NOT PROVIDED

Evaporation Rate & Reference:NOT PROVIDED

Solubility in Water:COMPLETE

Appearance and Odor:LIGHT YELLOW LIQUID. ODOR: AMMONIA

Percent Volatiles by Volume:60-65 WT

Corrosion Rate:NOT PROVIDED

===== Stability and Rea
ctivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS, BASES, STRONG OXIDIZING AGENTS, COMBUSTIBLE MATERIAL,
HALOGENATED MATERIALS, SODIUM HYPOCHLORITE (BLEACH). CONTACT WITH
BASE LIBERATES FLAMMABLE MATERIAL.

Stability Condition to Avoid:STABLE

Hazardous Decomposition Products:AMMONIA, CHLORAMINE, CARBON DIOXIDE,
CARBON MONOXIDE, OXIDES OF NITROGEN, OXIDES OF SULFUR

===== Toxicological Information =====

Toxicological

Information:EFFECTS OF EXPOSURE: INHALATION: EXPECTED TO
BE A LOW HAZARD FOR RECOMMENDED HANDLING. IN CONTACT WITH STRONG
ACIDS OR IF HEATED, SULFITES MAY LIBERATE SULFUR DIOXIDE GAS.
SULFUR DIOXIDE GAS IS IRRITATING TO THE RESPIRATORY TRACT. SOME
ASTHMATICS OR HYPERSENSITIVE INDIVIDUALS MAY EXPERIENCE DIFFICULT
BREATHING. EYES: NO SPECIFIC HAZARD KNOWN. MAY CAUSE TRANSIENT
IRRITATION. SKIN: THIS MATERIAL HAS A LOW POTENTIAL TO CAUSE
ALLERGIC SKIN REACTIONS; HOWEVE

R, CASES OF HUMAN SKIN SENSITIZATION
HAVE BEEN REPORTED. INGESTION: MAY BE HARMFUL IF SWALLOWED.

=====
Ecological Information
=====

Ecological:THE FOLLOWING PROPERTIES ARE ESTIMATED FROM THE COMPONENTS
OF THE PREPARATIONS. POTENTIAL TOXICITY: FISH LC50 MG/L: >100.
DAPHNID EC50 MG/L: >100. ALGAL IC50 MG/L: >100. ORGANICS
READILY DEGRADABLE (>70%): YES (7 DAYS). POTENTIAL
BIOACCUMULATION: LOG POW 100. AFTER DILUTION WITH A LARGE
AMOUNT OF WATER, FOLLOWED BY SECONDARY WASTE TREATMENT, THIS
MATERIAL IS NOT EXPECTED TO CAUSE ADVERSE ENVIRONMENTAL EFFECTS.

=====
Disposal Considerations
=====

Waste Disposal Methods:DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT
TO NATIONAL, STATE, OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE
AMOUNTS OF WATER. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE,
FOLLOW LABEL WARNINGS EVEN AFTER CONTAINER IS EMPTIED.

=====
MSDS Transport Information
=====

Transport Information:FOR TRANSPORTATION INFORMATION REGARDING THIS
PRODUCT CALL THE KODAK WORLDWIDE TRANSPORTATION HAZMAT HOT LINE:
(716) 722-2400 BETWEEN 8 A.M. AND 5 P.M. (EASTERN STANDARD TIME),
MONDAY THROUGH FRIDAY .

=====
Regulatory Information
=====

SARA Title III Information:CHEMICAL(S) SUBJECT TO THE REPORTING
REQUIREMENTS OF SECTION 313 OR TITLE III OF THE SUPERFUND
AMENDMENTS AND REAUTHORIZATION ACT (SARA) OF 1986 AND 40 CFR
PART 372: AMMONIUM THIOSULFATE (AS CHEMICAL SOURCE OF AQUEOUS
AMMONIA)

Federal Regulatory Information:NOT PROVIDED

State Regulatory Information:MATERIAL(S) KNOWN TO THE STATE OF
CALIFORNIA TO CAUSE CANCER: NONE - MATERIAL(S) KNOWN TO THE STATE
OF CALIFORNIA TO CAUSE ADVERSE REPRODUCTIVE EFFECTS: NONE

=====
Other Information
=====

Disclaimer (provided with this information by the compiler)

g agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.