

F.M. SOLUTIONS, INC. (FORMERLY JC ENTERPRISES, INC) -- ENTERPRISE 1000: LUBRICATING OIL  
-- 9150-00-252-6382

===== Product Identification =====

Product ID:ENTERPRISE 1000: LUBRICATING OIL

MSDS Date:08/03/2000

FSC:9150

NIIN:00-252-6382

Status Code:A

MSDS Number: CKXVT

=== Responsible Party ===

Company Name:F.M. SOLUTIONS, INC. (FORMERLY JC ENTERPRISES, INC)

Box:212

City:ROCKLAND

State:DE

ZIP:19732

Country:US

Info Phone Num:(302) 478-8326 FAX-302-478-8326

Emergency Phone Num:302-478-8326

Preparer's Name:V. C. WOLFF

CAGE:UO220

=== Contractor Identification ===

Company Name:F.M. SOLUTIONS, INC. (FORMERLY JC ENTERPRISES, INC)

Box:212

City:ROCKLAND

State:DE

ZIP:19732

Country:US

Phone:(302) 478-8326 FAX-302-478-8326

Contract Num:SP0450-01-M-C749

CAGE:UO220

Company Name:SDB CONSULTANTS LTD

Address:401 WHITNEY AVE SUITE 120

Box:City:GRETNA

State:LA

ZIP:70056

Country:US

Phone:504-366-9105

CAGE:0PG

=====  
Composition/Information on Ingredients  
=====

Ingr Name:HAZARDOUS COMPONENTS-SPECIFIC CHEMICAL IDENTITY COMMON NAMES: NONE.  
= Wt:100.  
Code:F

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:NOT ESTABLISHED.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:NOT DETERMINED.  
Medical Cond Aggra  
vated by Exposure:NOT DETERMINED.

=====  
First Aid Measures  
=====

First Aid:INGESTION & INHALATION: NONE SHOULD BE NEEDED. SKIN: FLUSH WITH WATER. EYES: FLUSH WITH WATER 15 MINUTES & SEE DOCTOR.

=====  
Fire Fighting Measures  
=====

Flash Point Method:TCC  
Flash Point:=200.C, 392.F  
MINIMUM  
Extinguishing Media:WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE.  
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND  
PROTECTIVE CLOTHING.  
Unusual Fire/Explosion Hazard:NONE.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:ASORB MATERIAL IN VERMICULITE OR OTHER SUITABLE ABSORBENT AND PLACE IN IMPERVIOUS CONTAINER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:KEEP FROM CONTACT WITH STRONG OXIDIZING MATERIALS.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protectio

n:NONE.

Ventilation:LOCAL EXHAUST: GOOD VENTILATION SHOULD BE SUFFICIENT.

Protective Gloves:STANDARD CHEMICAL OPERATION GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:NONE.

Work Hygienic Practices:WASH HANDS AFTER HANDLING PRODUCT.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:=400.C, 752.F

Vapor Pres:@185 DEG.C: 1.5

Vapor Density:1.06

Spec Gravity:(H2O=1): 1

Evaporation Rate & Reference:NEGLIGABLE

S

solubility in Water:NONE

Appearance and Odor:COLORLESS TO YELLOW LIQUID: SLIGHT WOOD ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS.

Stability Condition to Avoid:AVOID DIRECT FLAME.

Hazardous Decomposition Products:COMBUSTION WILL PRODUCE CARBON DIOXIDE AND WATER.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE BY INCINERATION OR CONTRACT WITH LICEN

SED CHEMICAL WASTE DISPOSAL AGENCY. DISCHARGE TREATMENT MAY BE SUBJECT TO STATE, FEDERAL OR LOCAL LAWS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional adv

ice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.