

AMERICAN SAFETY TECHNOLOGIES INC -- 76340 RTVS 1657 SEALANT -- 8030-01-435-3104
===== Product Identification =====

Product ID:76340 RTVS 1657 SEALANT
MSDS Date:03/30/1999
FSC:8030
NIIN:01-435-3104
Status Code:A
MSDS Number: CKYYT
=== Responsible Party ===
Company Name:AMERICAN SAFETY TECHNOLOGIES INC
Address:565 EAGLE ROCK AVE
City:ROSELAND
State:NJ
ZIP:07068
Country:US
Info Phone Num:973-403-260
0
Emergency Phone Num:(800)424-9300
Preparer's Name:HENRY SIMMONS
Chemtrec Ind/Phone:(800)424-9300
CAGE:88444

=== Contractor Identification ===
Company Name:AMERICAN SAFETY TECHNOLOGIES INC
Address:565 EAGLE ROCK AVE
Box:City:ROSELAND
State:NJ
ZIP:07068
Country:US
Phone:973-403-2600
CAGE:88444

===== Composition/Information on Ingredients =====

Ingred Name:ALUMINIUM
CAS:7429-90-5
RTECS #:BD0330000
Minumum % Wt:60.
Maxumum % Wt:75.
OSHA PEL:15 MG/M3
ACGIH TLV:10 MG/M3

Ingred N

ame:VM&P NAPTHA
CAS:64742-89-8
Code:F
< Wt:1.

=====
Hazards Identification
=====

Health Hazards Acute and Chronic:ACUTE OVEREXPOSURE-IRRITANT TO SKIN, EYES AND RESPIRATOY TRACT. CHRONIC OVEREXPOSURE-PROLONGED BREATHING OF VAPORS CAN CAUSE DIZZINESS, NAUSEA, AND HEADACHE. REPEATED CONTACT CAN CAUSE DEFATTING AND D ERMATITIS.

Medical Cond Aggravated by Exposure:

=====
First Aid Measures
=====

First Aid:INHAL

ATION: REMOVE TO FRESH AIR. RESTORE BREATHING. TREAT SYMPTOMATICALLY. CALL A PHYSICIAN. EYE CONTACT: FLUSH IMMEDIATELY WITH LARGE VOLUMES OF WATER FOR AT LEAST 15 MINUTES. TAKE TO A PHYSICIAN IF IRRITATION PERSISTS INGESTION: DRINK 1 TO 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITUS WHICH CAN BE FATAL. SKIN CONTACT: WASH AFFECTED AREA WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PH
YSICIAN IF IRRITATION PERSISTS.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:>200.C, 392.F

=====
Accidental Release Measures
=====

Spill Release Procedures:SPILLS-ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND PICK UP WITH SHOVEL. ELIMINATE ALL IGNITION SOURCES (FLARES, FLAMES INCLUDING PILOT LIGHTS, ELECTRICAL SPAR KS). STOP SPILL AT SOURCE.

=====
Handling and Storage
=====

Handling and Storage Precautions:PRACTICE REASONABLE CARE AND CLEANLINES. DO NOT STORE OR USE HEAR HEAT, SPARKS, OR OPEN FLAMES.
Other Precautions:AVIOD GROSS CONTAMINATION OF SKIN. WASH OFF WITH SOAP AND WATER.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH APPROVED ORGANIC VAPOR CARTRIDGE OR RESPIRATOR DESIGNED TO REMOVE COMBINATION OF PARTICULATES AND VAPOR WHERE CONCE

NTRATIONS ARE ENCOUNTERED.

Ventilation:LOCAL EXHAUST OF CAPABLE OF MINIMIZING VAPOR
CONCENTRATIONS. USE WITH ADEQUATE VENTILATION.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Vapor Pres:45 MMHG

Vapor Density:3.9

Evaporation Rate & Reference:1.6

Percent Volatiles by Volume: