

EASTMAN KODAK COMPANY -- KODAK PHOTOLIFE PHOTO/ELECTRONIC BATTERY SIZE:
IEC-MR52, KX -- 6135-00-826-4798

=====
Product Identification
=====

Product ID:KODAK PHOTOLIFE PHOTO/ELECTRONIC BATTERY SIZE: IEC-MR52, KX

MSDS Date:10/30/1990

FSC:6135

NIIN:00-826-4798

Status Code:A

MSDS Number: CKZVB

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State

:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

=====
Composition/Information on Ingredients
=====

Ingred Name:POTASSIUM HYDROXIDE (AQUEOUS SOLUTION CONCENTRATION: 43%)

Fraction by Wt: 3.5%

Ingred Name:MERCURIC OXIDE

CAS:21908-53-2

RTECS #:OW8750000

Fraction by Wt: 37.6%

Ingred Name:MERCURY

= Wt:.8

Ingred Name:ZINC

= Wt:8.5

=====
Hazards Identification
=====

Routes of Entry: Inhalation:UNKNOWN Skin:NO Ingestion:NO

Medical Cond Aggravated by Exposure:

=====
First Aid Measures
=====

First Aid:ELECTROLYTE CONTACT SKIN - IMMEDIATELY FLUSH WITH PLENTY OF
WATER FOR AT LEAST 15 MINUTES. IF SYMTOMS ARE PRESENT AFTER
FLUSHING, GE

T MEDICAL ATTENTION. EYES - IMMEDIATELY FLUSH WITH
PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION.
BATTERY INGESTION: OBTAIN IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Extinguishing Media:USE AN EXTINGUISHING MEDIUM APPROPRIATE FOR THE
SURROUNDING FIRE.

Fire Fighting Procedures:USE A POSITIVE PRESSURE SELF-CONTAINED
BREATHING APPARATUS IF BATTERIES ARE INVOLVED IN A FIRE. FULL
PROTECTIVE CLOTHING IS NECESSARY.

Unusual Fire/Explosion Hazard:BATTERIES MAY RELEASE TOXIC VAPORS AND/OR
IRRITATING FUMES IF EXPOSED TO FIRE OR HIGH TEMPERATURES.
BATTERIES MAY VENT AND/OR EXPLODE IF EXPOSED TO EXCESSIVE HEAT OR
FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:SPILL RELEASE PROCEDURES: NK NEUTRALIZING
AGENT: NK WASTE DISPOSAL METHOD: CONSULT LOCAL, STATE AND FEDERAL
ENVIRONMENTAL PROTECTION AUTHORITIES FOR THE MOST CURRENT
REGULATIONS REGARDING DISPOSAL OF BATTERIES.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE BATTERIES IN A MANNER
THAT ALLOWS TERMINALS TO SHORT CIRCUIT. STORE BATTERIES IN A COOL
(BELOW 70F), DRY AREA THAT IS SUBJECT TO LITTLE TEMPERATURE CHANGE.
DO NOT PLACE NEAR HEATING EQUIPMENT, NOR EXPOSE TO DIRECT
SUNLIGHT FOR LONG PERIODS. *

Other Precautions:*ELEVATED TEMPERATURES CAN RESULT IN REDUCED BATTERY
SERVICE LIFE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NP
Supplemental Safety and Health

===== Toxicological Information =====

Toxicological Information:THE MATERIALS IN THIS MSDS MAY ONLY REPRESENT
A HAZARD IF THE INTEGRITY OF THE BATTERY IS COMPROMISED.

===== Ecological Information =====

Ecological:THESE BATTERIES ARE NOT DESIGNED TO BE RECHARGED. CHARGING
A BATTERY

TERY MAY RESULT IN ELECTROLYTE LEAKAGE AND/OR EXPLOSION.

NEVER DISASSEMBLE A BATTERY. SHOULD A BATTERY UNINTENTIONALLY BE CRUSHED THUS RELEASING ITS CONTENTS, RUBBER GLOVES MUST BE USED TO HANDLE ALL BATTERY COMPONENTS. IN THE EVENT OF SKIN OR EYE EXPOSURE TO THE ELECTROLYTE REFER TO FIRST AID INFORMATION.

BATTERY SHORT CIRCUIT: MORE THAN A MOMENTARY SHORT CIRCUIT WILL GENERALLY REDUCE THE BATTERY SERVICE LIFE. EXTENDED SHORT CIRCUITING CREATES HIGH TEMPERATURES

IN THE CELL. HIGH

TEMPERATURES CAN CAUSE SKIN BURNS AND CAUSE THE CELL TO VENT OR EXPLODE.**

===== Disposal Considerations =====

Waste Disposal Methods: WASTE DISPOSAL METHOD: CONSULT LOCAL, STATE AND FEDERAL ENVIRONMENTAL PROTECTION AUTHORITIES FOR THE MOST CURRENT REGULATIONS REGARDING DISPOSAL OF BATTERIES. DO NOT INCINERATE OR EXPOSE BATTERIES TO FIRE. STORAGE AND HANDLING:

===== MSDS Transport Information =====

=====

Transport Information: **MIXED BATTERIES AND TYPES: THE USE OF OLD AND NEW BATTERIES OR BATTERIES OF VARYING SIZES AND TYPES IN THE SAME BATTERY ASSEMBLY SHOULD BE AVOIDED. THE BATTERIES ELECTRICAL CHARACTERISTICS AND CAP ABILITIES VARY AND DAMAGE MAY RESULT TO THE BATTERIES OR ELECTRICAL EQUIPMENT. BATTERY CONNECTION: USE NICKEL PLATED STEEL (OR STAINLESS STEEL) FOR POWER TERMINAL CONTACTS. DO NOT DIRECTLY SOLDER TO THE BATTERY. MAY CAUSE VENTING AND/OR

EXPLOSION. BATTERY ENCASEMENT: AVOID ENCASING BATTERIES IN AIRTIGHT COMPARTMENTS. FLAMMABLE HYDROGEN GAS, NORMALLY GENERATED, CAN FORM EXPLOSIVE MIXTURES.***

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information

to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.