

NILES CHEMICAL PAINT -- RDS-208A YELLOW STENCIL CS -- 7510-00-183-7698

=====  
Product Identification  
=====

Product ID:RDS-208A YELLOW STENCIL CS

MSDS Date:01/11/1989

FSC:7510

NIIN:00-183-7698

Status Code:A

MSDS Number: CKZZW

=== Responsible Party ===

Company Name:NILES CHEMICAL PAINT

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Info Phone Num:616-683-3377

Emergency Phon

e Num:219-236-5856

Preparer's Name:MICHAEL LICHATOWICH

CAGE:02388

=== Contractor Identification ===

Company Name:NILES CHEMICAL PAINT

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Phone:616-683-3377/219-236-5856

CAGE:02388

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ACETONE VAPOR PRESSURE=266 MM @ 77F

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 40%

OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

ACGIH STEL:1000 PPM

EPA Rpt Qty:

5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 10%  
OSHA PEL:200 PPM  
ACGIH TLV:100 PPM  
ACGIH STEL:150 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ALKYD RESIN  
RTECS #:1000239AR  
Fraction by Wt: 5%

Ingred Name:XYLENE VAPOR PRESSURE=7 MM @ 20 C.  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 5%  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM  
ACGIH STEL:150 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOBUTYL KETONE VAPOR P  
RESSURE=15 MM @ 20 C  
CAS:108-10-1  
RTECS #:SA9275000  
Fraction by Wt: 1%  
OSHA PEL:100 PPM  
ACGIH TLV:50 PPM/75 STEL; 9293  
ACGIH STEL:75 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:PROPRIETARY INGREDIENTS  
RTECS #:1004255PI  
Fraction by Wt: BALANCE

Ingred Name:PROPANE VAPOR PRESSURE=4400 MM @ 20 C. (AS BLEND WITH  
ISOBUTANE)  
CAS:74-98-6  
RTECS #:TX2275000  
Fraction by Wt: 15%  
OSHA PEL:1000

Ingred Name:ISOBUTANE VAPOR PRESSURE=4400 MM @ 20 C. AS BLEND W/  
PROPANE.  
CAS:75-28-5  
RTEC

S #:TI4300000

Fraction by Wt: 15%

Ingred Name:MINERAL SPIRITS VAPOR PRESSURE=2 MM @ 20 C

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 1%

OSHA PEL:500 PPM

ACGIH TLV:100 PPM

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:INHAL: ACUTE: CNS DEPRESSION:

HEADACHES, DIZZINESS, NAUSEA, & LOSS OF CONSCIOUSNESS. CHRONIC:  
PERMANENT BRAIN & NERVOUS SYST DAMAGE. SKIN: DEFATTING, DRY  
ING,

IRRIT & DERMATITIS. EYE: IRRITATION. PROPANE IS LISTED AS AN  
ASPHYXIANT BY OSHA.

Explanation of Carcinogenicity:NONE

=====  
===== First Aid Measures =====

First Aid:INHALATION: MOVE VICTIM TO FRESH AIR AT ONCE, IF BREATHING  
DIFFICULT: GIVE OXYGEN. IF BREATHING STOPPED-PERFORM ARTIFICIAL  
RESPIRATION. GET MED ATTN. SKIN: WASH W/SOAP & WATER. REMOVE  
CONTAMINATED CLOTHING. REUSE ONLY WHEN CLEANED. IF IRRITATION  
PERSISTS, GET MED ATTN.

EYES: FLUSH W/ WATER FOR 15 MINUTES,  
HOLDING EYE LIDS OPEN. GET MED ATTN.

=====  
===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point: