

3M -- SCOTCH BRAND ALUMINUM FOIL TAPE NO 425 -- 7510-00-071-6854

=====
Product Identification
=====

Product ID:SCOTCH BRAND ALUMINUM FOIL TAPE NO 425

MSDS Date:02/14/1995

FSC:7510

NIIN:00-071-6854

Status Code:A

MSDS Number: CLBDJ

=== Responsible Party ===

Company Name:3M

Address:3M CENTER

City:ST PAUL

State:MN

ZIP:55144-1000

Country:US

Info Phone Num:612-733-1110

Emergency Phone Num:0000000000

CA

GE:76381

=== Contractor Identification ===

Company Name:MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

=====
Composition/Information on Ingredients
=====

Ingred Name:ALUMINUM

CAS:7429-90-5

RTECS #:BD0330000

Minumum % Wt:60.

Maxumum % Wt:100.

Ingred Name:ACRYLIC ACID-ISOOCTYL ACRYLATE POLYMER

CAS:79-10-7

RTECS #:AS4375000

Minumum % Wt:10.

Maxumum % Wt:30.

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Health Hazards Acute and Chronic:EYE CONTACT IS NOT EXPECTED. NO ADVERSE HEALTH EFFECTS OF SKIN CONTACT. MECHANICAL SKIN IRRITATION SIGNS CAN INCLUDE ITCHING AND REDNESS. NOADVERSE EFFECTS ARE EXPECTED FROM INHALTION. INGESTION IS NO T LIKELY.NO ADVERSE HEALTH EFFECTS.

Medical Cond Aggravated by Exposure:

=====
===== First Aid Measures =====

=====

First Aid:NO NEED FOR FIRST AID IS ANTICIPATED.

=====
===== Fire Fighting Measures =====

Extinguishing Media:NOT COMBUSTABLE. CHOOSE MATERIAL SUITABLE FOR SURROUNDING FIRE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:IN THE USA CALL 612-733-1110 OR 612-733-6100 FOR 24-HOUR SPILL ASSISTANCE. COLLECT SPILLED MATERIAL.

=====
===== Handling and Storage =====

Handling and Storage
Precautions:STORE AT ROOM TEMPATURE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:AVOID PROLONGED INH VAPORS. KEEP CONTAINERS CLOSED.

Ventilation:USE MECH VENTILATION TO INSURE VAPOR REMOVAL.

Protective Gloves:IMPERVIOUS

Eye Protection:CHEMICAL GOGGLES

Other Protective Equipment:WHEN SPRAYING,USE BOOTH OR LOCAL EXH VENTILATION.

Supplemental Safety and Health

UPDATE PER 3M MSDS(OSHA) DTD 2NOV85,3M DOC#1027895. FORMER P/N: SCOTCHGRI

P 1357 CONTACT CEMENT.THIS NSN CANCELLED & REPLACED BY NSN
8040002738717. INGRED INFO VIA PHONE JA VOLNESS (3M) 13MAY86

===== Physical/Chemical Properties =====

Solubility in Water:2.2
Appearance and Odor:ROLL OF TAPE SILVER COLOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:RECLAIM IF FEASIBLE

===== Regulatory Information =====

SARA Title III Information:ALUMINUM
State Regulatory Information:

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability
for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.