

AMERICAN CODING AND MARKING IN -- 2023STRATA BLUE INK MARKING

=====  
MSDS Safety Information  
=====

FSC: 7510  
NIIN: 00-286-5362  
MSDS Date: 09/11/1991  
MSDS Num: CLBHY  
Product ID: 2023STRATA BLUE INK MARKING  
MFN: 02  
Responsible Party  
Cage: 0HB89  
Name: AMERICAN CODING AND MARKING INK CO  
Address: 1220 NORTH AVENUE  
City:  
PLAINFIELD NJ 07062  
Info Phone Number: 908-756-0373; 908-769-1386  
Emergency Phone Number: 0000000000  
Preparer's Name: RICHARD A. SWEET  
Proprietary Ind: Y  
Review Ind: Y  
Published: Y

=====  
Contractor Summary  
=====

Cage: 0HB89  
Name: AMERICAN CODING AND MARKING INK CO  
Address: 1220 NORTH AVENUE  
City: PLAINFIELD NJ 07062  
Phone: 908-756-0373; 908-769-1386

=====  
Item Description Information  
=====

Item Manager: GSA  
Item Name: INK,MARKING,PARACHUTE  
Specification Number: MIL-I-6903  
Unit of Issue: PT  
UI Container Qty: 1

=====  
Ingredients  
=====

Name: \*\*\* PROPRIETARY \*\*\*  
-----  
=====

=====  
Health Hazards Data  
=====

=====  
Effects of Exposure: INGESTION: SLIGHTLY IRRITATING TO GASTROINTESTINAL TRACT.  
OR HIGHLY TOXIC. WILL CAUSE HEADACHE, DIARRHEA, DROWSINESS, BREATHING  
DIFFICULTIES, NAUSEA, VOMITING AND UNCONSCIOUSNESS. EYES: MODERATELY IR  
RITATING. CAUSE REDNESS, AND BLURRED VISION, BUT REVERSIBLE WITHIN SEVEN  
DAYS. SKIN: SLIGHTLY IRRITATING. PROLONGED OR WIDESPREAD CONTACT MAY LEAD TO  
DEFATTING OR DERMITITIS. INHALATION: TOXIC OR MODERATELY IRRITATING TO NASAL  
AND R

ESPIRATORY TRACTS. CAN CAUSE HEADACHE, DIZZINESS, DROWSINESS, BREATHING  
DIFFICULTIES, NAUSEA, UNCONSCIOUSNESS.

Signs And Symptoms Of Overexposure: TARGET ORGANS: LIVER, LUNGS AND SKIN

First Aid: INGESTION: INDUCE VOMITING, IF CONSCIOUS, AS DIRECTED BY MEDICAL  
PERSONNEL. EYES: FLUSH IMMEDIATELY WITH WATER FOR AT LEAST 15 MINUTES. SEEK  
MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. THOROUGHLY WASH WITH  
SOAP AND WATER. SEEK MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. IF

NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE  
OXYGEN. GET MEDICAL ATTENTION.

=====  
Handling and Disposal

=====  
Spill Release Procedures: SECURE AREA AND REMOVE ALL SOURCES OF IGNITION AND  
HEAT. PREVENT ADDITIONAL DISCHARGE OF MATERIAL. ABSORB SMALL SPILLS WITH  
SAND, FILTER-AID VERMICULITE OR OTHER INERT ABSORBENT MATERIAL. FOR LARGE SP  
ILLS PREVENT MATERIAL FR

OM ENTERING SEWERS OR WATER COURSES. CONTAIN SPILL

WITH SAND OR EARTH DIKES. RECOVER AS MUCH AS POSSIBLE BY PUMPING.

Waste Disposal Methods: CONSULT FEDERAL, STATE AND LOCAL REGULATIONS FOR  
ACCEPTED PROCEDURES OF DISPOSAL, AND ANY REPORTING OR NOTIFICATION  
REQUIREMENTS.

Handling And Storage Precautions: STORE IN TIGHTLY CLOSED PROPERLY VENTED  
CONTAINER AWAY FROM HEAT, SPARKS, OPEN FLAME OR STRONG OXIDIZING AGENTS.  
CONTAINERS MUST BE PROPERLY GROUNDED. DO NOT UNSCREW UNTIL ALL PRESSURE  
HAS  
BEEN RELEASED.

Other Precautions: SEE HARD COPY MSDS FOR FURTHER INFORMATION.

=====  
Fire and Explosion Hazard Information

=====  
Flash Point Method: TCC

Flash Point: =43.3C, 110.F

Flash Point Text: 110 F

Lower Limits: 0.5

Extinguishing Media: WATER FOG, MULTIPURPOSE FOAM, DRY CHEMICAL, CO2

Fire Fighting Procedures: FIGHT AS VOLATILE LIQUID FIRE. WATER SPRAY MAY SPREAD  
FIRE.

Unusual Fire/E

Explosion Hazard: USE WATER SPRAY TO COOL FIRE-EXPOSED SURFACES AND TO PROTECT PERSONNEL. EMPTY CONTAINERS RETAIN RESIDUE AND CAN BE DANGEROUS. DO NOT PRESSURIZE CUT WELD BRAZE SOLDER DRILL GRIND EXPOSE TO HEAT OR OTHER FORMS OF IGNITION.

=====  
Control Measures  
=====

Respiratory Protection: SCBA  
Ventilation: GOOD VENTILATION. FANS SHOULD BE EXPLOSION PROOF.  
Protective Gloves: CHEMICAL SAFETY GLOVES  
Eye Protection: CHEMICAL SAFETY GOGGLES. DO NOT WEAR CONTACT LENSES.  
Other Protective Equipment: EYE WASH APPARATUS AND SAFETY SHOWER.

=====  
Physical/Chemical Properties  
=====

Boiling Point: -82.2C, 180.F  
B.P. Text: 320 F  
Vapor Pres: 1  
Vapor Density: 4  
Spec Gravity: 1.2  
Evaporation Rate & Reference: NBUACET=1 0.4  
Solubility in Water: NEGLIGIBLE  
Appearance and Odor: FLUID PIGMENT COLORED LIQUID WITH CHARACTERISTIC ODOR  
Percent Volatiles by Volume: 75

=====  
Reactivity Data  
=====

Stability Indicator: YES  
Stability Condition To Avoid: DO NOT STORE IN CONTAINER OF ALUMINIUM, COPPER, ZINC  
Materials To Avoid: STRONG OXIDIZING AGENTS, STRONG ACIDS, STRONG BASES, ALKALI METALS, HALOGENS  
Hazardous Decomposition Products: CO, CO2, AROMATIC HYDROCARBONS VAPORS  
Hazardous Polymerization Indicator: NO

=====  
Other Information  
=====

Other Information: AS THE CONDITIONS OR METHODS OF USE ARE BEYOND OUR CONTROL WE DO NOT ASSUME ANY RESPONSIBILITY AND EXPRESSLY DISCLAIM ANY LIABILITY FOR ANY USE OF THE MATERIAL DESCRIBED IN THIS MSDS. INFORMATION CONTAINED HEREIN IS GIVEN IN GOOD FAITH AND BELIEVED TO BE TRUE AND ACCURATE BUT ALL STATEMENTS OR SUGGESTIONS ARE MADE WITHOUT WARRANTY.

ANTY, EXPRESSED OR IMPLIED,  
REGUARDING THE ACCURACY OF THE INFORMATION , THE HAZARDS CONNECTED WITH THE  
USE OF THE MATERIAL OR RESULTS TO BE OBTAINED FROM THE USE THEREOF.

=====  
HAZCOM Label  
=====

Product ID: 2023STRATA BLUE INK MARKING

Cage: 0HB89

Company Name: AMERICAN CODING AND MARKING INK CO

Street: 1220 NORTH AVENUE

City: PLAINFIELD NJ

Zipcode: 07062

Health Emergency Phone: 0000000000

Label Required IND: Y

Date Of Label Review: 04/05/2001

Status Code: A

Origination Code: G

Hazard And Precautions: INGESTION: SLIGHTLY IRRITATING TO GASTROINTESTIONAL  
TRACT. OR HIGHLY TOXIC. WILL CAUSE HEADACHE, DIARRHEA, DROWSINESS, BREATHING  
DIFFICULTIES, NAUSEA, VOMITING AND UNCONSCIOUSNESS. EYES: MODERATELY IR  
RITATING. CAUSE REDNESS, AND BLURRED VISION, BUT REVERSIBLE WITHIN SEVEN  
DAYS. SKIN: SLIGHTLY IRRITATING. PROLONGED OR WIDESPREAD CONTACT MAY LEAD TO  
DEFATTING OR DERMITITIS.

INHALATION: TOXIC OR MOD ERATELY IRRITATING TO NASAL  
AND RESPIRATORY TRACTS. CAN CAUSE HEADACHE, DIZZINESS, DROWSINESS, BREATHING  
DIFFICULTIES, NAUSEA, UNCONSCIOUSNESS.

=====  
Disclaimer (provided with this information by the compiling agencies): This  
information is formulated for use by elements of the Department of Defense.  
The United States of America in no manner whatsoever expressly or implied  
warrants, states, or intends said info  
rmation to have any application, use or  
viability by or to any person or persons outside the Department of Defense  
nor any person or persons contracting with any instrumentality of the United  
States of America and disclaims all liability for such use. Any person  
utilizing this instruction who is not a military or civilian employee of the  
United States of America should seek competent professional advice to verify  
and assume responsibility for the suitability of this information to th  
eir  
particular situation regardless of similarity to a corresponding Department  
of Defense or other government situation.