

AVEX ELECTRONICS CORP -- NICKEL-CADMIUM SEALED CELL BATTERY -- 6140-01-092-3553

=====  
Product Identification  
=====

Product ID:NICKEL-CADMIUM SEALED CELL BATTERY

MSDS Date:02/19/1999

FSC:6140

NIIN:01-092-3553

Status Code:A

MSDS Number: CLCSM

=== Responsible Party ===

Company Name:AVEX ELECTRONICS CORP

Address:1683 WINCHESTER ROAD

Box:1026

City:BENSALEM

State:PA

ZIP:19020-4510

Country:US

Info Phone

Num:215-638-1515

Emergency Phone Num:215-638-1515

CAGE:58414

=== Contractor Identification ===

Company Name:AVEX ELECTRONICS CORP

Address:1683 WINCHESTER ROAD

Box:1026

City:BENSALEM

State:PA

ZIP:19020-4510

Country:US

Phone:215-638-1515

Contract Num:SP0430-97-M-R122

CAGE:58414

=====  
Composition/Information on Ingredients  
=====

Ingred Name:CADMIUM (PRESENT AS CADMIUM, CADMIUM HYDROXIDE, CADMIUM OXIDE)

Minumum % Wt:8.

Maxumum % Wt:20.

OSHA PEL:0.2 MG/M3 CD DUST

ACGIH TLV:.01



HE SPILLED

MATERIAL AND PLACE IT IN A PLASTIC-LINED CONTAINER. HEPA VACUUMING IS PREFERRED. FLUSH SPILL AREA WITH WATER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:FOR A BROKEN OR DAMAGED BATTERY CLEANUP, WEAR NIOSH/MSHA APPROVED DUST MASKS OR RESPIRATORS, IMPERVIOUS GLOVES; AND SAFETY GLASSES OR GOGGLES.  
Other Precautions:KEEP CONTAINER CLOSED, AVOID CONTACT WITH CLOTHING, AVOID GENERATING DUST.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED DUSTS.  
Ventilation:LOCAL EXHAUST, MECHANICAL (GENERAL).  
Protective Gloves:IMPERVIOUS  
Eye Protection:SAFETY GLASSES/GOGGLES  
Other Protective Equipment:DO NOT WEAR CONTAMINATED CLOTHING HOME. SHOWER AND CHANGE OR WEAR COVERALLS.  
Work Hygienic Practices:KEEP FOOD AND TOBACCO AWAY FROM WORK AREA.  
Supplemental Safety and Health  
BOTH AVEX (P/N AV2012) & SAFT AMERICA (P/N 402037-005) MEET NSN REQUIREMENT. AVEX PROVIDED SAFT AMERICA PRODUCT.

=====  
===== Physical/Chemical Properties =====

HCC:Z5  
Boiling Pt:B.P. Text:NA  
Melt/Freeze Pt:M.P/F.P Text:NOT AVAILABLE  
Vapor Pres:NA  
Vapor Density:NA  
Spec Gravity:1.6

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
Stability Condition to Avoid:GENERAL STORAGE PROCEDURES FOR HAZARDOUS MATERIALS ARE ACCEPTABLE. AVOID SHORTING, USE ONLY APPROVED CHARGING METHODS

Hazardous Decomposition Products:METAL OXIDES FUMES MAY BE EVOLVED AT TEMPERATURES ABOVE MELTING POINT.

Conditions to Avoid Polymerization:DO NOT PUNCTURE BATTERY CASE.

=====  
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL LAWS. IF DISCARDED, TREAT AS HAZARDOUS WASTE.

=====  
===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.