

UNI-KEM INTERNATIONAL -- 506, V V-P-236A, PETROLATUM -- 9150-00-250-0933
===== Product Identification =====

Product ID:506, V V-P-236A, PETROLATUM

MSDS Date:01/10/1999

FSC:9150

NIIN:00-250-0933

Status Code:A

MSDS Number: CLCTJ

=== Responsible Party ===

Company Name:UNI-KEM INTERNATIONAL

Box:747

City:NEW ORLEANS

State:LA

ZIP:70004-0747

Country:US

Info Phone Num:504-835-7600

Emergency Phone Num:504

-835-7600

CAGE:UO115

=== Contractor Identification ===

Company Name:UNI-KEM INTERNATIONAL

Address:1001 HARIMAW COURT EAST

Box:City:METAIRIE

State:LA

ZIP:70001

Country:US

Phone:504-835-7600/FAX:504-835-7608

CAGE:4S446

Company Name:UNI-KEM INTERNATIONAL

Address:Box:747

City:NEW ORLEANS

State:LA

ZIP:70004-0747

Country:US

Phone:504-835-7600

CAGE:UO115

===== Composition/Information on Ingredients =====

Ingred Name:PETROLATUM (MSDS GAVE CAS# 8009-03-0 - INVALID CAS#)

CAS:8009-03-8

RTECS #:SE6780000

= Wt:100.

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NO DATA PROVIDED BY MANUFACTURER

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Health Hazards Acute and Chronic:ACUTE: NA CHRONIC: NA

Explanation of Carcinogenicity:NO DATA PROVIDED BY MANUFACTURER

Effects of Overexposure:EYE: IRRITANT.

Medical Cond Aggravated by Exposure:NO DATA PROVIDED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:(IF SYMPTOMS PERSIST, GET PROMPT MEDICAL ATTENTION)

INGESTION: CONTACT A PHYSICIAN IMMEDIATELY. INHALE: NOT APPLICABLE.

EYE: IRRITANT. FOR MOLTEN PRODUCT ONLY: IMMEDIATELY FLUSH WITH
PLENTY OF COOL WATER FOR AT LEAST 15 MINUTES. CALL A PHYSICIAN.

SKIN: IF BURNED BY CONTACT WITH HOT MATERIAL, COOL BURNED SKIN AREA
AS QUICKLY AS POSSIBLE BY IMMERSING IN COLD WATER OR APPLYING COLD
WATER; CALL A PHYSICIAN

. WASH THOROUGHLY AFTER HANDLING AS PRODUCT
IS NOT INTENDED FOR USE ON THE HUMAN BODY.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>204.4C, 400.F

Extinguishing Media:CO2 OR WATER FOG OR SAND/EARTH OR FOAM.

Fire Fighting Procedures:WEAR APPROVED SELF-CONTAINED BREATHING
APPARATUS. WATER SPRAY IS AN UNSUITABLE EXTINGUISHING AGENT.

Unusual Fire/Explosion Hazard:TOXIC GASES CAN BE PRODUCED IN FIRES OF
THIS PRODUCT AS WITH ALL
PETROLEUM DERIVATIVES.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SHUT OFF LEAK AND DIKE LARGE SPILLS. AFTER
COOLING AND SOLIDIFICATION, SCRAP AND/OR SHOVEL MATERIAL AND PLACE
IN SEPARATE CONTAINER. CLEAN AREA WITH AN OIL ABSORBENT MATERIAL
AND THEN PLACE USED ABSORBENT IN CLOSED CONTAINERS FOR DISPOSAL.
KEEP FROM SEWERS AND WATERWAYS.

Neutralizing Agent:NO DATA PROVIDED BY MANUFACTURER.

=====
===== Handling and Sto

rage =====

Handling and Storage Precautions:THIS PRODUCT IS EXCLUSIVELY FOR USE BY TRAINED PROFESSIONALS. BEFORE USE, READ LABEL AND MSDS. COMBUSTIBLE. KEEP AWAY FROM HEAT, SPARKS, HOT SURFACES AND OPEN FLAMES. USE WITH ADEQUATE VENTILATION AVO ID BREATHING MIST OR VAPOR. HARMFUL IF SWALLOWED.

Other Precautions:KEEP OUT OF REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE.

Ventilation:UNDER NORM

AL USE CONDITIONS,NO ABSORPTION THROUGH SKIN, BY INHALATON OR OTHER ROUTE OF ENTRY INTO THE HUMAN BODY IS ANTICIPATED.

Protective Gloves:HEAT PROTECTIVE IMPERVIOUS GLOVES WHEN HANDLING MOLTEN PRODUCT

Eye Protection:CHEMICAL SAFETY GOGGLES, AND IF HANDLED HOT, FULL FACE SHIELD

Other Protective Equipment:COVERALLS WHEN HANDLING MOLTEN PRODUCT.

Work Hygienic Practices:DO NOT EAT, DRINK OR USE TOBACCO IN AREA. WASH HANDS, FACE AND EXPOSED SKIN THOROUGHLY AFTER USE AND BEFORE EATIN

G,
DRINKING OR USING TOBACCO, COSMETICS AND TOILET. WASH WORK APPAREL BEFORE REUSE.

Supplemental Safety and Health

NO DATA PROVIDED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:NA

Vapor Pres:NA

Vapor Density:NA

Spec Gravity: