

DEXTER CORP THE HYSOL DIV -- EPK 608 PART B -- 8040-00-092-2816

=====
Product Identification
=====

Product ID:EPK 608 PART B

MSDS Date:10/05/1998

FSC:8040

NIIN:00-092-2816

Status Code:A

MSDS Number: CLGDQ

=== Responsible Party ===

Company Name:DEXTER CORP THE HYSOL DIV

Address:1 DEXTER DRIVE

City:SEABROOK

State:NH

ZIP:03874

Country:US

Info Phone Num:603-474-5541

Emergency Phone Num:1-800-424-9300

Preparer's Name:ERNEST CARTER

Chemtrek Ind/Phone:(800)424-9300

CAGE:1JB33

=== Contractor Identification ===

Company Name:DEXTER CORP THE HYSOL DIV

Address:1 DEXTER DR

Box:City:SEABROOK

State:NH

ZIP:03874

Country:US

Phone:603-474-5541/FAX: 603-474-5545

CAGE:1JB33

=====
Composition/Information on Ingredients
=====

Ingred Name:2,4,6-TRIS.(.(DIMETHYLAMINO)METHYL.).PHENOL

CAS:90-72-2

RTECS #:SN3500000

Minumum % Wt:5.

Maxumum % Wt:10.

ACGIH TLV:5PPM

Ingred Name:MERCAPTAN-TERM

INATED POLYMER
Minumum % Wt:70.
Maxumum % Wt:90.

Ingred Name:SILICA
CAS:112945-52-5
Code:F
RTECS #:VV7310000
Minumum % Wt:1.
Maxumum % Wt:10.
OSHA PEL:20MMPCF
ACGIH TLV:10MG/M3

Ingred Name:ETHYLENE GLYCOL
CAS:107-21-1
RTECS #:KW2975000
Minumum % Wt:1.
Maxumum % Wt:2.
ACGIH STEL:C127 MG/M3;C50 PPM
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE
Health Hazards Acute and Chronic:NONE
Explanation of Carcinogenicity:NON
E
Effects of Overexposure:CAN CAUSE EYE IRRITATION. PROLONGED OR REPEATED
CONTACT CAN CAUSE SKIN IRRITATION. CAN BE IRRITATING TO THE
RESPIRATORY SYSTEM. CAN CAUSE GASTROINTESTINAL IRRITATION.
Medical Cond Aggravated by Exposure:NONE

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS
OPEN. SEEK MEDICAL ATTENTION. SKIN: FLUSH WITH AFFECTED AREA WITH
WATER FOR 15 MINUTES. REMOVE CONTAMINATED C
LOTHING. WASH SKIN
THOROUGHLY WITH SOAP AND WATER. DO NOT APPLY GREASES OR OINMENTS.
CONTAMINATED LEATHER WEAR SHOULD BE DISCARDED. SEEK MEDICAL
ATTENTION. INHALATION: REMOVE TO FRESH AIR AND PROVIDE OXYGEN IF
BREATHING IS DIFFICUL T. INGESTION: IF CONSCOUS, GIVE LARGE
QUANTITIES OF WATER. SEEK MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:=157.2C, 315.F
Autoignition Temp:Autoignition Temp Text:NO

NE
Lower Limits:NONE
Upper Limits:NONE
Extinguishing Media:DRY CHEMICAL OR HALON FIRE EXTINGUISHER, OR WATER
SPRAY, FOAM OR FOG.
Fire Fighting Procedures:USE SELF CONTAINED BREATHING APPARATUS WHEN
FIGHTING FIRES IN CONFINED AREAS.
Unusual Fire/Explosion Hazard:DENSE SMOKE AND TOXIC GASSES MAY BE
LIBERATED.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE CLOTHING, GLOVES AND SAFETY
GLASSES. SCRAPE UP OR SHOVEL INTO DO
T APPROVED WASTE CONTAINERS.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE. KEEP AWAY
FROM OPEN FLAMES AND HIGH TEMPERATURES. CONTAINERS, EVEN THOSE THAT
HAVE BEEN EMPTIED, CAN CONTAIN HAZARDOUS PRODUCT RESIDUES. HANDLE
IN ACCORDANCE WITH THE HAZAR D POTENTIAL OF CURING AGENT USED.
Other Precautions:HEATING THE RESIN ABOVE 300 DEG. F IN THE PRESENCE OF
AIR MAY CAUSE SLOW OX
IDATIVE DECOMPOSITION ABOVE 500 DEG. F
POLYMERIZATION MAY OCCUR.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE
Ventilation:LOCAL EXHAUST RECOMMENDED.
Protective Gloves:PROTECTIVE GLOVES IMPERVIOUS PLASTIC OR RUBBER.
Eye Protection:SAFETY GLASSES OR GOGGLES.
Other Protective Equipment:AVOID CONTACT WITH EYES. WEAR SAFETY GLASSES
OR GOGGLES AS APPROPRIATE AVOID PROLONGED ORREPEATED CONTACT WITH
SKIN. WEAR CHEMICAL-RESISTANT GLOVES AND
OTHER CLOTHING AS REQUIRED
TO MINIMIZE CONTACT.
Work Hygienic Practices:NONE
Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

Boiling Pt:=120.C, 248.F
Melt/Freeze Pt:M.P/F.P Text:NONE
Decomp Temp:Decomp Text:NONE
Vapor Pres:(MM HG)
Vapor Density:AIR=1
Spec Gravity:1.2
Appearance and Odor:AMBER, LOW VISCOSITY LIQUID, PUNGENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Av

oid:YES

NONE

Stability Condition to Avoid:DO NOT HEAT OVER 200 DEGREES C.

Hazardous Decomposition Products:MALEIC ANHYDRIDE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:WASTE DISPOSAL MAY BE MORE RESTRICTIVE OR OTHERWISE DIFFERENT FROM FEDERAL LAWS AND REGULATIONS. CONSULT STATE AND LOCAL REGULATIONS REGARDING PROPER DISPOSAL OF THIS MATERIAL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.