

PRATT AND LAMBERT INC -- ENAMEL: LUSTERLESS, QUICK DRY, STYRENATED ALKYD,YELLOW
33538 -- 8010-00-297-2112

=====
Product Identification
=====

Product ID:ENAMEL: LUSTERLESS, QUICK DRY, STYRENATED ALKYD,YELLOW 33538

MSDS Date:06/29/1999

FSC:8010

NIIN:00-297-2112

Status Code:A

MSDS Number: CLGRL

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-10

27

Country:US

Info Phone Num:216-566-2902

Emergency Phone Num:216-566-2917

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
Composition/Information on Ingredients
=====

Ingred Name:V.M.&P. NAPHTHA

CAS:64742-89-8

Code:F

= Wt:29.

OSHA PEL:300 PPM

ACGIH TLV:300

Ingred Name:TOLUENE

CAS:108-88-

3

RTECS #:XS5250000

= Wt:5.

OSHA PEL:SEE TABLE Z-2

ACGIH TLV:188 MG/M3;50 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:XYLENE

CAS:1330-20-7

RTECS #:ZE2100000

= Wt:1.

OSHA PEL:100

ACGIH TLV:434 MG/M3;100 PPM

ACGIH STEL:651 MG/M3;150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:2-METHYL-1-PROPANOL

CAS:78-83-1

RTECS #:NP9625000

= Wt:4.

OSHA PEL:300 MG/M3;100 PPM

ACGIH TLV:152 MG/M3;50 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:COBALT 2-ETHYLHEXANOATE (1:2

)

CAS:136-52-7

= Wt:.2

Ingred Name:N-BUTYL ACETATE

CAS:123-86-4

RTECS #:AF7350000

= Wt:2.

OSHA PEL:710 MG/M3;150 PPM

ACGIH TLV:713 MG/M3;150 PPM

ACGIH STEL:950 MG/M3;200 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:QUARTZ

CAS:14808-60-7

RTECS #:VV7330000

= Wt:.4

OSHA PEL:SEE TABLE Z-3

ACGIH TLV:0.1 MG/M3

Ingred Name:CRISTOBALITE

CAS:14464-46-1

RTECS #:VV7325000

= Wt:4.

OSHA PEL:SEE TABLE Z-3

ACGIH TLV:0.05 MG/M3

Ingred Name:TALC

CAS:14807-96-6

RTECS #:WW2710000

:SEE TABLE Z-3
ACGIH TLV:2 MG/M3

Ingred Name:LEAD CHROMATE
CAS:1344-37-2
Code:F
= Wt:18.
OSHA PEL:0.05MG/M3
ACGIH TLV:0.05

Ingred Name:LEAD (AS PB)
= Wt:12.02
OSHA PEL:0.05MG/M3
ACGIH TLV:0.15

Ingred Name:CHROMIUM VI (AS CR)
= Wt:2.56
ACGIH TLV:0.05

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE
Health Hazards Acute and Chronic:EXPOSURE MAY BE BY INHALATION AND/OR
SKIN OR EYE CONTACT, DEPENDING ON CONDITIONS OF USE. TO MINIMIZE
EXPOSURE,
FOLLOW RECOMMENDATIONS FOR PROPER USE, VENTILATION, AND
PERSONAL PROTECTIVE EQUIPMENT.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION OF EYES, SKIN AND RESPIRATORY
SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME OVEREXPOSURE
MAY RESULT IN UNCONSCIOUSNESS AND POSSIBLY DEATH.
Medical Cond Aggravated by Exposure:MAY CAUSE ALLERGIC SKIN REACTION IN
SUSCEPTIBLE PERSONS OR SKIN SENSITIZATION.

=====
===== First Aid Measures =====
=====

First Aid:IF INHALED: REMOVE FROM EXPOSURE. RESTORE BREATHING. IF ON
SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER. IF IN
EYES: FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. IF
SWALLOWED: GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:=6.7C, 44.F
Autoignition Temp:Autoignition Temp Text:NONE
Lower Limits:0.9
Upper Limits:10.9
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL,

FOAM.

Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.

Neutralizing Agent:NONE

===== Handling and Storage =====

=====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE. TRANSFER ONLY TO APPROVED CONTAINERS WITH COMPLETE AND APPROPRIATE LABELING. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

Other Precautions:DO NOT APPLY ON TOYS AND OTHER CHILDREN'S ARTICLES, FURNITURE, OR ANY INTERIOR SURFACE OF A DWELLING OR FACILITY WHICH MAY BE OCCUPIED OR USED BY CHILDREN. DO NOT APPLY ON ANY EXTERIOR SURFACE OF DWELLING UNITS, SUCH AS WINDOW SILLS, PORCHES, STAIRS, OR RAILINGS TO WHICH CHILDREN MAY BE COMMONLY EXPOSED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR.

Ventilation:LOCAL EXHAUST PREFERABLE. GENERAL EXHAUST ACCEPTABLE IF THE EXPOSURE TO MATERIALS IN SECTION 11 IS MAINTAINED BELOW APPLICABLE EXPOSURE LIMITS.

Protective Gloves:WEAR GLOVES WHICH ARE RECOMMENDED BY GLOVES.

Eye Protection:WEAR SAFETY SPECTACLES WITH UNPERFORATED SIDE SHIELDS.

Other Protective Equipment:USE BARRIER CREAM ON EXPOSED SKIN.

Work Hygienic Practices:NONE

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:222-325 F

Melt/Freeze Pt:M.P/F.P Text:NONE

Decomp Temp:Decomp Text:NONE

Vapor Density:HEAVIER

Spec Gravity:1.19

VOC Pounds/Gallon:507

VOC Grams/Liter:4.23

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:NONE

=====

== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

NONE

Stability Condition to Avoid: NONE

Hazardous Decomposition Products: CARBON DIOXIDE, CARBON MONOXIDE,
OXIDES OF METALS IN SECTION 11.

Conditions to Avoid Polymerization: WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods: WASTE MUST BE TESTED FOR IGNITABILITY AND
EXTRACTABILITY TO DETERMINE THE APPLICABLE EPA HAZARDOUS WASTE
NUMBER

S. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED
CONTAINER. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL
REGULATIONS REGARDING POLLUTION.

===== Regulatory Information =====

State Regulatory Information: CALIFORNIA PROPOSITION 65: THIS PRODUCT
CONTAINS

CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO
CAUSE CANCER AND BIRTH DEFECTS OR OTHER
REPRODUCTIVE HARM. TSCA CERTIFICATION. ALL
CHEMICALS IN THIS PRODUCT ARE LISTED, OR ARE EXEMPT
FROM LISTING, ON THE TSCA INVENTORY.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.