

PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY -- POLYSULFIDE RUBBER
COMPOUND PR1775 B-2 BASE COMPOUND -- 8030-01-370-2160

=====
Product Identification
=====

Product ID:POLYSULFIDE RUBBER COMPOUND PR1775 B-2 BASE COMPOUND

MSDS Date:08/05/1996

FSC:8030

NIIN:01-370-2160

Status Code:A

MSDS Number: CLJLY

==== Responsible Party ====

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES C
OMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-240-2060

Emergency Phone Num:(800)424-9300

Preparer's Name:HENRY SIMMONS

Chemtrec Ind/Phone:(800)424-9300

CAGE:83574

==== Contractor Identification ====

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

=====
Composition/Information on Ingredients
=====

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

< Wt:5.

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:CALCIUM CARBONATE @ LIMESTONE

CAS:1317-65-3

RTECS #:EV9580000

= Wt:30.

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:ETHYL ACETATE

CAS:141-78-6

RTECS #:AH5425000

< Wt:5.

OSHA PEL:1400 MG/M3;400 PPM

:109159-22-0

Ingred Name:SILICA DERIVATIVES
CAS:67762-90-7

Ingred Name:PHSPHATE SALT

===== Hazards Identification =====

Effects of Overexposure:ETHYL ACETATE EYES: MAY CAUSE BURNING, TEARING, REDDENING, POSSIBLE TRANSIENT CORNEAL INJURY. SKIN: PROLONGED EXPOSURE MAY CAUSE DRYING AND CRACKING OF SKIN. POSSIBLE DERMATITIS. INHALATION: DROWSI NESS, HEADACHE, NAUSEA, DIZZINESS AND UNCONSCIOUSNESS. MAY CAUSE LIVER OR KIDNEY DAMAGE. INGESTION: MAY CAUSE FLUSHING HEADACHE, DIZZINESS, MENTAL DEPRESSION, NAUSEA, VOMITING NARCOSIS

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES. IF SYMPTOMS PERSIST, CONSULT A PHYSICIAN. SKIN:WASH WITH SOAP AND WATER. DO NOT USE SOLVENTS. CONSULT PHYSICIAN. INHALATION:REMOVE TO FRESH AIR. IF SYMPTOMS ARE PRESENT CONSULT A PHYSICIAN. INGESTION. CONSULT A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:>71.1C, 160.F
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER.
Fire Fighting Procedures:USE AIR SUPPLIED RESPIRATOR. USE WATER TO COOL HEAT EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:HIGH TEMPERATURE MAY CAUSE PRESSURE BUILDUP IN CLOSED CONTAINERS..

===== Accidental Release Measures =====

Spill Release Procedures:COVER WITH ABSORBANT. SCOOP INTO CONTAINERS. CLEAN-UP RESIDUE WITH A SUITABLE SOLVENT.

=====

==== Handling and Storage =====

Handling and Storage Precautions:WASH THOROUGHLY AFTER HANDLING AND BEFORE SMOKING OR EATING. AVOID INGESTION. EMPTY DRUMS MAY CONTAIN EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEAR DRUM. VAPORS OF THIS PRODUCT ARE HEAVIER THAN AIR AND MAY COLLECT IN LOW OR CONFINED AREAS.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:WHEN APPLYING IN ANY CIRCUMSTANCES LIKELY TO PRODUCE

AIRBORNE LEVEL OF HAZARDOUS INGREDIENTS IN EXCESS OF TLV, USE A VAPOR CARTRIDGE OR AIR-SUPPLIED RESPIRATOR.

Ventilation:GENERAL VENTILATION TO MAINTAIN VAPORS BELOW TLV.

Protective Gloves:SOLVENT RESISTANT GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:KEEP CONTAINERS TIGHTLY CLOSED. DO NOT STORE ABOVE 120 DEG F. GROUNDING AND BONDING PROCEDURE SHOULD BE FOLLOWED WHEN TRANSPORTING THIS MATERIAL.

Supplemental Safety and Health

==== Physical/Chemical Properties =====

Boiling Pt:=77.2C, 171.F

B.P. Text:171-350

Vapor Density:>AIR

Spec Gravity:1.48

VOC Pounds/Gallon:132

Evaporation Rate & Reference:> N-BUTYL ACETATE

Appearance and Odor:WHITE PASTE

Percent Volatiles by Volume:6.9%

==== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

INORGANIC ACIDS AND OXIDIZING AGENTS

Stability Condition to Avoid:NOT KNOWN

Hazardous Decomposition Products:OXIDES OF CARBON AND NITROGEN

EN, SULFUR
DIOXIDE, TRACES OF HYDROGEN SULFIDE

===== Disposal Considerations =====

Waste Disposal Methods: NOT A HAZARDOUS WASTE ACCORDING TO EPA
REGULATIONS. CONSULT STATE REGULATIONS
PRIOR TO DISPOSAL TO DISPOSAL OF SPILLAGE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.