

ADVANCED CHEMISTRY & TECHNOLOGY -- AC-236 CLASS A BASE -- 8030-00-723-5343

=====  
Product Identification  
=====

Product ID:AC-236 CLASS A BASE

MSDS Date:06/22/2000

FSC:8030

NIIN:00-723-5343

Status Code:A

Kit Part:Y

MSDS Number: CLKHV

=== Responsible Party ===

Company Name:ADVANCED CHEMISTRY & TECHNOLOGY

Address:7341 ANACONDA AVE

City:GARDEN GROVE

State:CA

ZIP:92841-2921

Country:US

Info Phone Num:71

4-373-2837

Emergency Phone Num:(800)424-9300

Preparer's Name:HENRY SIMMONS

Chemtec Ind/Phone:(800)424-9300

CAGE:1DWR5

=== Contractor Identification ===

Company Name:ADVANCED CHEMISTRY & TECHNOLOGY

Address:7341 ANACONDA AVE

Box:City:GARDEN GROVE

State:CA

ZIP:92841-2921

Country:US

Phone:714-373-2837

CAGE:1DWR5

=====  
Composition/Information on Ingredients  
=====

Ingred Name:LIMESTONE

CAS:1317-65-3

RTECS #:EV9580000

= Wt:38.5

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:CALC

IUM CARBONATE  
CAS:471-34-1  
RTECS #:FF9335000  
= Wt:3.

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR2275000  
= Wt:2.5  
OSHA PEL:15 MG/M3  
ACGIH TLV:10 MG/M3

Ingred Name:FORMALDEHYDE  
CAS:50-00-0  
RTECS #:LP8925000  
&lt; Wt:.1  
OSHA PEL:SEE 1910.1048  
ACGIH STEL:C0.37 MG/M3;C0.3 PPM  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

Ingred Name:TOLUENE  
CAS:108-88-3  
RTECS #:XS5250000  
= Wt:13.  
OSHA PEL:SEE TABLE Z-2  
ACGIH TLV:188 MG/M3;50 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

=====  
Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:LIVER, KIDNEYS, NERVOUS SYSTEM, EYES.  
SKIN

Effects of Overexposure:EYE CONTACT: CAUSES SEVERE IRRITATION. CAN  
CAUSE BURNING SENSATION, TEARING, AND REDNESS. SKIN CONTACT: MAY  
CAUSE SLIGHT TO MILD IRRITATION. PROLONGED OR REPEATED CONTACT MAY  
DRY THE SKIN AND LEAD TO IRRITATION (I.E. DERMATITIS) MAY BE  
ABSORBED THROUGH THE SKIN. INHALATIO

N (BREATHING): IRRITATION TO

THE MOUTH, THROAT, AND STOMACH. CAN CAUSE DIZZINESS, HEADACHES, AND INCOORDINATION, NAUSEA, VOMITING, AND STOMACH UPSET CAN OCCUR.

INGESTION (SWALLOWING): IRRITATION TO THE MOUTH, THROAT, AND STOMACH. MAY CAUSE NAUSEA, VOMITING, PAIN, AND STOMACH UPSET (E.G. DIARRHEA). CAN CAUSE DIZZINESS, FAINTNESS, HEADACHE, AND INCOORDINATION.

Medical Cond Aggravated by Exposure:NERVOUS SYSTEM, SKIN

===== First Aid Measures =====

=====

First Aid:EYE CONTACT: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

SKIN CONTACT: IMMEDIATELY FLUSH WITH WATER. REMOVE CONTAMINATED CLOTHING AND SHOES. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

PROFESSIONALLY WASH CLOTHING AND SHOES BEFORE RE-USE. INHALATION (BREATHING): REMOVE TO FRESH AIR. IF SYMPTOMS DEVELOP, SEEK

IMMEDIATE MEDICAL ATTENTION. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. INGESTION (SWALLOWING): SEEK MEDICAL ATTENTION:

IMMEDIATELY INDUCE VOMITING, AS DIRECTED BY MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:>32.8C, 91.F

Extinguishing Media:SMALL FIRES: DRY CHEMICAL, CARBON DIOXIDE, HALON, WATER SPRAY, OR FOAM. LARGE FIRES: WATER SPRAY, FOG, OR ALCOHOL FOAM.

Fire Fighting Procedures:FIRE FIGHTERS AND OTHERS WHO MAY BE EXPOSED TO

THE PRODUCTS OF COMBUSTION SHOULD BE EQUIPPED WITH NIOSH-APPROVED POSITIVE PRESSURE SELF-CONTAINED BREATHING APPARATUS (SCBA) AND FULL PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:DURING A FIRE, IRRITATING AND HIGHLY

TOXIC GASES MAY BE GENERATED DURING COMBUSTION OR DECOMPOSITION. HIGH TEMPERATURES CAN CAUSE CONTAINERS TO RUPTURE. COOL WITH WATER.

===== Accidental Release Measures =====

Spill Release Pr

cedures: ISOLATE HAZARD AREA. KEEP UNNECESSARY AND UNPROTECTED PERSONNEL FROM ENTERING. SAFETY STOP DISCHARGE. CONTAIN MATERIAL, AS NECESSARY, WITH A DIKE OR BARRIER. STOP MATERIAL FROM CONTAMINATING SOIL, OR FROM ENTERING SEWERS OF BODIES OF WATER. APPROPRIATE SAFETY MEASURES AND PROTECTIVE EQUIPMENT SHOULD BE USED. USE SUPPLIED AIR RESPIRATOR OR SELF-CONTAINED BREATHING APPARATUS IN ENCLOSED SPACES.

=====**Handling and Storage**=====

Handling and Storage Precautions: STORE IN COOL, DRY, WELL VENTILATED AREA AWAY FROM HEAT, IGNITION SOURCES, AND DIRECT SUNLIGHT. KEEP CONTAINERS TIGHTLY CLOSED. TRANSFER- NO SPECIAL PRECAUTIONS ARE NEEDED. FOLLOW GOOD MANUFACTURING AND HANDLING PRACTICES.

Other Precautions: THIS CONTAINER CAN BE HAZARDOUS WHEN EMPTY. FOLLOW LABEL WARNINGS EVEN AFTER CONTAINER IS EMPTIED SINCE EMPTY CONTAINERS MAY RETAIN PRODUCT RESIDUES. DO NOT REUSE EMPTY CONTAINER WITHOUT PROFESSIONAL CLEANING FOR FOOD, CLOTHING, OR PRODUCTS FOR HUMAN OR ANIMAL CONSUMPTION OR WHERE SKIN CONTACT CAN OCCUR.

=====**Exposure Controls/Personal Protection**=====

Respiratory Protection: AVOID BREATHING VAPOR OR MIST. WEAR NIOSH/MSHA-APPROVED EQUIPMENT. DETERMINE THE APPROPRIATE TYPE BY CONSULTING THE RESPIRATOR MANUFACTURER. HIGH AIRBORNE CONCENTRATION MAY NECESSITATE THE USE OF SELF-CONTAINED BREATHING APPARATUS (SCBA) OR A SUPPLIED AIR RESPIRATOR. RESPIRATORY PROTECTION

PROGRAMS MUST BE IN COMPLIANCE WITH 29 CFR 1910.134

Ventilation: LOCAL EXHAUST VENTILATION WHEN VAPORS, MISTS, OR DUSTS CAN BE RELEASED IN EXCESS OF ESTABLISHED AIRBORNE EXPOSURE LIMITS (TLV'S OR PEL'S)

Protective Gloves: WEAR PROTECTIVE CLOTHING AND APPROPRIATE IMPERVIOUS GLOVES.

Eye Protection: WEAR CHEMICAL SPLASH GOGGLES OR SAFETY GLASSES WITH SIDE SHIELDS.

Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING, DRINKING, SMOKING

NG, AND USING RESTROOM FACILITIES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Spec Gravity:1.31

VOC Pounds/Gallon:183

VOC Grams/Liter:1.5

Solubility in Water:INSOLUBLE

Appearance and Odor:OFF-WHITE PASTE AND SULFIDE ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZERS, REDUCERS, STRONG BASES, ACIDS

Stability Condition to Avoid:HIGH TEMPERATURES

Hazardous Decompos

ition Products:SMOKE, SOOT, AND TOXIC/IRRITATING

FUMES (I.E., CARBON DIOXIDE, CARBON MONOXIDE, ETC). FORMALDEHYDE AND/OR OTHER ALDEHYDES. OXIDES OF SULFUR, HYDROGEN SULFIDE, LOW MOLECULAR WEIGHT HYDROCARBONS.

===== Toxicological Information =====

Toxicological Information:LIMESTONE REPEATED EXPOSURE TO DUST CAN LEAD TO PARTICULATE IN THE LUNGS (I.E., PNEUCONIOSIS). CAN CONTAIN TRACE AMOUNTS OF CRYSTALLINE SILICA AS AN IMPURITY. TOLUENE ORAL LD5

0

5,000 MG/KG DERMAL L D50 RABBIT 12,124 MG/KG INHALATION LC50

5,320 PPM/8-HOURS CALCIUM CARBONATE: REPEATED EXPOSURE TO DUSTS CAN LEAD TO PARTICULATE IN THE LUNGS (I.E., PNEUCONIOSIS).

TITANIUM DIOXIDE: IN A 2 YEAR STUDY, AN INCREASE IN BENIGN AND MALIGNANT LUNG TUMORS WERE OBSERVED AT 250-MG/M3 RESPIRABLE DUST LEVEL. THIS LEVEL IS 50 TIMES THE CURRENT OCCUPATIONAL EXPOSURE LEVEL AND IS NOT EXPECTED TO CORRELATE TO HUMAN EXPOSURES.

FORMALDEHYDE:

=====

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF ACCORDING TO APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS OF THE METHODS OF DISPOSAL CURRENTLY AVAILABLE, IT IS RECOMMENDED THAT AN ALTERNATIVE BE ACCORDING OR THE FOLLOWING ORDER OF PREFERENCE. BASED UPON ENVIRONMENTAL ACCEPTABILITY. (1) RECYCLE OR REWORK, IF FEASIBLE; (2) INCINERATE AT AN AUTHORIZED FACILITY.

===== Regulatory Information =====

====

SARA Title III Information:SARA TITLE III - SECTION 311/312 HAZARD  
CATEGORIES: FIRE, ACUTE AND CHRONIC HAZARD. SARA  
SECTION 302 EXTREMELY HAZARDOUS MAT FORMALDEHYDE SARA SECTION 313  
TOXIC CHEMICALS TOLUENE FORM ALDEHYDE

Federal Regulatory Information:UNITED STATES CHEMICAL COMPONENTS THIS  
PRODUCT ARE ON THE SECTION 8(B) CHEMICAL SUBSTANCE INVENTORY LIST  
(40 CFR 710) TSCA: SECTION 8(D) DATA REPORTING RULE TOLUENE

State Regulatory Information:STATE RIGHT TO KNOW  
PENNSYLVANIA-NEW

JERSEY R-T-K LIMESTONE 1317-65-3 38.5% TOLUENE ENVIRONMENTAL  
HAZARD 108-88-3 13.0% CALCIUM CARBONATE 474-34-1 3% TITANIUM  
DIOXIDE 13463-67-7 2.2% FORMALDEHYDE 50-00-0