View NSN Online: https://aerobasegroup.ae/nsn/6750-01-319-5407

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS -- 847 1484, PT B, KODAK EKTACOLOR RA BLEACH FIX (SEE SUPPL) -- 6750-01-319-5407

Product ID:847 1484, PT B, KODAK EKTACOLOR RA BLEACH FIX (SEE SUPPL) MSDS Date:05/01/2000 FSC:6750 NIIN:01-319-5407 Status Code:A Kit Part:Y MSDS Number: CLKWL === Responsible Party === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CON TRACTS Address:343 STATE ST City:ROCHESTER State:NY ZIP:14650-1115 Country:US Info Phone Num:716-722-5151/(800) 242-2424 Emergency Phone Num:716 722-5151 Preparer's Name:NOT PROVIDED CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 Contract Num:SP0500-96-D-9413N375 CAGE:19139 Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 Contract Num:SP0500-96-D-9413N385 CAGE:19139 Ingred Name:WATER CAS:7732-18-5 RTECS #: ZC0110000

Minumum % Wt:70. Maxumum % Wt:75. Code:F Code:F

Ingred Name:AMMONIUM FERRIC ETHYLENEDIAMINETETRAACETIC ACID CAS:21265-50-9 Minumum % Wt:20. Maxumum % Wt:25. ROVIDED

Ingred Name: ACETIC ACID CAS:64-19-7 RTECS #:AF1225000 Minumum % Wt:1. Maxumum % Wt:5. Other REC Limits:NOT PROVIDED OSHA PEL:25 MG/M3:10 PPM ACGIH TLV:25 MG/M3;10 PPM ACGIH STEL:37 MG/M3;15 PPM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS LD50 LC50 Mixture:NOT PROVIDED Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EFFECTS OF EXPOSURE: GENERAL: CONTAINS: AMMONIUM FERRIC ETHYLEN EDIAMINETETRAACETIC ACID. THIS COMPOUND CAN CHELATE METALS AND MAY ALTER CALCIUM AND OTHER CATION BALANCES. INHALATION: LOW HAZARD FOR US UAL INDUSTRIAL HANDLING BY TRAINED PERSONNEL. EYES: NO SPECIFIC HAZARD KNOWN. MAY CAUSE TRANSIENT IRRITATION. SKIN: LOW HAZARD FOR USUAL INDUSTRIAL HANDLING BY TRAINED PERSONNEL. INGESTION: EXPECTED T O BE A LOW INGESTION HAZARD. Explanation of Carcinogenicity:CARCINOGENICITY CLASSIFICATION (COMPONENTS PRESENT AT 0.1% OR MORE): - IN TERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC): NONE - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS (ACGIH): NON E - NATIONAL TOXICOLOGY PROGRAM (NTP): NONE - OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA): NONE Effects of Overexposure: EYES: MAY CAUSE TRANSIENT IRRITATION. Medical Cond Aggravated by Exposure:NOT PROVIDED

First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. TREAT SY

MPTOMATICALLY. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES: ANY MATERIAL THAT CONTACTS THE EYE SHOULD BE WASHED OUT IMMEDIATELY WITH WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. SKIN: WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. WASH CONTAMINATED CLOTHING BEFORE REUSE. DESTROY OR THOROUGHLY CLEAN CONTAMINATED SHOE S. INGESTION: DRINK 1-2 GLASSES OF WATER. SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

==

Flash Point:NONE

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE (CO2), DRY CHEMICAL, ALCOHOL FOAM.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS.

Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: FLUSH TO SEWER WITH LARGE AMOUN T OF WATER. OTHERWISE, ABSORB SPILL WITH VERMICULITE OR OTHER INERT MATERIAL, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE THOROUGHLY TO REMOVE RESIDUAL C ONTAMINATION. Neutralizing Agent: NOT PROVIDED

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED. KEEP AWAY FROM INCOMPATIBLE SUBSTANCES. KEEP FROM CONTACT WITH OXIDIZING MATERIALS.
Other Precautions:AVOID BREATHING VAPOR AT CON
CENTRATIONS GREATER THAN
THE EXPOSURE LIMITS. AVOID CONTACT WITH EYES AND PROLONGED OR
REPEATED CONTACT WITH SKIN. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HAND LING.

Respiratory Protection: IF ENGINEERING CONTROLS DO NOT MAINTAIN AIRBORNE CONCENTRATIONS BELOW RECOMMENDED EXPOSURE LIMITS, AN APPROVED RESPIRATOR MUST BE WORN. RESPIRATOR: FULL-FACE ORGANIC VAPOR CARTRIDGE. A RESPIRATOR SHO ULD

BE WORN IF HAZARDOUS DECOMPOSITION PRODUCTS ARE LIKELY TO BE OR HAVE BEEN RELEASED. RESPIRATOR: ACID GAS. ASSURE COMPLIANCE W/OSHA STANDARD 29 CFR 1910.134 Ventilation: USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO MAINTAIN AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS. Protective Gloves: FOR PROLONGED OR REPEATED SKIN CONTACT, IMPERVIOUS GLOVES SHOULD BE WORN. Eye Protection: WEAR SAFETY GLASSES WITH SIDE SHIELDS (OR GOGGLES). Other P rotective Equipment: EYE BATH, WASHING FACILITIES, SAFETY SHOWER. Work Hygienic Practices: IT IS A GOOD INDUSTRIAL HYGIENE PRACTICE TO MINIMIZE EYE CONTACT. IT IS A GOOD INDUSTRIAL HYGIENE PRACTICE TO MINIMIZE SKIN CONTACT. Supplemental Safety and Health CONTD FROM PRODUCT ID: AND REPLENISHER. THIS IS A KIT. THE OTHER MSDS SERIAL NUMBER: CLKYF.

HCC:N1 NRC/State Lic Num:NOT RELEVANT Boiling Pt:>100.C, 212.F Melt/Fre eze Pt:M.P/F.P Text:NOT PROVIDED Decomp Temp:Decomp Text:NOT PROVIDED Vapor Pres:68F: 24MBAR (18 MM HG) Vapor Density:0.6 Spec Gravity:1.10 pH:5.6 Viscosity:NOT PROVIDED Evaporation Rate & amp; Reference: NOT PROVIDED Solubility in Water:COMPLETE Appearance and Odor: REDDISH-BROWN LIQUID. SLIGHT AMMONIA ODOR. Percent Volatiles by Volume:70-75 WT Corrosion Rate:NOT PROVIDED

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZI

| NG AGENTS, BASES, SODIUM HYPOCHLORITE (BLEACH). |
|--|
| Stability Condition to Avoid:NOT PROVIDED |
| Hazardous Decomposition Products: AMMONIA, CHLORAMINE, CARBON DIOXIDE, |
| CARBON MONOXIDE, OXIDES OF NITROGEN |

Toxicological Information:EFFECTS OF EXPOSURE: GENERAL: CONTAINS: AMMONIUM FERRIC ETHYLENEDIAMINETETRAACETIC ACID. THIS COMPOUND CAN CHELATE METALS AND MAY ALTER CALCIUM AND OTHER CATION BALANCES. INHALATION: LOW HAZARD

FOR US UAL INDUSTRIAL HANDLING BY TRAINED PERSONNEL. EYES: NO SPECIFIC HAZARD KNOWN. MAY CAUSE TRANSIENT IRRITATION. SKIN: LOW HAZARD FOR USUAL INDUSTRIAL HANDLING BY TRAINED PERSONNEL. INGESTION: EXPECTED T O BE A LOW INGESTION HAZARD.

Ecological:THE FOLLOWING PROPERTIES ARE ESTIMATED FROM THE COMPONENTS OF THE PREPARATIONS. POTENTIAL TOXICITY: FISH LC50 MG/L: >100.
DAPHNID EC50 MG/L: >100. ALGAL
IC50 MG/L: >100. ORGANICS
READILY DEGRAD ABLE (>70%): YES (14 DAYS). POTENTIAL
BIOACCUMULATION: LOG POW 100.

Waste Disposal Methods:DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE, OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE AMOUNT OF WATER.

Transport Information:FOR TRANSPORTATION INFORMATION REGARDING THIS PRODUCT CA

LL THE KODAK WORLDWIDE TRANSPORTATION HAZMAT HOT LINE: (716) 722-2400 BETWEEN 8 A.M. AND 5 P.M. (EASTERN STANDARD TIME), MONDAY THROUGH FR IDAY.

SARA Title III Information:CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OR TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) OF 1986 AND 40 CFR PART 372: NONE Federal Regulatory Information:NOT PROVIDED State Regula

tory Information:MATERIAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER: NONE - MATERIAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE ADVERSE REPRODUCTIVE EFFECTS: NONE

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants t

his information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.