

DEXTER CORPORATION ADHESIVE & COATING SYSTEMS -- HYSOL EA 956 PART A --
8040-00-463-7042

===== Product Identification =====

Product ID:HYSOL EA 956 PART A

MSDS Date:04/09/1994

FSC:8040

NIIN:00-463-7042

Status Code:A

Kit Part:Y

MSDS Number: CLMJJ

=== Responsible Party ===

Company Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS

Address:2850 WILLOW PASS ROAD

Box:312

City:BAY POINT

State:CA

ZIP:94

565-3299

Country:US

Info Phone Num:202-483-7616

Emergency Phone Num:800-424-9300

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:33564

=== Contractor Identification ===

Company Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS

Address:2850 WILLOW PASS ROAD

Box:312

City:BAY POINT

State:CA

ZIP:94565-3299

Country:US

Phone:202-483-7616

CAGE:33564

===== Composition/Information on Ingredients =====

Ingred Name:EPOXY POLYMER PROPRIETARY

Minimum % Wt:40.

Maximum

% Wt:70.

Ingred Name:4-GLYCIDYLOXY-N,N-DIGLYCIDYL-ANILINE

CAS:5026-74-4

Code:F

RTECS #:RR0504000

Minumum % Wt:30.

Maxumum % Wt:60.

=====
Hazards Identification
=====

Effects of Overexposure:BRIEF CONTACT MAY IRRITATE THE SKIN OR CAUSE A RASH. REPEATED OR PROLONGED SKIN CONTACT RESULT IN ALLERGIC SENSITIZATION.

Medical Cond Aggravated by Exposure:SKIN SENSITIZATION.

=====
First Aid Measures
=====

First Aid:EYE: F

LUSH EYES WITH WATER FOR 15 MINUTES. SKIN: WASH SKIN

THOROUGHLY WITH SOAP AND WATER. INHALATION: REMOVE VICTIM TO FRESH AIR. INGESTION: DRINK PLENTY OF WATER.

=====
Fire Fighting Measures
=====

Extinguishing Media:DRY CHEMICAL, OR HALON FIRE EXTINGUISHER, OR WATER SPRAY, FOAM OR FOG.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING , SUCH AS TURN-OUT GEAR. CARTRIDGE RESPIRATORS DO NOT PROVIDE AD EQUATE PROTECTION FOR FIRE FIGHTERS OR EXOTHERM MITIGATION.

Unusual Fire/Explosion Hazard:MAY LIBERATE LARGE QUANTITIES OF DENSE FOUL-SMELLING SMOKE WHICH MAY CONTAIN UNIDENTIZIED TOXIC GASSES.

=====
Accidental Release Measures
=====

Spill Release Procedures:SCRAPE UP OR SHOVEL INTO DOT APPROVED WASTE CONTAINERS.

=====
Handling and Storage
=====

Handling and Storage Precautions:REFRIGERATED STORAGE IS RECOMMENDED TO

MAINTAIN PRODUCT QUALITY. THIS PRODUCT MAY BE STORED AT 40 DEG.F FOR UP TO 12 MONTHS.

Other Precautions:DO NOT CUT, GRIND, WELD, OR DRILL ON OR NEAR THIS CONTAINER.

=====
===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL EXHAUST VENTILATION.

Protective Gloves:WEAR BUTYL RUBBER, PVC, OR NITRILE RUBBER GLOVES.

Eye Protection:WEAR SAFETY GLASSES WITH SIDE SHIELDS OR CHEMICAL GOGGLES.

Other Protective Equipment:AN EYEWASH AND SAFETY SHOWER SHOULD BE

NEARBY AND READY FOR USE.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

Vapor Pres:MMHG: NIL

Vapor Density:AIR=1:>1

Spec Gravity:WATER=1: 1.25

VOC Pounds/Gallon:10

Viscosity:P: 5000-9000

Solubility in Water:NEGLIGIBLE

Appearance and Odor:AMBER LIQUID WITH SLIGHT ODOR

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG LEWIS OR MINERAL ACIDS.

Stabil

ity Condition to Avoid:AVOID MIXING RESIN (PART A) AND CURING

AGENT (PART B) IN BATCHES GREATER THAN 1 POUND UNLESS YOU PLAN TO USE IMMEDIATELY. DO NOT HEAT MIXED ADHESIVE ABOVE 125 DEG.F .

Hazardous Decomposition Products:CO, NOX, ALDEHYDES, ACIDS AND UNDETERMINED ORGANICS.

Conditions to Avoid Polymerization:MAY OCCUR.

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL AS A WASTE, THIS MATERIAL, AS A WASTE, IS NOT CONSIDERED A R

CRA HAZARDOUS WASTE, HOWEVER, INCINERATION IN
AN EPA APPROVED WASTE INCINERATOR IS A PREFERRED DISPOSAL PRACTICE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent profes
sional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.