View NSN Online: https://aerobasegroup.ae/nsn/3439-00-727-5947

INWELD MFG CORP -- 2% THORIATED TUNGSTEN ELECTRODES -- 3439-00-727-5947

Product ID:2% THORIATED TUNGSTEN ELECTRODES MSDS Date:07/01/2001 FSC:3439 NIIN:00-727-5947 Status Code:A MSDS Number: CLNTD === Responsible Party === Company Name: INWELD MFG CORP Address:3962 PROTLAND ST Box:40 City:COPLAY State:PA ZIP:18037-0040 Country:US Info Phone Num:610-261-1900 Emergen cy Phone Num:800-346-5368 CAGE:66376 === Contractor Identification === Company Name: BLACK AND CO Address:5351 W MINNESOTA ST Box:UNKNOW **City:INDIANAPOLIS** State:IN ZIP:46241 Country:US Phone:317-243-8676 Contract Num:SP0490-00-D-4063 CAGE:00WU8 Company Name: INWELD MFG CORP Address: 3962 PORTLAND ST Box:40 City:COPLAY State:PA ZIP:18037-0040 Country:US Phone:610-261-1900 CAGE:66376

Ingred Name:TUNGSTEN CAS:7440-33-7 RTECS #:YO71 75000 = Wt:98. ACGIH TLV:5 MG/M3 ACGIH STEL:10 MG/M3

Ingred	Name:THORIUM
= Wt:2	

Reports of Carcinogenicity:NTP:UNKNOWN IARC:UNKNOWN OSHA:NO Health Hazards Acute and Chronic: ELECTRIC SHOCK AND BURNS. RADIANT ENERGY CAN PRODUCE "FLASH" BURNS OF EYES AND SKIN. GASES, FUMES, AND DUST OVEREXPOSURE CAN CAUSE PERSONAL INJURY. NOISE OVEREXPOSURE CAN DAMAGE HEARING. Effects of Overexposure:SYMPTOMS WILL VARY ACCORDIN G TO THE PROCESS AND ITS APPLICATION. NOISE OVEREXPOSURE CAN DAMAGE HEARING. GASES, FUMES AND DUST OVEREXPOSURE CAN CAUSE PERSONAL INJURY. BURNS, REDNESS. First Aid: ELECTRIC SHOCK AND BURNS: DEACTIVATE POWER. ADMINISTER CPR AS REQUIRED. COVER BURNS WITH STERILE DRESSING, CALL A PHYSICIAN. Extinguishing Media: WILL NOT BURN USE WATER TO COOL. Fire Fighting Procedures:NONE CURRENTLY KNOWN. Unusual Fire/Explosion Hazard:NONE CURRENTLY KNOWN. Spill Release Procedures: CLEAN OFF AND USE. Handling and Storage Precautions: ARCS AND SPARKS DURING USE COULD BE THE SOURCE OF IGNITION OF COMBUSTIBLE MATERIALS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:D

EPENDS ON USE, CONDITION, AND LOCATION. USE ADEQUATE VENTILATION OR PERSONAL RESPIRATORY PROTECTION.
Ventilation:LOCAL VENTILATION RECOMMENDED. SEE OSHA 29CFR1910.252 & ANSI Z49.1. IN CONFINED AREAS LOCAL EXHAUST IS ESSENTIAL.
Protective Gloves:WELLDING GLOVES RECOMMENDED.
Eye Protection:SAFETY SPECTACLES OR WELDING GOGGLES.
Other Protective Equipment:SEE ANSI Z49.1, WELDING HELMET, FLAME RETARDANT CLOTHING RECOMMENDED. SEE AWS C5.3.
Supplemental Safety and Health

Physical/Chemical Properties ===============

HCC:N1

Boiling Pt:B.P. Text:ND Melt/Freeze Pt:=618.C, ######F Vapor Pres:NA Vapor Density:NA Spec Gravity:APPROX: 1.80 pH:NA Viscosity:NA Evaporation Rate & amp; Reference:NA Solubility in Water:NA Appearance and Odor:SILVER SOLID, NO ODOR. Percent Volatiles by Volume:NA

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:ELEVATED T
EMPERATURES IN AN OXIDIZING
ENVIRONMENT.
Hazardous Decomposition Products:N/P BY MFR. HMIS: WELDING FUMES
(OXIDES OF METALS) AND GASES SUCH AS OZONE, CARBON MONOXIDE, CARBON DIOXIDE, NITROGEN OXIDES?MAY BE FORMED.

Waste Disposal Methods:NORMAL, ENVIRONMENTALLY ACCEPTABLE, INDUSTRIAL WASTE DISPOSAL, LAND FILL, BURIAL, ETC. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (pro

vided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.