

LOCTITE CORPORATION -- REMOVABLE THREADLOCKER 242, IN 24231

=====  
MSDS Safety Information  
=====

FSC: 8030  
NIIN: 01-014-5869  
MSDS Date: 05/01/1995  
MSDS Num: CLNYZ  
Product ID: REMOVABLE THREADLOCKER 242, IN 24231  
MFN: 01  
Responsible Party  
Cage: 05972  
Name: LOCTITE CORPORATION  
Address: 1001 TROUT BROOK CROSSING  
City  
: ROCKY HILL CT 06067-3910  
Info Phone Number: 860-571-5100  
Emergency Phone Number: 203-571-5100  
Preparer's Name: ERNEST CARTER  
Chemtrec IND/Phone: (800)424-9300  
Review Ind: Y  
Published: Y

=====  
Contractor Summary  
=====

Cage: 05972  
Name: LOCTITE CORPORATION  
Address: 1001 TROUT BROOK CROSSING  
City: ROCKY HILL CT 06067-3910  
Phone: 860-571-5100

=====  
Item Description Information  
=====

Item Manager: GSA  
Item Name: SEALING COMPOUND  
Specification Number: MIL-S-16163  
Type/Grade/Class: 2 TYPE,N GRADE  
Unit of Issue: BT  
Quantitative Expression: 00000000050CC  
UI Container Qty: 0  
Type of Container: BOTTLE

=====  
Ingredients  
=====

Cas: 25852-47-5  
Name: POLYGLYCOL DIMETHACRYLATE  
% low Wt: 60.  
% high Wt:

65.

-----  
Cas: 9004-96-0  
RTECS #: MD0880000  
Name: POLYGLYCOL OLEATE  
% low Wt: 25.  
% high Wt: 30.  
-----

Cas: 81-07-2  
RTECS #: DE4200000  
Name: SACCHARIN  
% low Wt: 3.  
% high Wt: 5.  
EPA Rpt Qty: 100 LBS  
DOT Rpt Qty: 100 LBS  
-----

Cas: 80-15-9  
RTECS #: MX2450000  
Name: CUMENE HYDROPEROXIDE  
% low Wt: 1.  
% high Wt: 3.  
EPA Rpt Qty: 10 LBS  
DOT Rpt Qty: 10 LBS  
-----

Cas: 67-56-1  
RTECS #: PC1400000  
Name: METHYL  
ALCOHOL  
% low Wt: 1.  
% high Wt: 3.  
OSHA PEL: 260 MG/M3;200 PPM  
ACGIH TLV: 262 MG/M3;200 PPM  
ACGIH STEL: 328 MG/M3;250 PPM  
EPA Rpt Qty: 5000 LBS  
DOT Rpt Qty: 5000 LBS  
-----

Cas: 112945-52-5  
RTECS #: VV7310000  
Name: SILICA, AMORPHOUS TREATED  
% low Wt: 1.  
% high Wt: 3.  
-----

Cas: 613-48-9  
Name: N,N-DIALKYL TOLUIDINES  
% low Wt: .1  
% high Wt: 1.  
-----

Cas: 13463-67-7  
RTECS #: XR2275000  
Name: TITANIUM DIOXIDE  
% low Wt: .1  
% high

Wt: .5  
OSHA PEL: 15 MG/M3  
ACGIH TLV: 10 MG/M3  
ACGIH STEL: NOT ESTABLISHED

=====  
Health Hazards Data  
=====

LD50 LC50 Mixture: LD50 10000 MG/KG. LD50 5000 MG/KG.  
Skin: YES  
Effects of Exposure: MILD EYE IRRITANT.  
Signs And Symptions Of Overexposure: MAY CAUSE DERMATITIS ON PROLONGED CONTACT IN SENSITIVE INDIVIDUALS.  
First Aid: INGESTION: DO NOT INDUCE VOMITING. KEEP INDIVIDUAL CALM. OBTAIN MEDICAL ATTENTION.  
SKIN CONTACT: WASH THOROUGHLY WITH SOAP AND WATER.OBTAIN MEDICAL ATTENTION.EYE CONTACT: FLUSH AT LEAST 15 MINUTES WITH WATER. OBTAIN MEDICAL ATTENTION.

=====  
Handling and Disposal  
=====

Spill Release Procedures: SOAK UP IN AN INERT ABSORBENT. STORE IN A PARTLY FILLED, CLOSED CONTAINER UNTIL DISPOSAL.  
Waste Disposal Methods: INCINERATE FOLLOWING EPA AND LOCAL REGULATIONS.  
Handling And Storage Precautions: SAFE STORAGE: STORE BELOW 100 F. HANDLING: AVOID PROLONGED SKIN CONTACT. KEEP AWAY FROM EYES.

=====  
Fire and Explosion Hazard Information  
=====

Flash Point Method: TCC  
Flash Point: >93.3C, 200.F  
Extinguishing Media: CARBON DIOXIDE, FOAM, DRY CHEMICAL.

=====  
Control Measures  
=====

Protective Gloves: NEOPRENE, RUBBER, OR BUTYL RUBBER GLOVES.  
Eye Protection: SAFETY GLASSES OR GOGGLES.

=====  
Physical/Chemical Properties  
=====

Boiling Point: =148.9C, 300.F  
Vapor Pres: LESS THAN 5MM AT 80 F  
Spec Gravity: 1.1 AT 75 F  
VOC Grams/Liter: 146  
Solubility in Water: SLIGHT  
Appearance and Odor: BLUE LIQUID MILD ODOR

Reactivity Data

=====  
Stability Indicator: YES

Hazardous Decomposition Products: IRRITATING VAPORS, OXIDES OF CARBON.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: WILL NOT OCCUR.  
=====

HAZCOM Label

=====  
Product ID: REMOVABLE THREADLOCKER 242, IN 24231

Cage: 05972

Company Name: LOCTITE CORPORATION

Street: 1001 TROUT

BROOK CROSSING

City: ROCKY HILL CT

Zipcode: 06067-3910

Health Emergency Phone: 203-571-5100

Label Required IND: Y

Date Of Label Review: 10/23/2001

Status Code: A

Origination Code: G

Hazard And Precautions: MILD EYE IRRITANT.  
=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied

warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsi

bility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.