View NSN Online: https://aerobasegroup.ae/nsn/6505-00-133-8025

Product ID:PETROLEUM JELLY, PN-011 MSDS Date:07/21/1997 FSC:6505 NIIN:00-133-8025 Status Code:A MSDS Number: CLPCG === Responsible Party === Company Name: HUMCO HOLDING GROUP, INC. Address:7400 ALUMAX DRIVE **City:TEXARKANA** State:TX ZIP:75501 Country:US Info Phone Num:903-831-7808 **Emergency Pho** ne Num:800-424-9300 Chemtrec Ind/Phone:(800)424-9300 CAGE:TO364 === Contractor Identification === Company Name: HUMCO HOLDING GROUP, INC Address:7400 ALUMAX DRIVE Box:City:TEXARKANA State:TX ZIP:75501 Country:US Phone:903-831-7808 CAGE:TO364

Ingred Name:PETROLEUM WHITE U.S.P. CAS:8009-03-8 RTECS #:SE6780000 Other REC Limits:NONE OSHA PEL:5MG/M3 OIL MIST TWA ACGIH TLV:NONE

======== Hazards Identification =======

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:POTENTIAL HEALTH HAZARDS: SKIN: NON-IRRITATING. EYES: MAY BE SLIGHTLY IRRITATING TO THE EYES. INHALATION: OIL MIST CONCENTRATION OF 50 MG/M3 CAN CAUSE SHORTNESS OF BREATH, COUGHING OR WHEEZING. INGEST ION: INGESTION OF A LARGE DOES MAY HAVE A LAXATIVE EFFECT AND CAUSE CRAMPS AND DIARRHEA. RISK OF ASPIRATION. Explanation of Carcinogenicity:NO INGREDIENTS LISTED IN THIS SECTION.

Medical Cond Aggravated by Exposure:PRE-EXISTING EYE, SKIN AND RESPIRATORY DISORDERS AND ASTHMA.

First Aid:SKIN: IN CASE OF SKIN CONTACT REMOVE CONTAMINATED CLOTHING, WASH AFFECTED AREA WITH SOAP AND WATER. EYE: IN CASE OF EYE CONTACT, IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER, KEEPING EYELIDS WIDE OPEN. INHALATION: IF OIL MIST INHALED REMOVE PATIENT TO FRESH AIR. IF NOT BREATHING GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, OXYGEN CAN BE GIVEN BY A QUALIFIED OPERATOR. INGESTION: IF SWALLO WED, DO NOT INDUCE VOMITING UNLESS ADVISED BY A PHYSICIAN DUE TO RISK OF ASPIRATION. GET PROMPT MEDICAL ATTENTION.

Flash Point Method:COC Flash Point:=204.4C, 400.F Extinguishing Media:SMALL FIRE: USE CARBON DIOXIDE OR DRY CHEMICAL. LARGE FIRE: USE ALC OHOL FOAM. NOTE: NORMAL FIRE FIGHTING FOAMS THAT ARE SUITABLE FOR GASOLINE OR HYDROCARBON (FIRE/EXPLOSION HAZARD.) Fire Fighting Procedures:USE NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT . USE WATER TO KEEP FIRE EXPOSED TANKS AND CONTAINERS COOL. WATER OR FOAM MAY CAUSE FROTHING OF MOLTEN MATERIA L. DO NOT ENTER FIRE AREA WITHOUT PROPER PERSONAL PROTECTIVE EQUIPMENT TO INCLUDE A SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosio

n Hazard:DENSE SMOKE MAY BE GENERATED WHEN BURNING. EXTINGUISHING MEDIA (CON'T): FIRES WILL BREAK DOWN AND WILL NOT EXTINGUISH FIRES. WATER SPRAY WILL REDUCE THE INTENSITY OF THE FLAMES.

Spill Release Procedures: ALWAYS WEAR THE PROPER PERSONAL PROTECTIVE EQUIPMENT. ISOLATE THE SPILL AREA AND CONTAIN. ONLY TRAINED PERSONNEL FITTED WITH THE PROPER PERSONAL PROTECTIVE EQUIPMENT SHOULD BE ALLOWED TO ENTER

THE SPI LL SITE. COLLECT THE SPILL IN A WASTE CONTAINER FOR DISPOSAL. FLUSH THE SPILL AREA THOROUGHLY WITH WATER. SPILL CAN CAUSE VERY SLICK SURFACES!

Handling and Storage Precautions:DO NOT STORE ABOVE 120F (49C) KEEP AWAY FROM SOURCES OF INGNITION AND OXIDIZING MATERIALS. ALWAYS USE IN A WELL VENTILATED AREA. Other Precautions:KEEP AWAY FROM CHILDREN!

Respiratory Protection:USE A NIOSH-APPROVED RESPIRATOR APPROPRIATE FOR THE EXPOSURE OF CONCERN . IF SURROUNDING ATMOSPHERE CONTAINS AN OIL MIST OF 50 MG/M3 OR GREATER THEN A FULL FACE AIR SUPPLIED RESPIRATOR IS RECOMM ENDED.

Ventilation: ALWAYS USE IN A WELL-VENTILATED AREA. Protective Gloves: IMPERVIOUS GLOVES FOR PROLONGED OR HOT EXPOSURES . Eye Protection: ANSI APPROVED CHEMICAL SAFETY GOGGLES . (SUPP SFTY) Other Protective Equipment: EYE WASH AND DELUGE SHOWER MEETING A NSI

DESIGN CRITERIA . APRON AND SLIP RESISTANT WORK BOOTS IF CLEANING LARGE SPILLS.

Work Hygienic Practices: FOLLOWING GENERALLY RECOGNIZED SAFETY PRACTICES AND SOUND WORK METHODS SHOULD BE USED WHEN HANDLING THIS PRODUCT IN LARGE OR SMALL QUANTITIES.

Supplemental Safety and Health

EYE PROTECTION (CON'T) : NONE NEEDED WHEN USED IN JELLY FORM. IF IN LIQUID FORM USE CHEMICAL GOGGLES.

Boiling Pt:=343.3C, 650.F

Vapor Pres:1 MMHG @ 20C Vapor Density:1 (AIR=1) Spec Gravity:0.86 (H2O=1) Evaporation Rate & amp; Reference:NONE Solubility in Water:INSOLUBLE Appearance and Odor:YELLOWISH, TRANSLUCENT JELLY. ODOR: NONE.
======================================
 Stability Indicator/Materials to Avoid:YES AVOID STRONG OXIDIZING AGENTS. Stability Condition to Avoid:NORMALLY STABLE. KEEP AWAY FROM HEAT, SPARKS AND FLAME. Hazardous Decomposition Products:CARBON MONOXIDE, WTER VAPOR AND
UNIDENTIFIED ORGANIC COMPOUNDS.
======================================
Toxicological Information:N/P.
======================================
Ecological:N/P.
======================================
Waste Disposal Methods:DISPOSE ACCORDING TO FEDERAL, STATE AND LOCAL REGULATIONS.
======================================
Transport Information:N/P.
===== Regulatory Information ====================================
SARA Title III Information:N/P. Federal Regulatory Information:N/P. State Regulatory Information:N/P.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whats

oever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.