View NSN Online: https://aerobasegroup.com/nsn/8010-01-418-7646

## SHERWIN-WILLIAMS CO THE -- QUIK-MARK INVERTED MARKING PAINTS-4 -- 8010-01-418-7646

============ Product Identification ==============

Product ID:QUIK-MARK INVERTED MARKING PAINTS-4

MSDS Date:08/17/1998

FSC:8010

NIIN:01-418-7646

Status Code:A

MSDS Number: CLRQZ === Responsible Party ===

Company Name: SHERWIN-WILLIAMS CO THE

Address: 101 PROSPECT AVE NW

City:CLEVELAND

State:OH

ZIP:44115-1042

Country:US Info Phone Nu

m:216-566-2902/216-566-2917

Emergency Phone Num:216-566-2917 Preparer's Name:ERNEST CARTER Chemtrec Ind/Phone:(800)424-9300

CAGE:54636

=== Contractor Identification ===

Company Name: SHERWIN-WILLIAMS CO THE

Address:101 PROSPECT AVE NW

Box:City:CLEVELAND

State:OH

ZIP:44115-1042

Country:US

Phone:800-251-2486/216-566-2242

CAGE:54636

======= Composition/Information on Ingredients ========

Ingred Name:PROPANE

CAS:74-98-6

RTECS #:TX2275000

= Wt:13.

OSHA PEL:1800 MG/M3;1000 PPM

Ingred Na

me:BUTANE CAS:106-97-8

RTECS #:EJ4200000

= Wt:12.

ACGIH TLV:1900 MG/M3;800 PPM

Ingred Name: V.M.& P. NAPHTHA

CAS:64742-89-8

Code:F = Wt:7.

OSHA PEL:300 PPM OSHA STEL:400 PPM

ACGIH TLV:3>0

Ingred Name: TOLUENE

CAS:108-88-3

RTECS #:XS5250000

= Wt:10.

OSHA PEL:SEE TABLE Z-2 ACGIH TLV:188 MG/M3;50 PPM

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: ACETONE

CAS:67-64-1

RTECS #:AL3150000

= Wt:20.

OSHA PEL:2400 MG/M3;1000 PPM ACGIH TLV:1780 MG/M3;750 PPM ACGIH STEL:2380 MG/M3;1000 PPM

EPA Rpt Qt y:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:CALCIUM CARBONATE

= Wt:25.

========== Hazards Identification ===============

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Health Hazards Acute and Chronic:EXPOSURE MAY BE BY INHALATION AND/OR SKIN OR EYE CONTACT, DEPENDING ON CONDITIONS OF USE. TO MINIMIZE EXPOSURE, FOLLOW RECOMMENDATIONS FOR PROPER USE, VENTILATION, AND PERSONAL PROTECTIVE EQUIPMENT.

Effects of Overexposure: IRRITATION OF EYES, SKIN AND RESP

## **IRATORY**

SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME OVEREXPOSURE MAY RESULT IN UNCONSCIOUSNESS AND POSSIBLY DEATH. HEADACHE, DIZZINESS, NAUSEA, AND LOSS OF CO ORDINATIONS OF EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MISTS. REDNESS AND ITCHING OR BURNING SENSATION MAY INDICATE EYE OR EXCESSIVE SKIN EXPOSURE.

Medical Cond Aggravated by Exposure: NONE RECOGNIZED.

First Aid:IF INHALED: REMOVE FROM EXPOSURE

. RESTORE BREATHING, KEEP WARM

AND QUIET. IF ON SKIN: WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER.REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE RE-USE. IF IN EYE S: FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES.GET MEDICAL ATTENTION. IF SWALLOWED: DO NOT INDUCE VOMITING. GIVE SEVERAL GLASSES OF WATER. SEEK MEDICAL ATTENTION

========== Fire Fighting Measures ================

Flash Point Method: PMCC Flash Point: