

FISKE BROTHERS REFINING CO -- LUBRIPLATE NO. 100, 105, 107, 110, NO. 115 -- 9150-00-140-4434

=====
Product Identification
=====

Product ID:LUBRIPLATE NO. 100, 105, 107, 110, NO. 115

MSDS Date:01/01/2000

FSC:9150

NIIN:00-140-4434

Status Code:A

MSDS Number: CLSHN

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

City:TOLEDO

State:OH

ZIP:43605

Country:US

Info

Phone Num:419-691-2491

Emergency Phone Num:(800) 255-3924 CHEM-TEL

Preparer's Name:JAMES R. KONTAK

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

Company Name:SDB CONSULTANTS LTD

Address:401 WHITNEY AVE SUITE 120

Box:City:GRETNA

State:LA

ZIP:70056

Country:US

Phone:504-366-9105

Contract Num:SP0450-02-M-L394

CAGE:0PGK2

=====
Composition/Information o

n Ingredients =====

Ingred Name:NON-HAZARDOUS

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:THRESHOLD LIMIT VALUE 5MG/M3 FOR OIL
MIST IN AIR OSHA REGULATION 29 CFR 1910.1000.

Effects of Overexposure:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE
SKIN IRRITATION. PRODUCT CONTACTING THE EYES MAY CAUSE EYE
IRRITATION. HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON. AS A

PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS, MISTS AND FUMES SHOULD BE
MINIMIZED. THIS PRODUCT HAS A LOW ORDER OF ACUTE ORAL TOXICITY, BUT
MINUTE AMOUNTS ASPIRATED INTO THE LUNGS DURING INGESTION MAY CAUSE
MILD TO SEVERE PULMONARY INJURY.

===== First Aid Measures =====

First Aid:EYE: FLUSH WITH CLEAR WATER FOR 15 MINUTES OR UNTIL
IRRITATION SUBSIDES. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.

SKIN: REMOVE ANY CONTAMINATED CLOTHING
AND WASH WITH SOAP AND WARM

WATER. IF INJECTED BY HIGH PRESSURE UNDER SKIN, REGARDLESS OF THE
APPEARANCE OR ITS SIZE, CONTACT A PHYSICIAN IMMEDIATELY. DELAY MAY
CAUSE LOSS OF AFFECTED PART OF THE BODY. INHALATION: VAPOR PRESSURE
IS VERY LOW AND INHALATION AT ROOM TEMPERATURE IS NOT A PROBLEM.
IF OVERCOME BY VAPOR FROM HOT PRODUCT, IMMEDIATELY REMOVE FROM
EXPOSURE AND CALL A PHYSICIAN. INGESTION: IF INGESTED, CALL A
PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

==
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:182.2C, 360.F

Lower Limits:0.9%

Upper Limits:7.0%

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE OR WATER SPRAY
(FOG).

Fire Fighting Procedures:COOL EXPOSED CONTAINERS WITH WATER. USE
AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED OR CONFINED SPACES.

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS.
EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GR

IND, OR WELD,
AS THEY MAY EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE, WASH REMAINDER WITH SUITABLE
PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCTS OUT OF
SEWERS AND WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED
OR MAY ENTER SEWER S AND WATER COURSES.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN N
OT IN

USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG
OXIDANTS.

Other Precautions:REMOVE OIL-SOAKED CLOTHING AND LAUNDER BEFORE REUSE.
CLEANSE SKIN THOROUGHLY AFTER CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED.

Ventilation:LOCAL EXHAUST: USED TO CAPTURE FUMES AND VAPORS.

Protective Gloves:USE OIL-RESISTANT GLOVES, IF NEEDED.

Eye Protection:IF CHANCE OF EYE CONTACT, WEAR GOGGLES.

Other Protect

ive Equipment:USE OIL-RESISTANT APRON, IF NEEDED.

Supplemental Safety and Health

PRODUCT NAME OR NUMBER : LUBRIPLATE NO. 100, NO. 105, NO. 107, NO. 110,
NO. 115 . FORMULA: CALCIUM SOAP, MINERAL OIL AND ADDITIVES.

GENERIC/CHEMICAL NAME: PETROLEUM LUBRICATING GREASE. USDA
AUTHORIZAT ION: H-2.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:>287.8C, 550.F

Melt/Freeze Pt:M.P/F.P Text:SEMI-SOLID

Vapor Pres:5

Spec Gravity:0.89 - 0.93

Evaporation Rat

e & Reference: